

Luja Universal Primer

DESCRIPTION Acrylic primer for use as part of the Luja Hygiene system. Forms a tight moisture resistant primer film and provides a solid base for subsequent finishing coats of Luja 7, 20 or 40. Ideal for use in humid and wet environments.

Acrylic primer for use as part of the Luja hygiene system. Forms a tight moisture resistant primer film and provides a solid base for subsequent finishing coats of Luja 7, 20 or 40. Ideal for use in humid and wet environments.




PRODUCT FEATURES

For priming and finishing concrete, filler treated, brick, cardboard, chipboard and wood fibre board surfaces. Also adheres well to previously painted clean dispersion, alkyd, epoxy and acid catalyzed paint surfaces.



RECOMMENDED USES Interior walls and ceilings. Suitable as a primer for Luja finishing paints and Tikkurila interior acrylate paints. Also under wallpapers.

TECHNICAL DATA



Base paints AP
Colour Range White. Can be tinted to light shades from Tikkurila Symphony colour collection. Use only half of the colourant amount given in the formula. Colour accuracy is not perfect.
Gloss grade Full-matt
Coverage Non-absorbent surfaces 7 - 10 m²/l. Absorbent surfaces 5 - 8 m²/l.
Can sizes 0,9 l, 2,7 l, 9 l, 18 l.
Thinner Water
Application method Brush, roller or spray. For airless spray application, use a nozzle 0.015" - 0.021"
Thinning: 0 - 10 vol-%

Drying time at 23°C and 50% relative air humidity Dry to touch in half an hour. Re-coatable after 2 hours.

Wet scrub resistance SFS-EN 13300 class II, ISO 11998

Chemical resistance Resists cleaning detergents and weak solvents, e.g. White Spirit.

Heat resistance 85°C, ISO 4211-3.

Solids volume 36 %.

Density 1.4 kg/l, ISO 2811.

Storage Protect from frost.

Product code 219_0201




Luja Universal Primer

APPLICATION DETAILS

Application conditions	The surface to be painted must be dry, the temperature of the air at least +5°C, and the relative humidity of the air below 80 %.
Preparation	Unpainted surfaces: Remove all dirt and dust. Fill the surfaces with a suitable Presto filler and sand the dried surface. Remove sanding dust. Previously painted surfaces: Wash down previously painted surfaces with Cleaning Agent (Maalipesu) and rinse carefully with water. Fill holes and cracks with a suitable Presto filler and sand the dried surface. Remove sanding dust.
Painting	Stir Luja Universal Primer well before use and thin with water, if necessary. Apply by brush, roller or spray. Finish the surface with Luja Finishing Paint, Remontti-Ässä or Ässä finishing paint.
Cleaning of tools	Clean tools with water. Use of Tikkurila Pensselipesu (Tool Cleaner) is recommended when cleaning a bit hardened paint from the brush. Clean the surfaces with neutral (pH 6-8) detergent with soft brush, sponge or cloth at the earliest 1 month after painting. Follow the dilution instructions of the detergent manufacturer. The surface may not remain wet after the cleaning.
Maintenance instructions	Be careful with the painted surfaces during few weeks time, because the paint will achieve its final hardness and durability in normal conditions after 1 month. If the surfaces must be cleansed soon after painting, cleanse them lightly with a damp cleaning cloth.
EU VOC 2004/42/	(cat A/g) 30g/l(2010)
EC-limit value	Luja Universal Primer contains VOC max. 30 g/l

HEALTH AND SAFETY

LABELLING according to Regulation (EC) No. 1272/2008	The product is not classified as dangerous. A Safety Data Sheet is available on request.  Safety data sheet
--	--

ENVIRONMENTAL and WASTE DISPOSAL Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations. [Ympäristöseloste](#)

TRANSPORT VAK/ADR -
ser070415 / garta181214 / pih101214 / ome040609 / 2190201
