



## NATURAL OIL WOODSTAIN EFFECT

Twice as much coverage through high oil content – saves time and money!



1140  
Agate-Silver  
on Spruce



1142  
Graphite-Silver  
on Spruce



1143  
Onyx-Silver  
on Spruce



### PRODUCT DESCRIPTION

Transparent, satin wood protective finish with metallic effects based on natural oils for any wood in the exterior.

Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent and extremely weather-resistant and UV-stable surface does not crack, peel, flake or blister.

No sanding necessary, just simply recoat; no primer is needed.

Easy and seamless application. Finish stays workable while coating.

Finish contains active ingredients to protect against mould, algae and fungal attack and has proven itself over decades, and also under extreme climatic conditions.

### RECOMMENDED USE

Osmo Natural Oil Woodstain is ideal for all wood in outdoor areas: doors, windows and window shutters (dimensionally stable elements), carports, timber cladding, balconies, fences, pergolas, garden furniture and summer houses (dimensionally unstable elements).

### INGREDIENTS

Based on natural plant oils (sunflower oil, soya oil, thistle oil and linseed oil), iron oxide and organic pigments, titanium dioxide white pigment, effect pigments, siccatives (drying agents) and additives. Biocidal active ingredient: Propiconazole. Dearomatized white spirit (benzene-free). EU limit value for this product (cat. A/e): 400 g/l VOC (2010). This product contains max. 400 g/l VOC.

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.97-1.0 g/cm<sup>3</sup>

Viscosity: 43-60s DIN EN ISO 2431/4 mm, viscid

Odour: faint/mild, after drying odourless

Flash point: 55°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%).

Osmo Natural Oil Woodstain Effect is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works.

If possible, please apply the first coat to all sides before installation.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat.

### METHODS OF APPLICATION

With Osmo Flat Brush or Osmo Microfibre Roller, apply thinly along the wood grain and spread well.

Allow to dry for approx. 4-6 hours under good ventilation.

Then apply a second coat.

For renovation works, one coat applied to the clean and dry surface is usually sufficient.



## CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

## DRYING TIME

Approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

## COVERAGE

1 litre covers approx. 26 m<sup>2</sup> with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

Dried surface is satin-glossy at first and is afterwards satin.

Transparent colours are influenced by the natural colour of the wood and therefore they may deviate from the sample colours.

To extend the life of the coating, apply one coat of Osmo UV Protection Oil Extra 420 Clear after thoroughly drying.

Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

Osmo Natural Oil Woodstain Effect is furnished with biocides and therefore it is only to be used in outdoor areas. The added active ingredients delay or minimize the risk of algae and fungal attack. For effective protection, two coats are to be carried out. In accordance with the latest technical research, permanent protection against algae and fungal attack cannot be provided.

## Warning



## CAUTION

Flammable liquid and vapour. Keep out of reach of children. Keep away from heat/open flames. No smoking. Do not get in eyes, on skin, or on clothing. Contains propiconazole. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Harmful to aquatic life with long lasting effects. Avoid release to the environment. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations.

Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

1140 Agate-Silver  
1142 Graphite-Silver  
1143 Onyx-Silver

## CAN SIZES

0.75 L; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/17