

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier****Trade name:** Osmo Spray-Wax**Article number:** 3009 Clear Semi-matt; 3010 Natural; 3012 White Opaque; 3013 Black Opaque; 3066 White Weiß Transparent; 3084 Clear Matt; 3085 Clear Satin; 3086 Clear Gloss;**1.2 Relevant identified uses of the substance or mixture and uses****advised against** No further relevant information available.**Application of the substance / the mixture**Coating compound/ Surface coating/ paint  
Paint**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf**Further information obtainable from:**Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de**1.4 Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02

**Signal word**

Warning

**Hazard statements**

H226 Flammable liquid and vapour.

**Precautionary statements**

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P210 Keep away from heat. - No smoking.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

(Contd. on page 2)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 1)

**Additional information:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container in accordance with national regulations.  
 Observe the general safety regulations when handling chemicals.  
 Always wear a dust mask when sanding.

**Information concerning particular hazards for human and environment:****Warning:**

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)  
 Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 ----- ☠ Asp. Tox. 1, H304	25-50%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	aliphatic hydrocarbons, C9-C10 ----- ☠ Flam. Liq. 3, H226; ☠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	10-<15%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≤2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

**Trade name: Osmo Spray-Wax**

(Contd. of page 2)

<b>After skin contact:</b>	Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. Then consult a doctor.
<b>After swallowing:</b>	If swallowed, seek medical advice immediately and show this container or label.
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	Dizziness Headache
<b>4.3 Indication of any immediate medical attention and special treatment needed</b>	No further relevant information available.

### **SECTION 5: Firefighting measures**

<b>5.1 Extinguishing media</b>	
<b>Suitable extinguishing agents:</b>	CO <sub>2</sub> , powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
<b>For safety reasons unsuitable extinguishing agents:</b>	Water with full jet
<b>5.2 Special hazards arising from the substance or mixture</b>	Formation of toxic gases is possible during heating or in case of fire.
<b>5.3 Advice for firefighters</b>	
<b>Protective equipment:</b>	Mouth respiratory protective device.
<b>Additional information</b>	Cool endangered receptacles with water spray. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.
<b>6.2 Environmental precautions:</b>	Do not allow to enter sewers/ surface or ground water.
<b>6.3 Methods and material for containment and cleaning up:</b>	Warm water and cleansing agent Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
<b>6.4 Reference to other sections</b>	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

**Trade name: Osmo Spray-Wax**

(Contd. of page 3)

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Keep away from heat and direct sunlight.  
Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.

**Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
Store in a cool location.

**Information about storage in one common storage facility:** Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.

**Further information about storage conditions:** Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

**Storage class:** 3

**7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m <sup>3</sup> , 150 ppm ppm Source: UK SIA
-----------	--------------------------------------------------------------------------

**34590-94-8 Dipropylene glycol monomethyl ether**

WEL	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Sk
-----	-------------------------------------------------------

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

(Contd. on page 5)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 4)

<b>Respiratory protection:</b>	Do not carry product impregnated cleaning cloths in trouser pockets. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Not necessary if room is well-ventilated. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).
<b>Protection of hands:</b>	Protective gloves Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation To avoid skin problems reduce the wearing of gloves to the required minimum.
<b>Material of gloves</b>	Nitrile rubber, NBR
<b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
<b>For the permanent contact gloves made of the following materials are suitable:</b>	Nitrile rubber, NBR Recommended thickness of the material: $\geq 0.4$ mm For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
<b>For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:</b>	Nitrile rubber, NBR
<b>Eye protection:</b>	Tightly sealed goggles
<b>Body protection:</b>	Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

<b>Form:</b>	Viscous
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Mild

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	144 °C

<b>Flash point:</b>	> 30 °C (DIN EN ISO 2719)
---------------------	---------------------------

<b>Ignition temperature:</b>	240 °C
------------------------------	--------

(Contd. on page 6)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 5)

<b>Auto-ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits:</b>	
<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	7.0 Vol %
<b>Vapour pressure at 20 °C:</b>	10 hPa
<b>Density at 20 °C:</b>	0.85-1.08 g/cm <sup>3</sup> (DIN 51757)
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	20–35 s (DIN 53211/4mm) >21 mm <sup>2</sup> /s (40°C)
<b>Solvent separation test:</b>	< 3 % (ADR 2.2.3.1.4 f)
<b>Solvent content:</b>	
<b>VOC (EC)</b>	< 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)
<b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	No further relevant information available.
<b>10.2 Chemical stability</b>	
<b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
<b>10.3 Possibility of hazardous reactions</b>	Reacts with fabric soaked in the product (e.g. cleaning wool).
<b>10.4 Conditions to avoid</b>	No further relevant information available.
<b>10.5 Incompatible materials:</b>	No further relevant information available.
<b>10.6 Hazardous decomposition products:</b>	Carbon monoxide and carbon dioxide Nitrogen oxides (NO <sub>x</sub> )
<b>Additional information:</b>	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

(Contd. on page 7)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 6)

Must not be applied on the same spraying stand as lacquers or lacquer corrosives that contain NC (nitrocellulose). Risk of self-ignition.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****aliphatic hydrocarbons, C10-C13**

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

**aliphatic hydrocarbons, C9-C10**

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	>20 mg/l (rat)

**34590-94-8 Dipropylene glycol monomethyl ether**

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat) 13000 - 14000 mg/kg (rabbit)
Inhalative	LC50 / 4h	500 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)

**Primary irritant effect:**

**Skin corrosion/irritation** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)

**Trade name: Osmo Spray-Wax**

(Contd. of page 7)

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Aquatic toxicity:

##### aliphatic hydrocarbons, C10-C13

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

##### aliphatic hydrocarbons, C9-C10

EC50 / 24h	<130 mg/kg (Oncorhynchus mykiss (Regenbogenforelle)) >100 mg/kg (selenastrum capricornutum)
------------	------------------------------------------------------------------------------------------------

##### 34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h (Static)	1919 mg/l (daphnia)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

##### Additional ecological information:

**General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

##### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

##### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 9)



**Trade name: Osmo Spray-Wax**

(Contd. of page 8)

**Recommended cleansing agents:** Solvent naphtha

### SECTION 14: Transport information

#### 14.1 UN-Number

**ADR, IMDG, IATA** UN1263

#### 14.2 UN proper shipping name

**ADR** 1263 PAINT  
**IMDG, IATA** PAINT

#### 14.3 Transport hazard class(es)

**ADR**  
**Class** 3 (F1) Flammable liquids.  
**Label** 3

#### IMDG, IATA

**Class** 3 Flammable liquids.  
**Label** 3

#### 14.4 Packing group

**ADR, IMDG, IATA** III

#### 14.5 Environmental hazards:

**Marine pollutant:** No

#### 14.6 Special precautions for user

Warning: Flammable liquids.  
**Danger code (Kemler):** 30  
**EMS Number:** F-E,S-E  
**Stowage Category** A

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

#### Transport/Additional information:

#### ADR

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
**Transport category** 3  
**Tunnel restriction code** D/E

(Contd. on page 10)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 9)

**IMDG****Limited quantities (LQ)**

5L

**Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

**UN "Model Regulation":**

UN1263, PAINT, 3, III

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Qualifying quantity (tonnes) for the application of lower-tier requirements**

5.000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements**

50.000 t

**National regulations:****VOC (EC)** < 500 g/l (VOC-max. = 500 g/l (2010 A/i))**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Department issuing SDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

**Material Safety Data Sheets**  
according to 1907/2006/EC, Article 31

Printing date 09.07.2018

Version number 2

Revision: 02.05.2018

**Trade name: Osmo Spray-Wax**

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous  
version altered.**