

Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

from: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void
 Hazard pictograms Void
 Signal word Void
 Hazard statements Void

Precautionary statements Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed. Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding. Safety data sheet available on request.

2.3 Other hazards Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

(Contd. on page 2)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 1)

10-25%

🚯 Asp. Tox. 1, H304

Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 918-481-9 aliphatic hydrocarbons, C10-C13

Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed No further

No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

(Contd. on page 3)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 2)

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas. Prevent formation of aerosols.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from frost.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm

Source: UK SIA

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

Filter A/P2

Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBREye protection: If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side

protection)

(Contd. on page 5)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 4)

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid
Colour: White
Odour: Mild

Change in condition

Melting point/freezing point: Undetermined. *Initial boiling point and boiling range:* > 180 °C (DIN 51751)

Flash point: ≥ 65 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Vapour pressure: 3 hPa [20°C]

Density at 20 °C: 1.31 - 1.33 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: >100 s (ISO 4mm)
>21 mm²/s (40°C)

Solvent separation test: < 3 % (ADR 2.2.1.4f)

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

(Contd. on page 6)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 5)

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

Reacts with acids, alkalis and oxidising agents.

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC:	50 values re	levant for classification:	
aliphat	ic hydrocar	bons, C10-C13	
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)	

Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreesing

effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met. **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
aliphatic hydrocarbo	ons, C10-C13
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

12.2 Persistence and degradability No further relevant information available.
 12.3 Bioaccumulative potential No further relevant information available.
 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

	Europear	European waste catalogue		
Ī	08 01 11	waste paint and varnish containing organic solvents or other dangerous substances		
ſ	15 01 10	packaging containing residues of or contaminated by dangerous substances		

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR Void

(Contd. on page 8)



Printing date 23.05.2018 Version number 15 Revision: 08.05.2018

Trade name: 2104 Osmo Opaque Gloss Wood Stain, white

(Contd. of page 7)

ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex I	II of Marpol
and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

VOC(EC) < 300 g/l (VOC-max. = 300 g/l (2010 A/d))

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H304 May be fatal if swallowed and enters airways.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1