

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking


- **1.1 Product identifier**
- **Trade name:** beko B10 Universal-Öl (Spray)
- **UFI:** K0QV-20FW-Y009-1S4E
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Lubricating oil
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
beko GmbH
Rappenfeldstr. 5
D-86653 Monheim
+49 (0) 90 91 / 9 08 98-0
info@beko-group.com
www.beko-group.com
- **Further information obtainable from:**
Vertrieb / Produktsicherheit
+49 (0) 90 91 / 9 08 98-0
info@beko-group.com
- **1.4 Emergency telephone number:** Poison Control Center Mainz - 24 hour – phone: +49 (0) 6131/19240

SECTION 2: Hazards identification


- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The labelling of an aspiration hazard (Asp. Tox. 1 H304) is not required for aerosols and containers with a sealed spray attachment (Regulation (EC) 1272/2008, Annex I, 1.3.3).
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C6, isoalkanes, <5% n-hexane
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 1)

- P260 Do not breathe vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents / container as special waste.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:**

Mixture of substances listed below with nonhazardous compounds or compounds with no duty to declare.

· **Dangerous components:**

EC number: 918-167-1 Reg.nr.: 01-2119472146-39	Kohlenwasserstoffe, C11-C12, iso-Alkane, <2% Aromaten ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 4, H413	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-25%
CAS: 64742-49-0 EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
CAS: 92045-53-9 EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics. ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220; Press. Gas (Liq.), H280	2.5-10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (<0,1% butadiene) ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-10%
CAS: 64742-49-0 EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	≥0.25-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Wash with water and soap

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Risk of bursting in case of fire heat
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Product forms slippery surface when combined with water.
Particular danger of slipping on leaked/spilled product.
Avoid contact with skin / eyes and inhalation.
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C
- **Storage class:** German storage class: 2B (Aerosols)

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

64742-49-0 Hydrocarbons, C6, isoalkanes, <5% n-hexane

RCP-TWA (Great Britain)	Long-term value: 1400 mg/m ³
-------------------------	---

92045-53-9 Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

RCP-TWA (Great Britain)	Long-term value: 1400 mg/m ³
-------------------------	---

64742-49-0 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

RCP-TWA (Great Britain)	Long-term value: 1400 mg/m ³
-------------------------	---

110-54-3 n-hexane

WEL (Great Britain)	Long-term value: 72 mg/m ³ , 20 ppm
IOELV (EU)	Long-term value: 72 mg/m ³ , 20 ppm

· DNELs

64742-49-0 Hydrocarbons, C6, isoalkanes, <5% n-hexane

Oral	DNEL Endverbraucher/ Consumers /Consommateur	1,301 mg/kg BW/ day (.)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	1,377 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	13,964 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	1,137 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	5,306 mg /m ³ (.)

92045-53-9 Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

Oral	DNEL Endverbraucher/ Consumers /Consommateur	149 mg/kg BW/ day (hum)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	149 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	300 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	477 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	2,085 mg /m ³ (.)

64742-49-0 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Oral	DNEL Endverbraucher/ Consumers /Consommateur	1,301 mg/kg BW/ day (.)
Dermal	DNEL - Endverbraucher/ Consumers /Consommateur	1,377 mg/kg BW /day (.)
	DNEL Arbeiter / Workers/ Travailleur	13,964 mg/kg BW /day (.)
Inhalative	DNEL Endverbraucher/ Consumers /Consommateur	1,131 mg /m ³ (.)
	DNEL Arbeiter / Workers/ Travailleur	5,306 mg /m ³ (.)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid contact with the eyes and skin.

· Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 4)

- **Protection of hands:**
- **Material of gloves** If contamination is possible, use gloves made of nitrile according EN 374
- **Penetration time of glove material** > 480 min / 0,4 mm thickness
- **Eye protection:** Safety glasses in case of spittings

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Yellowish
Odour:	Solvent-like

· **pH-value:** Not applicable.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44 °C value concerns to propellant

· **Flash point:** -97 °C
concerns to propellant

· **Ignition temperature:** 250 °C

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.

· Explosion limits:

Lower:	1.5 Vol %
Upper:	8.5 Vol %
Pressure (20°C)	2.5 - 4.5 bar

· **Density at 20 °C:** 0.680 - 0.695 g/cm³

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· Solvent content:

VOC (EC) 82.20 % = 571,1 g/L

· **9.2 Other information** No further relevant information available.

· **Additional information** Vapors are heavier than air.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.

· **10.3 Possibility of hazardous reactions**

By use or incidental release the formation of explosive vapor/air mixtures is possible.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

· **Additional information:** Stable for a storage time of min. 24 months

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 5)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

Kohlenwasserstoffe, C11-C12, iso-Alkane, <2% Aromaten		
Oral	LD50	>5,000 mg/kg (rat)
106-97-8 butane, pure		
Inhalative	LC50/4 h	658 mg/l (rat)
74-98-6 propane		
Inhalative	LC50/4 h	>20 mg/l (rat)
	LC50 /15 min	1,443 mg/l (rat)
75-28-5 isobutane (<0,1% butadiene)		
Inhalative	LC50/4 h	>20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
low irritant - no duty to declare
Causes skin irritation.
- **Serious eye damage/irritation** low
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

Kohlenwasserstoffe, C11-C12, iso-Alkane, <2% Aromaten	
EC50	>1,000 mg/kg (fis)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 6)

SECTION 13: Disposal considerations



- **13.1 Waste treatment methods**
- **Recommendation**
empty cans: material recycling
filled cans: remove in accordance with local regulations

- **European waste catalogue**

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
· **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· **IMDG** AEROSOLS
· **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
· **ADR**

· **Class** 2 5F Gases.
· **Label** 2.1
- **IMDG, IATA**

· **Class** 2.1
· **Label** 2.1
- **14.4 Packing group**
· **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
· **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.
· **Hazard identification number (Kemler code):** -
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 7)

For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**
 · **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity
 · **Transport category** 2
 · **Tunnel restriction code** D
 · **Remarks:** Transportation as "LIMITED QUANTITIES" according 3.4 ADR is possible.
 Sole marking: Sign for "Limited Quantities" (rhombus with two black edges)
 Entry in the transportation document: Transportation according chapter 3.4 ADR
 Tunnel category "E" in case of a load of 8000 kg (rgross weight) or more.

· **IMDG**
 · **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Class	Share in %
I	0.5
NK	49.9

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.08.2020

Revision: 17.08.2020

Trade name: beko B10 Universal-Öl (Spray)

(Contd. of page 8)

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Press. Gas (Liq.): Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

*** Data compared to the previous version altered.**

GB