



Acid Etch Solution

PRODUCT DATA

Description:

Acid Etch Solution is a pre-treatment for concrete power floated or very smooth concrete floors. The Acid Etch Solution opens the pores of the concrete and prepares the surface to accept its next treatment, allowing excellent adhesion.

Apply evenly and allow 24hrs for the Acid Etch to react. After the reaction has taken place, the surface should be rinsed with clean water only. Allow to dry completely before attempting to paint the surface.

Area of use:

Interior or Exterior

Substrates:

Concrete

Packing:

5 Litres

Physical Constants:

Colour: Clear

Finish: -

Volume solids: -

Theoretical spreading rate: Approx. 20 sq. metres per litre

Flash point: -

Specific gravity: 1.1

Dry to touch: 2-4 hours

Over-coating time: 1-2 days

****The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush / Mop / Broom

Thinner: N/A

Cleaning of tools: Water

Surface Condition: Ensure surface is free from dust and debris. Excess dirt, oil or grease should be scrapped off or removed.

Please refer to the Material Safety Data Sheet for further information.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel: +44 1621 785173, Fax: +44 1621 785393