



## Chlorinated Rubber

### PRODUCT DATA

---

#### Description

A very hard-wearing chemically resistant paint. Ideal where conditions require a degree of chemical and water resistance typical examples would be swimming pools, manhole covers and metal tanks. It is also excellent for road markings where high visibility and durability is a must.

#### Area of use

Interior and exterior

#### Substrates

Concrete, ferrous metal, manhole covers and road surfaces

#### Packing

5 litres

#### Physical Constants

Colours: Yellow 10E53 and White  
(other colours on request min batch 200L)

Finish: Semi gloss

Volume solids: 55%

Theoretical spreading rate: 15 sq. metres per litre

Flash point: 23°C

Specific gravity: 1.3 – 1.4

Dry to touch: 1 - 2 hours (20°C)

Over-coating time: 16 hours

***\*The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

#### Application Details

Application method: Brush, roller, conventional and airless spray  
Thinner: Xylene  
Cleaning of tools: Xylene

**Surface condition** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

*Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.