

SAFETY DATA SHEET NITOPRIME ZINCRICH PLUS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name NITOPRIME ZINCRICH PLUS

Product number 1958023UK9, 1958220UK9

UFI: 3SD0-R0HN-G00N-MYT0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Rust-preventing primer.

1.3. Details of the supplier of the safety data sheet

Supplier Fosroc International Limited

Drayton Manor Business Park

Coleshill Road Tamworth Staffordshire B78 3XN England

Tel: +44 (0) 1827 262222 Fax: +44 (0) 1827 262444 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (Monday-Sunday 24 hours a day)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226 Water-react. 3 - H261

Health hazards Lact. - H362 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 1 - H410

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

Physicochemical Vapours may form explosive mixtures with air.

2.2. Label elements

Hazard pictograms







Signal word

Danger

Hazard statements H226 Flammable liquid and vapour.

H261 In contact with water releases flammable gases.

H362 May cause harm to breast-fed children. H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P260 Do not breathe vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Supplemental label

EUH066 Repeated exposure may cause skin dryness or cracking. information EUH018 In use may form flammable/explosive vapour-air mixture.

Contains ZINC POWDER, HYDROCARBONS, C9, aromatics, CHLORINATED PARAFFIN (C14-17)

Supplementary precautionary

statements

P201 Obtain special instructions before use.

P231+P232 Handle and store contents under inert gas. Protect from moisture.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P263 Avoid contact during pregnancy and while nursing. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P391 Collect spillage.

P402+P404 Store in a dry place. Store in a closed container. P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ZINC POWDER 60-100%

CAS number: 7440-66-6 EC number: 231-175-3

M factor (Chronic) = 1

Classification

Pvr. Sol. 1 - H250 Water-react. 1 - H260 Aquatic Chronic 1 - H410

HYDROCARBONS, C9, aromatics 10-30%

CAS number: 64742-95-6 EC number: 918-668-5 REACH registration number: 01-

2119455851-35-0000

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

ZINC OXIDE 1-5%

Classification

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

CHLORINATED PARAFFIN (C14-17) 1-5%

CAS number: 85535-85-9 EC number: 287-477-0 REACH registration number: 01-

2119519269-33-xxxx

M factor (Acute) = 1 M factor (Chronic) = 100

Classification

Lact. - H362

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

CALCIUM OXIDE <1%

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335

NITOPRIME ZINCRICH PLUS

2-piperazin-1-ylethylamine <1%

CAS number: 140-31-8 EC number: 205-411-0 REACH registration number: 01-

2119471486-30-XXXX

Classification

Acute Tox. 4 - H302 Acute Tox. 3 - H311 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 2 - H361fd STOT RE 1 - H372 Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. Get medical attention. Move affected person to

fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting

occurs, the head should be kept low so that vomit does not enter the lungs. Give plenty of water to drink. Get medical attention immediately. Move affected person to fresh air and keep

warm and at rest in a position comfortable for breathing.

Skin contact Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical

attention promptly if symptoms occur after washing.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion The product irritates mucous membranes and may cause abdominal discomfort if swallowed.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema. Prolonged or

repeated exposure may cause severe irritation.

Eye contact May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

NITOPRIME ZINCRICH PLUS

Specific hazards Dust may form explosive mixture with air. The product is flammable.

Hazardous combustion

producto

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and

watercourses.

Special protective equipment

for firefighters

Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation

of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBONS, C9, aromatics

Long-term exposure limit (8-hour TWA): WEL 100 mg/m³

CALCIUM OXIDE

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

WEL = Workplace Exposure Limit.

ZINC POWDER (CAS: 7440-66-6)

DNEL Workers - Inhalation; Long term systemic effects: 5 mg/m³

Workers - Dermal; Long term systemic effects: 83 mg/kg/day

PNEC - Fresh water; 20.6 μg/l

- marine water; 6.1 µg/l

HYDROCARBONS, C9, aromatics (CAS: 64742-95-6)

DNEL Professional - Dermal; systemic effects: 25 mg/kg/day

Professional - Inhalation; systemic effects: 150 mg/m³ Consumer - Oral; systemic effects: 11 mg/kg/day Consumer - Inhalation; systemic effects: 32 mg/m³ Consumer - Dermal; systemic effects: 11 mg/kg/day

CHLORINATED PARAFFIN (C14-17) (CAS: 85535-85-9)

DNEL Industry - Inhalation; Long term systemic effects: 1.6 mg/m³

Industry - Dermal; Long term systemic effects: 47.9 mg/kg/day Consumer - Oral; Long term systemic effects: 0.58 mg/kg/day Consumer - Inhalation; Long term systemic effects: 2 mg/m³ Consumer - Dermal; Long term systemic effects: 28.75 mg/kg/day

PNEC - Fresh water; 1000 mg/l

- marine water; 200 mg/l

- STP; 80 mg/l

CALCIUM OXIDE (CAS: 1305-78-8)

DNEL Workers - Inhalation; Long term local effects: 1 mg/m³

Workers - Inhalation; Short term local effects: 4 mg/m³

PNEC - Fresh water; 0.37 mg/l

- marine water; 0.24 mg/l

2-piperazin-1-ylethylamine (CAS: 140-31-8)

DNEL Workers - Inhalation; Long term systemic effects: 3.6 mg/m³

Workers - Inhalation; Short term systemic effects: 21.4 mg/m³ Workers - Dermal; Long term systemic effects: 3.3 mg/kg/day Workers - Dermal; Short term systemic effects: 20 mg/kg/day

PNEC - Fresh water; 0.0058 mg/l

- marine water; 0.58 mg/l

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

NITOPRIME ZINCRICH PLUS

Hand protection Use protective gloves. It is recommended that gloves are made of the following material:

Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are

recommended.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respiratory

fitted with the following cartridge: Gas filter, type A2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Grey.

Odour Aromatic.

Odour threshold Not determined.

pH Not applicable.

Melting point Not determined.

Initial boiling point and range 155 - 181°C @ 1 atm

Flash point 41°C

Evaporation rate 0.2 (ethanol = 1)

Evaporation factor Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not determined.

Other flammability Not determined.

Vapour pressure 0.25 kPa @ 20°C

Vapour density Not determined.

Relative density 2.6 @ 25°C

Bulk density Not applicable.

Solubility(ies) Insoluble in water.

Partition coefficient Not determined.

Auto-ignition temperature >450°C

Decomposition Temperature Not determined.

Viscosity 6 P @ 25°C

Explosive properties Vapours may form explosive mixtures with air.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 495 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Acids. Alkalis. Oxidising materials.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Acids. Bases Oxidising materials.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation May cause respiratory system irritation. Vapours in high concentrations are anaesthetic.

Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness.

Central nervous system depression.

Ingestion Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Inhalation Prolonged inhalation of high concentrations may damage respiratory system. SKIN

CONTACT. Product has a defatting effect on skin. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation. EYE CONTACT. May cause severe eye irritation. INGESTION. The product irritates mucous membranes and may cause

abdominal discomfort if swallowed.

Target organs Skin Eyes Respiratory system, lungs

Toxicological information on ingredients.

HYDROCARBONS, C9, aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅o

3,592.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,160.0

mg/kg)

NITOPRIME ZINCRICH PLUS

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation 6.2

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

mg/l)

ZINC OXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

7,950.0

6.2

Species Mouse

Acute toxicity - dermal

Acute toxicity dermal (LD₅ 2,000.0

mg/kg)

Species Rat

CHLORINATED PARAFFIN (C14-17)

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >4890 mg/kg, Dermal, Rat

Acute and chronic health

hazards

May cause harm to breast-fed children.

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.1. Toxicity

Ecological information on ingredients.

ZINC POWDER

Chronic aquatic toxicity

M factor (Chronic) 1

HYDROCARBONS, C9, aromatics

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, : 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, : 3.2 mg/l, Daphnia magna

NITOPRIME ZINCRICH PLUS

Acute toxicity - aquatic

plants

EC₅₀, : 2.6 mg/l, Pseudokirchneriella subcapitata

ZINC OXIDE

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute)

Acute toxicity - fish LC₅₀, 96 hours: 1.1 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 0.098 mg/l, Daphnia magna

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Degradability Non-rapidly degradable

M factor (Chronic) 1

CHLORINATED PARAFFIN (C14-17)

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: >5000 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 0.006 mg/l, Daphnia magna

Chronic aquatic toxicity

M factor (Chronic) 100

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

Ecological information on ingredients.

HYDROCARBONS, C9, aromatics

Biodegradation Water - Degradation (%) 78: 28 days

The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

CHLORINATED PARAFFIN (C14-17)

Bioaccumulative potential BCF: < 2000 L/kg,

12.4. Mobility in soil

Mobility The product contains substances which are insoluble in water and which may spread on water

surfaces. The product contains volatile substances which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

Ecological information on ingredients.

CHLORINATED PARAFFIN (C14-17)

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. assessment

12.6. Other adverse effects

Other adverse effects When used and disposed of as intended no adverse environmental effects are foreseen

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name

PAINT RELATED MATERIAL (ZINC POWDER - ZINC DUST (STABILISED))

(ADR/RID)

Proper shipping name (IMDG) PAINT RELATED MATERIAL (ZINC POWDER - ZINC DUST (STABILISED))

Proper shipping name (ICAO) PAINT RELATED MATERIAL (ZINC POWDER - ZINC DUST (STABILISED))

Proper shipping name (ADN) PAINT RELATED MATERIAL (ZINC POWDER - ZINC DUST (STABILISED))

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

NITOPRIME ZINCRICH PLUS

Transport labels



14.4. Packing group

ADR/RID packing group III
IMDG packing group III
ICAO packing group III
ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

30

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 18/09/2020

Revision 6f

Supersedes date 09/09/2019

Hazard statements in full H226 Flammable liquid and vapour.

H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H261 In contact with water releases flammable gases.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H362 May cause harm to breast-fed children.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.