

SAFETY DATA SHEET PATCHROC GP

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PATCHROC GP

Product number 2060002UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious overlay

1.3. Details of the supplier of the safety data sheet

Supplier Fosroc Limited

Drayton Manor Business Park

Coleshill Road Tamworth Staffordshire B78 3XN England

Tel: +44 (0) 1827 262222 Fax: +44 (0) 1827 262444 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (Monday-Sunday 24 hours a day)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Not Classified

Human health Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the

respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of

developing lung diseases.

Environmental The product will harden into a solid mass in contact with water and moisture. The resultant

material is not biodegradable.

2.2. Label elements

PATCHROC GP

Hazard pictograms





Signal word Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Precautionary statements P261 Avoid breathing dust.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Contains CEMENT POWDER, CALCIUM SULFOALUMINATE

Supplementary precautionary

statements

P272 Contaminated work clothing should not be allowed out of the workplace.

P310 Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CALCIUM CARBONATE	30-60%

CAS number: 1317-65-3 EC number: 215-279-6

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

ORDINARY PORTLAND CEMENT 10-30%

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

PATCHROC GP

CALCIUM SULFOALUMINATE 10-30%

CAS number: 65997-15-1 EC number: 266-043-4

No. REACH: Exempt of registration

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1B - H317 STOT SE 3 - H335

LITHIUM CARBONATE(ANHYDROUS) <1%

CAS number: 554-13-2 EC number: 209-062-5 REACH registration number: 01-

2119516034-53-XXXX

Classification

Acute Tox. 4 - H302 Eye Irrit. 2 - H319

TARTARIC ACID POWDER <1%

CAS number: 87-69-4 EC number: 201-766-4

Classification

Eye Dam. 1 - H318

Iron (II) sulfate heptahydrate <1%

CAS number: 7782-63-0 EC number: 231-753-5

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

avoid contact with wet cement or wet cement containing preparations.

Inhalation Move affected person to fresh air at once. Dust in throat and nasal passages should clear

spontaneously. Get medical attention if irritation persists or later develops, or if discomfort,

coughing or other symptoms persist.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give

milk instead of water if readily available. Never give anything by mouth to an unconscious

person. Get medical attention immediately.

Skin contact Wash immediately with copious quantities of water. Remove contaminated clothing

immediately. Obtain medical advice if skin orders develop.

PATCHROC GP

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention. Show this

Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

Ingestion Ingestion of large doses may result in irritation to the gastrointestinal tract.

Skin contact May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis

after repeated contact. Prolonged skin contact with wet preparation may cause serious burns

without pain being felt, including through clothing.

Eye contact Eye contact may cause serious and potentially irreversible injuries.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Water used for fire extinguishing, which has been in contact with the product, may be

corrosive. No unusual fire or explosion hazards noted.

Hazardous combustion

products

No known hazardous decomposition products.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.

Avoid inhalation of dust.

6.2. Environmental precautions

Environmental precautions Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or

watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

PATCHROC GP

Methods for cleaning up

Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Dry material: Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of

dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Unsuitable container

materials: Aluminium. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 6 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible. To be stored out of reach of children in its

original packaging in a dry place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³

QUARTZ (SiO2)

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³

ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

CALCIUM SULFOALUMINATE

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

TARTARIC ACID POWDER

Long-term exposure limit (8-hour TWA): WEL 5 mg/m3 resp.dust

WEL = Workplace Exposure Limit

ORDINARY PORTLAND CEMENT (CAS: 65997-15-1)

DNEL Workers - Inhalation; Short term : 3 mg/m³

LITHIUM CARBONATE(ANHYDROUS) (CAS: 554-13-2)

PATCHROC GP

DNEL Workers - Dermal; Acute: 100 mg/kg

Workers - Inhalation; Acute: 30 mg/m³
Workers - Dermal; Long term: 64,3 mg/kg
Workers - Inhalation; Long term: 10 mg/m³
General population - Dermal; Acute: 19,23 mg/kg
General population - Inhalation; Acute: 28,92 mg/m³
General population - Oral; Long term: 6,43 mg/kg

General population - Dermal; Long term : 64,3 mg/kg General population - Inhalation; Long term : 9,64 mg/m³

PNEC Fresh water; 9 mg/l

marine water; 0,9 mg/l

Sediment (Freshwater); 35,2 mg/kg Sediment (Marinewater); 3,52 mg/kg

Soil; 1,76 mg/kg

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.

Eye/face protection

The following protection should be worn: Chemical splash goggles. (conform EN 166)

Hand protection

Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove

Other skin and body protection

Use barrier creams to minimise skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

This product contains silica sands.

The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause

health effects.

Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and

breathlessness.

Occupational exposure to respirable crystalline silica dust should be monitored and controlled.

Respiratory protection

Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Dusty powder.

PATCHROC GP

Colour Grey.

Odour Odourless.

Odour threshold Not relevant.

pH (concentrated solution): >12

Melting point >1250°C

Initial boiling point and range Not applicable.

Flash point Not applicable.

Evaporation factor Not applicable.

Flammability (solid, gas) No.

Upper/lower flammability or

explosive limits

Evaporation rate

The product is not flammable.

Not applicable.

Other flammability

Vapour pressure

Vapour density

Not applicable.

Not applicable.

Not applicable.

Not determined.

Solubility(ies) Slightly soluble in water. Hardens in contact with water.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not applicable.

Explosive properties Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity When mixed with water, hardens to form a stable mass that is not reactive in normal

conditions.

10.2. Chemical stability

Stability Stable under the prescribed storage conditions. When stored under humid conditions, the

chromate neutralization will decrease. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis causes by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic

reaction.

PATCHROC GP

10.3. Possibility of hazardous reactions

Possibility of hazardous

None known. Will not polymerise.

reactions

10.4. Conditions to avoid

Conditions to avoid Water, moisture.

10.5. Incompatible materials

Materials to avoid Acids. Chemically-active metals.

10.6. Hazardous decomposition products

Hazardous decomposition

No known hazardous decomposition products.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation Some individuals may exhibit eczema upon exposure to wet cement caused either by the high

pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is

not expected.

Inhalation Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to

cement dust.

Ingestion May cause irritation of mouth, throat and digestive tract.

Skin contact This product is strongly irritating. Prolonged contact may cause burns. May cause

sensitisation by skin contact.

Eye contact Irritating and may injure eye tissue if not removed promptly.

Acute and chronic health

hazards

Repeated and/or prolonged contact may lead to dermatitis.

Toxicological information on ingredients.

ORDINARY PORTLAND CEMENT

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rabbit

CALCIUM SULFOALUMINATE

General information May cause respiratory allergy.

LITHIUM CARBONATE(ANHYDROUS)

Acute toxicity - oral

Notes (oral LD50) LD50 525 mg/kg, Oral, Rat

Acute toxicity - dermal

PATCHROC GP

Notes (dermal LD₅o) LD50 > 2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC50 > 2 mg/l, 4 hours, Rat

TARTARIC ACID POWDER

Eye contact Causes serious eye damage.

Iron (II) sulfate heptahydrate

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

1,520.0

Species Mouse

ATE oral (mg/kg) 1,520.0

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some

circumstances.

Ecological information on ingredients.

ORDINARY PORTLAND CEMENT

Acute aquatic toxicity

Acute toxicity - fish Not determined.

LITHIUM CARBONATE(ANHYDROUS)

Acute aquatic toxicity

Acute toxicity - fish CL50, 96 hours: 30,3 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC50, 48 hours: 33 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

NOEC, 72 hours: 50 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms

EC50, 3 hours: 278 mg/l, Activated sludge

TARTARIC ACID POWDER

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

PATCHROC GP

Ecological information on ingredients.

CALCIUM SULFOALUMINATE

Persistence and degradability

Expected to be not readily biodegradable.

TARTARIC ACID POWDER

Persistence and degradability

Expected to be readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Ecological information on ingredients.

CALCIUM SULFOALUMINATE

Bioaccumulative potential No data available on bioaccumulation.

TARTARIC ACID POWDER

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance. The product is not volatile but may be

spread by dust-raising handling.

Ecological information on ingredients.

CALCIUM SULFOALUMINATE

Mobility Insoluble in water.

TARTARIC ACID POWDER

Mobility Soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

CALCIUM SULFOALUMINATE

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. assessment

TARTARIC ACID POWDER

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. **assessment**

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

PATCHROC GP

CALCIUM SULFOALUMINATE

Other adverse effects None known.

TARTARIC ACID POWDER

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life:

when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or

treated again with a reducing agent.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Note that fully cured material is not considered as hazardous

waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

PATCHROC GP

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information For professional users only. Only trained personnel should use this material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 09/09/2019

Revision 9a

Supersedes date 13/11/2017

Hazard statements in full H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.