

# DATA<sub>sheet</sub>



Providing Practical Solutions

## Torstrip WBS water based paint stripper

SS4300005

### intended uses

A high performance water based stripping system. Specifically developed for the removal of multi-layers of both conventional and two-component paint finishes from ceilings and soffits, where the use of conventional stripping systems may not be appropriate.

### product description

A non hazardous blend of Benzyl Alcohol, surfactants and evaporation retardants.

### product information

<b>Product reference</b>	SS4300005
<b>Theoretical coverage</b>	Up to 4 square metres per litre per coat
<b>Practical coverage</b>	Can vary, depends on number of paint coats, type of material, overall film thickness, substrate type, number of removals necessary, etc.
<b>Appearance/Colour range</b>	White / Milky
<b>VOC content</b>	Not applicable

### application details

**Method of Application** See detailed Torstrip WBS Application Guidelines.

### storage and handling

<b>Storage</b>	Store in a safe place out of the reach of children
<b>Pack Size</b>	25 litre drum, filled to 22 litres (25kg)
<b>Flash point</b>	Not classified as flammable
<b>Product weight</b>	1.13 kilogram/litre
<b>Shelf life</b>	3 years

### surface preparation

Ensure surfaces to be stripped are dry. Waxy or extremely greasy surfaces should be thoroughly cleaned prior to stripping.

Adjacent surfaces which are not to be stripped should be suitably masked and protected, preferably with polypropylene sheeting.

### limitations

Use as supplied. Do not dilute or add other products.

The area to be treated should not be allowed to dry out during treatment.

If scraping is attempted too early the stripper will not have had sufficient time to penetrate the layers and removal will be restricted.

### safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to

using the product. This can be faxed if urgently required.

A draft Torstrip WBS Method Statement is available and recommended for use.

Minimum precautions for all paints:

1. Avoid prolonged skin and eye contact i.e. wear suitable protective gloves, overalls, goggles, etc.
2. Ensure good ventilation, mechanical ventilation is not required.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

## Definitions

### **Tolerances**

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### **Practical coverage**

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

### **Pot Life**

Applies only to two pack products and refers to the time the mixture remains usable.

### **VOC**

Volatile organic compounds

### **dft**

Dry film thickness

### **wft**

Wet film thickness

## Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated: January 2020**

**SS4300005**