

Torstrip WDA10 wash down agent



intended uses	For the washing down of previously painted surfaces prior to application of paint systems. For the washing down recently stripped surfaces prior to application of paint systems.	
product description	A blend of surfactants, detergents and water.	
product information	Product reference	SS4200005
	Theoretical coverage	N/A
	Practical coverage	N/A
	Appearance/Colour range	Clear
	VOC content	0 grams/litre
application details	Method of application	Dilute with water, 1 part Torstrip WDA10 to 10 parts water. Apply by brush or cloth.
storage and handling	Storage	Store in a safe place out of the reach of children
storage and handling	Storage Pack Size	Store in a safe place out of the reach of children 5 litres
storage and handling		·
storage and handling	Pack Size	5 litres
storage and handling	Pack Size Flash point	5 litres Non flammable
storage and handling surface preparation	Pack Size Flash point Product weight Shelf life Previously painted: Prepare Repair with a high quality surf Remove existing graffiti using Torclean 'G' Graffiti Remover Stripped: To be applied follow	5 litres Non flammable 1.1kilogram/litre

safety precautions	A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.		
	A draft Torstrip Method Statement is available and recommended for use.		
	Minimum precautions for all paints: 1. Avoid skin and eye contact i.e. wear gloves, goggles, etc.		
	2. Ensure good ventilation, mechanical if necessary.		
	 Store and use away from heat and flame. Do not eat or smoke in the vicinity of work. Wash hands before eating. 		
	6. Refer to supply container for additional warning labels.		
definitions	; Tolerances	All information quoted in this data sheet is subject to normal manufacturing tolerances.	
	Practical coverage	Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.	
	Pot Life	Applies only to two pack products and refers to the time the mixture remains usable.	
	VOC	Volatile organic compounds	
	dft	Dry film thickness	
	wft	Wet film thickness	
disclaimer	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.		

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

Updated: January 2020

SS420005