

# LOW SLIP ADDITIVE – AGGREGATE LS30



**A hard Aluminium Oxide aggregate additive providing additional under foot traction to floor coatings**

## Recommended Areas of Use

Used in conjunction with Bradite floor paints requiring a hard wearing low slip additive.

## Certificates & Approvals

Manufactured under the auspices of an ISO 9001:2008 quality & ISO 14001:2004 environmental management systems.

## Properties

<b>Theoretical spreading rate</b>	0.25 to 1.0 kg/m <sup>2</sup>	<b>Shelf life</b>	Unlimited in original unopened containers
<b>Density</b>	3.77 kg/L	<b>Colour range</b>	Light grey
<b>Volume solids</b>	100%	<b>Particle Size</b>	Approximately 0.1 mm

## Suitable Surfaces

Consult technical datasheet for the specific Bradite floor paint product for recommendations.

## Application Information

Consult technical datasheet for the specific Bradite floor paint product for recommendations.

## Incorporation

This additive may be incorporated into the paint by direct incorporation providing a more even appearance on large areas.

- Dincorporation

Bradite Low Slip Soft Aggregate LS30 should be added to the paint and mixed thoroughly just before use at a rate of 1 x 250ml LS30 tin (400g) per 5 litre of paint.

The end user and applicator must ensure that the finished floor is safe against slips in all likely usage conditions.

## Summary Safety Information

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label.

**Disclaimer** - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.