

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : OWATROL PRO SOLID COLOR STAIN Product code : SCS02. (All tones)

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Solid Finish for exterior wood

# 1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..

Address : Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE. Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84. info@durieu.com www.durieu.com

### 1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

### Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

# **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

#### 2.2. Label elements

# In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :					
EUH208	Contains 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC). May produce an allergic reaction.				
EUH208	Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND				
	2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.				
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or				
	mist.				
Hazard statements :					
H412	Harmful to aquatic life with long lasting effects.				
Precautionary statements - G	eneral :				
P101	If medical advice is needed, have product container or label at hand.				
P102	Keep out of reach of children.				
Precautionary statements - Pr	revention :				
P260	Do not breathe dust vapours.				
P262	Do not get in eyes, on skin, or on clothing.				
P273	Avoid release to the environment.				
Precautionary statements - Response :					
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.				
Precautionary statements - Disposal :					
P501	Dispose of contents / container in a waste collection point.				

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

# SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

# 3.2. Mixtures

# Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 022-006-00-2	GHS08	[1]	10 <= x % < 25
CAS: 13463-67-7	Wng	[10]	
EC: 236-675-5	Carc. 2, H351		
TITANIUM DIOXIDE [IN POWDER			
FORM CONTAINING 1 % OR MORE OF			
PARTICLES WITH AERODYNAMIC			
DIAMETER <= 10 µM]			
INDEX: PCP186	GHS08		2.5 <= x % < 10
CAS: 64742-48-9	Dgr		
EC: 918-481-9	Asp. Tox. 1, H304		
REACH: 01-2119457273-39	EUH:066		
HYDROCARBONS, C10-C13,			
N-ALKANES, ISOALKANES, CYCLICS,			
<2% AROMATICS			
INDEX: 061	GHS06, GHS05, GHS09, GHS08	[1]	0 <= x % < 0.5
CAS: 55406-53-6	Dgr	[']	0 - 1/0 - 0.0
EC: 259-627-5	Acute Tox. 4, H302		
REACH: 01-2120762115-60	Skin Sens. 1, H317		
REACH. 01-2120102113-00	Eye Dam. 1, H318		
3-IODO-2-PROPYNYL	Acute Tox. 3, H331		
BUTYLCARBAMATE (IPBC)	STOT RE 1, H372		
	Aquatic Acute 1, H400		
	M Acute = $1$		
	Aquatic Chronic 1, H410		
	M Chronic = 1		
INDEX: 613-167-00-5	GHS06, GHS05, GHS09	B	0 <= x % < 0.05
CAS: 55965-84-9	Dgr		0 - 7 /0 - 0.00
	Acute Tox. 3, H301		
REACTION MASS OF	Acute Tox. 2, H310		
5-CHLORO-2-METHYL-2H-ISOTHIAZOL	Skin Corr. 1C, H314		
-3-ONE AND	Skin Sens. 1A, H317		
2-METHYL-2H-ISOTHIAZOL-3-ONE	Eye Dam. 1, H318		
(3:1)	Acute Tox. 2, H330		
()	Aquatic Acute 1, H400		
	M Acute = $100$		
	Aquatic Chronic 1, H410		
	M Chronic = 100		
	EUH:071		

(Full text of H-phrases: see section 16)

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter = 10 µm.

### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

# 4.1. Description of first aid measures

# In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

If a large quantity is inhaled, move the patient to the fresh air.

## In the event of splashes or contact with eyes :

Wash thoroughly with soft clean water for 15mn holding the eyelids open.

Refer to an ophthalmologist in particular if there is any redness, pain or visual impair.

#### In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

Wash thoroughly with soft clean water.

# In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

#### **SECTION 5 : FIREFIGHTING MEASURES**

This product is not classed as flammable.

#### 5.1. Extinguishing media

#### Suitable methods of extinction

- In the event of a fire, use :
- multipurpose ABC powder
- foam
- carbon dioxide (CO2)
- sprayed water or water mist

Alcohol resistant foam, CO2, Dry chemical powder.

#### Unsuitable methods of extinction

Direct water jet.

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- nitrogen oxide (NO)
- nitrogen dioxide (NO2)

## 5.3. Advice for firefighters

No data available.

# SECTION 6 : ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

## 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling. Remove and wash contaminated clothing before re-using.

Avoid getting on skin or in eyes when handling product.

### Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock between +5°C and +30°C in a dry, well ventilated place.

# Storage

Keep out of reach of children.

#### Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Vats
- Buckets

Suitable packaging materials :

- Coated steel

#### 7.3. Specific end use(s)

No data available.

# SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

# Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

TWA :	STEL :	Ceiling :	Definition :	Criteria :		
10 mg/m3			A4			
W (BAuA - TRGS 90	0, 08/08/2019) :					
VME :	VME :	Excess	Notes			
	0.005 ppm		2 (I)			
	0.058 mg/m <sup>3</sup>					
- ED984 / 2019-1487	·):					
VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :	
-	10	-	-	-	-	
- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :						
TWA :	STEL :	Ceiling :	Definition :	Criteria :		
- ppm	- ppm					
4 mg/m <sup>3</sup>	- mg/m³					
	10 mg/m3 W (BAuA - TRGS 90 VME : - ED984 / 2019-1487 VME-ppm : - orkplace exposure lim TWA : - ppm	10 mg/m3	10 mg/m3    Formalise      10 mg/m3    Image: Constraint of the second sec	10 mg/m3    Factor    Factor      10 mg/m3    A4      6W (BAuA - TRGS 900, 08/08/2019) :    Excess    Notes      VME :    VME :    Excess    Notes      0.005 ppm 0.058 mg/m³    2 (I)    2      - ED984 / 2019-1487) :    VLE-ppm :    VLE-mg/m3 :      - MME-nppm :    VME-mg/m3 :    VLE-ppm :      - 10    -    -      orkplace exposure limits, EH40/2005, 2011) :    TWA :    STEL :    Ceiling :    Definition :      - ppm    - ppm    - ppm    -    -    -	10 mg/m3    Factor of the second of	10 mg/m3    Factor of the second se

#### 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

- Type of gloves recommended :
- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# - Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

# **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

# General information :

Physical state :	Fluid liquid.		
Colour :	Depend on tones		
odours :	small		
Important health, safety and environmental information			

pH :	8.50 .		
	Slightly basic.		
Boiling point/boiling range :	Not specified.		
Flash point interval :	Not relevant.		
Vapour pressure (50°C) :	Not relevant.		
Vapour density :	>1		
Density :	> 1		
Water solubility :	Dilutable.		
Melting point/melting range :	Not specified.		
Self-ignition temperature :	Not relevant.		
Decomposition point/decomposition range :	Not specified.		
% VOC :	<11		
9.2. Other information	9.2. Other information		
VOC (g/l) :	129		

## **SECTION 10 : STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Avoid :

- frost

#### 10.5. Incompatible materials

No data available.

# 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

- nitrogen oxide (NO)
- nitrogen dioxide (NO2)

	SAFETY DATA SHEET (REGULATION (EC OWATROL PRO SOLID COLOR STAIN - S	, , ,	Version 9.1 (23-02-2021) - Page 6/9			
	SECTION 11 : TOXICOLOGICAL INFORM	IATION				
	11.1. Information on toxicological effects					
	-	ture may cause removal of natural fat from th	ne skin resulting in non-allergic contact dermatitis and			
	11.1.1. Substances					
	Acute toxicity :					
	3-IODO-2-PROPYNYL BUTYLCARBAMAT	ΓΕ (IPBC) (CAS: 55406-53-6)				
	Oral route :	LD50 = 1056 mg/kg				
		Species : Rat OCDE Ligne directrice 401 (To	xicité aiguë par voie orale)			
	Dermal route :	LD50 > 2000 mg/kg				
		Species : Rat				
		OCDE Ligne directrice 402 (To	xicité aiguë par voie cutanée)			
	HYDROCARBONS, C10-C13, N-ALKANES	S, ISOALKANES, CYCLICS, <2% AROMATI	CS (CAS: 64742-48-9)			
	Oral route :	LD50 > 5000 mg/kg				
		Species : Rat				
		OCDE Ligne directrice 401 (To	xicité aiguë par voie orale)			
	Dermal route :	LD50 > 5000 mg/kg				
		Species : Rabbit				
		OCDE Ligne directrice 402 (To	xicité aiguë par voie cutanée)			
	Inhalation route (Vapours) :	LC50 > 5000 mg/l				
		Species : Rat				
		OCDE Ligne directrice 403 (To	xicité aiguë par inhalation)			
þ	Germ cell mutagenicity :					
	HYDROCARBONS, C10-C13, N-ALKANES	S, ISOALKANES, CYCLICS, <2% AROMATI	CS (CAS: 64742-48-9)			
		No mutagenic effect.				
b	Carcinogenicity :					
	HYDROCARBONS, C10-C13, N-ALKANES	S, ISOALKANES, CYCLICS, <2% AROMATI	CS (CAS: 64742-48-9)			
	Carcinogenicity Test :	Negative.				
		No carcinogenic effect.				
þ	Reproductive toxicant :					
	HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)					
	No toxic effect for reproduction					
		OCDE Ligne directrice 414 (Étr prénatal)	ude de la toxicité pour le développement			
	11.1.2. Mixture					
	Respiratory or skin sensitisation :					
	Contains at least one sensitising substance	. May cause an allergic reaction.				
<b>b</b>	-	Monograph(s) from the IARC (International Agency for Research on Cancer) :				
-	CAS 128-37-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.					
	CAS 13463-67-7 : IARC Group 2B : The ag	ent is possibly carcinogenic to humans.				

# **SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

# 12.1. Toxicity

Insufficient data.

## 12.1.1. Substances

 $\sim$ 

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6) Fish toxicity : LC50 = 0.067 mg/l Species : Others

	FETY DATA SHEET (REGULATION (EC) n° 1907/200 VATROL PRO SOLID COLOR STAIN - SCS02	o - KEACH)	Version 9.1 (23-02-2021) - Page
		Duration of exposure : 96 h	
		NOEC = 0.0084 mg/l	
		Factor M = 1	
		Species : Pimephales promelas Duration of exposure : 35 jours	
	Crustacean toxicity :	EC50 = 0.16 mg/l Species : Daphnia magna	
		Duration of exposure : 48 h	
		EC50 mg/l	
		Species : Daphnia magna	
		Duration of exposure : 21 jours	
		Species : Others	
	Algae toxicity :	ECr50 = 0.022 mg/l	
		Species : Scenedesmus subspicatus	
		Duration of exposure : 72 h	
		NOEC = 0.0046 mg/l	
		Factor M = 1	
		Species : Scenedesmus subspicatus	
	HYDROCARBONS, C10-C13, N-ALKANES, ISOAL		2-48-9)
	Fish toxicity :	LC50 = 1000 mg/l Species : Oncorhynchus mykiss	
		Duration of exposure : 96 h	
	Crustacean toxicity :	EC50 = 1000 mg/l	
	-	Species : Daphnia magna	
		Duration of exposure : 48 h	
	Algae toxicity :	ECr50 = 1000 mg/l	
		Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h	
	12.1.2. Mixtures		
	12.2. Persistence and degradability Insufficient data.		
•	12.2.1. Substances		
	3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)		
	Biodegradability :	Rapidly degradable.	
	HYDROCARBONS, C10-C13, N-ALKANES, ISOAL Biodegradability :	ANES, CYCLICS, <2% AROMATICS (CAS: 64742 Rapidly degradable.	2-48-9)
		. apiers acgradatio.	
	12.2.2. Mixtures	no degradability data is available, the substanc	e is considered as not
	<b>C</b>	egrading quickly.	
	12.3. Bioaccumulative potential		
	12.3.1. Substances	(CAS: 55406.53.6)	
	3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) Octanol/water partition coefficient :	log Koe = 2.81	
	12.4. Mobility in soil		
	Contains volatile products that will disperse in air.		
	Contains a solid phase. This product is dilutable in water in all proportion		
	This product is dilutable in water in all proportion. 12.5. Results of PBT and vPvB assessment		
	No data available.		

#### 12.6. Other adverse effects

No data available.

#### **SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

# Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

#### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

## 14.1. UN number

- 14.2. UN proper shipping name
- -
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- -
- 14.5. Environmental hazards
- 14.6. Special precautions for user

#### **SECTION 15 : REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

- The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)
- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 129 g/l.

The permitted European levels of VOC in the ready-to-use product (category IIAe) are 150 g/l maximum in 2007 and 130 g/l maximum in 2010. - Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

#### **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a

# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PRO SOLID COLOR STAIN - SCS02

# guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

······································		
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H310	Fatal in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H351	Suspected of causing cancer .	
H372	Causes damage to organs through prolonged or repeated exposure .	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH071	Corrosive to the respiratory tract.	

#### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.