



**VIDEO** 



## OWACLEAN HULL AND DECK CLEANER

Description	OWACLEAN is a concentrated, solvent and acid free cleaner for the regular maintenance of hulls, decks and other surfaces.
Properties	<ul> <li>Quick and easy to use.</li> <li>Waterbased all-purpose cleaner – Removes dirt, grease and other surface contamination.</li> <li>Non-aggressive - Will not damage the surface.</li> <li>Concentrated formula - Highly economical.</li> <li>Residue and smear free after rinsing.</li> <li>Easy application.</li> <li>Removes mould and other similar marking.</li> </ul>
Basic uses	<ul> <li>Exterior use only.</li> <li>Horizontal and vertical surfaces.</li> <li>Glassfibre, Plastic, Stainless Steel, Anodised Aluminium, PVC, Paint</li> <li>Hulls, Decks, Handrails, Masts, Cabins</li> </ul>
Technical data	CONTAINS: Sodium Hydroxide Potassium Hydroxide Tetrasodium Ethylenediaminetetraacetate Amphoteric Surfactants <5% Ionic Surfactants ≥5% - <15% EDTA and salts ≥5% - <15% EDTA and salts ≥5% - <15% Appearance & Odour: Pale yellow / Light Solvent type: Water Specific gravity at 25°C (77°F): 1.08 ± 0.02 PH: 12-13 Flash point: Non-flammable Drying times (at 20°C (68°F) and 50% RH): 24 hours before applying a finish. Depending on temperature and humidity. Container size: 1Ltr Shelf life: Indefinite VOC: N/A
Application tools	Pump Sprayer, Brush, Sponge, Roller, Hose, Power Washer.
Good application practice	Cover everything you do not wish to clean.  Apply between 10°C (50°F) and 25°C (77°F).  Do not apply in direct sunlight or to hot surfaces.  When applying by spray, adjust nozzle to prevent formation of a mist.  Always test on a small inconspicuous area first.  Use appropriate protective clothing – Gloves, Goggles
Dilutions	Adjust dilution according to degree of surface dirt. As a guide: - Dirty Surfaces: 1 part OWACLEAN to 20 parts Water Very Dirty Surfaces: 1 part OWACLEAN to 10 parts Water. Concentrated formula. <b>Do not use undiluted.</b>
Application	Make up diluted solution as dictated by the surface contamination.  Stir or shake solution well to ensure OWACLEAN is well mixed in.  Apply diluted OWACLEAN to surface using brush, sponge, roller or pump sprayer.  Allow to work 10 minutes.  Do not allow solution to dry on the surface while working.  Rinse surface with fresh clean water using a hose, power washer or bucket and sponge (change water regularly). The use of a powerwasher ensures better dirt removal.  After cleaning check surface is clean by spraying on water. If water droplets form surface is not clean.  Repeat cleaning process.

Coverage	Diluted: 7m² (75ft²) to 10m² (107ft²) per Litre Actual coverage is dependent on condition of surface being cleaned.
Clean-up	Water
Storage	Keep from freezing and high temperatures. Store in original container and close lid tightly after use. Store in cool, dry place.
General information	Every care is taken to ensure that the information provided in this technical data sheet is accurate. <b>Owatrol International</b> is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at <a href="info@owatrol.com">info@owatrol.com</a> or the local Owatrol Agent for your country.  The information above is correct at the date of issue.  All other OWATROL products named in this document should be used as per label instructions and the technical data sheet.
Safety	Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children.
Issue date	October 2016

<sup>\*</sup> Same manufacturer

Owatrol Marine is a trademark

