



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OWATROL PRO PRIMAFLOOR 2 IN 1 Product code : PRFL220.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and varnish

1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..

Address : Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.

Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.

info@durieu.com www.durieu.com

1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

| Additional labeling : | | | | | |
|------------------------------|--|--|--|--|--|
| EUH208 | Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction. | | | | |
| EUH208 | Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND | | | | |
| | 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction. | | | | |
| Precautionary statements - C | General : | | | | |
| P101 | If medical advice is needed, have product container or label at hand. | | | | |
| P102 | Keep out of reach of children. | | | | |

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

| Identification | (EC) 1272/2008 | Note | % |
|---------------------------------|----------------|------|-----------------|
| INDEX: 008 | | [1] | 2.5 <= x % < 10 |
| CAS: 34590-94-8 | | | |
| EC: 252-104-2 | | | |
| REACH: 01-2119450011-60 | | | |
| | | | |
| (2-METHOXYMETHYLETHOXY)PROPANOL | | | |

| ETY DATA SHEET (REGULATION (EC) n° ATROL PRO PRIMAFLOOR 2 IN 1 - PRFL22 | , | Versio | n 7.1 (10-06-2021) - Page 2/8 |
|---|---|--------|-----------------------------------|
| INDEX: 154 CAS: 111-90-0 EC: 203-919-7 REACH: 01-2119475105-42 2-(2-ETHOXYETHOXY)ETHANOL INDEX: PCP226 CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23 | GHS07 Wng Eye Irrit. 2, H319 | [1] | 2.5 <= x % < 10 0 <= x % < 2.5 |
| PROPANE-1,2-DIOL INDEX: 199 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60 1,2-BENZISOTHIAZOL-3(2H)-ONE | GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1 | | 0 <= x % < 0.05 |
| INDEX: 613-167-00-5 CAS: 55965-84-9 REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL -3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) | GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH:071 | B | 0 <= x % < 0.05 |

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- dry chemical agents
- carbon dioxide (CO2)
- sprayed water or water mist

Unsuitable methods of extinction

Direct water jet.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock between +5°C and +30°C in a dry, well ventilated place. Keep only in the original container

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

| European Union (2010 | 11001 0017/0000 | 2017/161 | 2000/464 | 20000/45/05 | 2000/20/05 | 00/04/00 |
|------------------------|-----------------|-------------|-----------|-------------|-------------|------------|
| - European Union (2019 | 1031. ZUT7/Z390 | . 2017/104. | 2009/101. | 2000/15/CE. | 2000/39/CE. | 90/24/UE1: |

| CAS VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|-----------------|-----------|-------------|-----------|---------|
|-----------------|-----------|-------------|-----------|---------|

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PRO PRIMAFLOOR 2 IN 1 - PRFL220

| 34590-94-8 | 308 | 50 | - | - | Peau | |
|--------------|-----------------------|------------------------|----------------------|-------------------------|--------------|----------|
| - ACGIH TL | V (American Conferent | ence of Governmental | Industrial Hygienist | s, Threshold Limit Valu | ies, 2010) : | 1 |
| CAS | TWA : | STEL : | Ceiling : | Definition : | Criteria : | |
| 34590-94-8 | 100 ppm | 150 ppm | | Skin | | |
| - Germany | - AGW (BAuA - TRG | S 900, 08/08/2019) : | | | | |
| CAS | VME : | VME : | Excess | Notes | | |
| 34590-94-8 | | 50 ppm | | 1(I) | | |
| | | 310 mg/m ³ | | | | |
| 111-90-0 | | 6 ppm | | 2(I) | | |
| | | 35 mg/m ³ | | | | |
| - France (IN | NRS - ED984 / 2020- | 1546) : | | | | |
| CAS | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP No : |
| 34590-94-8 | 50 | 308 | - | - | * | 84 |
| - UK / WEL | (Workplace exposur | e limits, EH40/2005, F | ourth Edition 2020) | : | | |
| CAS | TWA : | STEL : | Ceiling : | Definition : | Criteria : | |
| 34590-94-8 | 50 ppm | | | Sk | | |
| | 308 mg/m ³ | | | | | |
| 57-55-6 | 10 mg/m ³ | | | | | |
| 8.2 Exposure | e controls | | | | | |

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :

Fluid liquid.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PRO PRIMAFLOOR 2 IN 1 - PRFL220

| Colour : | Depend on tones | | | | |
|--|--|--|--|--|--|
| Important health, safety and environmental information | Important health, safety and environmental information | | | | |
| pH : | 8.50 . | | | | |
| | Slightly basic. | | | | |
| Boiling point/boiling range : | Not specified. | | | | |
| Flash point interval : | Not relevant. | | | | |
| Vapour pressure (50°C) : | Not relevant. | | | | |
| Vapour density : | >1 | | | | |
| Density : | >1 | | | | |
| Water solubility : | Dilutable. | | | | |
| Viscosity : | 12-14 sec (n°4 - ISO2431) | | | | |
| Melting point/melting range : | Not specified. | | | | |
| Self-ignition temperature : | Not relevant. | | | | |
| Decomposition point/decomposition range : | Not specified. | | | | |
| % VOC : | <5 | | | | |
| 9.2. Other information | | | | | |
| VOC (g/l) : | 100 | | | | |

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

Always stock in its original packaging. Do not transfer in another package.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Dermal route :

Dermal route :

Acute toxicity :

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) Oral route :

PROPANE-1,2-DIOL (CAS: 57-55-6) Oral route :

LD50 = 22000 mg/kg Species : Rat

LD50 = 597 mg/kg

LD50 > 2000 mg/kg

OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Species : Rat

Species : Rat

LD50 > 2000 mg/kg Species : Rabbit

Inhalation route (Dusts/mist) :

LC50 > 315642 mg/l Species : Rabbit

~

Respiratory or skin sensitisation : PROPANE-1,2-DIOL (CAS: 57-55-6) Local lymph node stimulation test :

Non-Sensitiser. Species : Rabbit OCDE Ligne directrice 406 (Sensibilisation de la peau)

OCDE Ligne directrice 406 (Sensibilisation de la peau)

OCDE Ligne directrice 406 (Sensibilisation de la peau)

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

| 12.1.1. Substances | |
|---|---|
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) | |
| Fish toxicity : | LC50 = 0.74 mg/l |
| | Duration of exposure : 96 h |
| Crustacean toxicity : | EC50 = 2.44 mg/l |
| | Species : Daphnia magna |
| | Duration of exposure : 48 h |
| PROPANE-1,2-DIOL (CAS: 57-55-6) | |
| Fish toxicity : | LC50 = 40613 mg/l |
| | Species : Oncorhynchus mykiss |
| | Duration of exposure : 96 h |
| | OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë) |
| Crustacean toxicity : | EC50 = 18340 mg/l |
| | Species : Ceriodaphnia dubia |
| | Duration of exposure : 48 h |
| | OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate) |
| Algae toxicity : | ECr50 = 19000 mg/l |
| | Species : Pseudokirchnerella subcapitata |
| | Duration of exposure : 96 h |
| | OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance) |
| 12.1.2. Mixtures | |
| No aquatic toxicity data available for the mixture. | |
| 12.2. Persistence and degradability | |
| 12.2.1. Substances | |
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) | |
| Biodegradability : | Rapidly degradable. |
| blouegradability. | Rapidly degradable. |
| PROPANE-1,2-DIOL (CAS: 57-55-6) | |
| Biodegradability : | no degradability data is available, the substance is considered as not degrading quickly. |
| 12.3. Bioaccumulative potential | |
| 12.3.1. Substances | |
| 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) | |
| Octanol/water partition coefficient : | log Koe = 0.4 |
| | |

Bioaccumulation :

C

BCF = 1.4

12.4. Mobility in soil

Contains a solid phase.

Contains volatile products that will disperse in air. This product is dilutable in water in all proportion.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

08 01 11 * waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- _
- 14.5. Environmental hazards
- 14.6. Special precautions for user

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

- The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)
- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 51 g/l.

The permitted European level of VOC in the ready-to-use product (category IIAi) is 140 g/l maximum (2007/2010).

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

| • • • • | • |
|---------|---|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |
| | |

Abbreviations :

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.