

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING



#### 1.1. Product identifier

Product name: OWATROL TRANSYL AEROSOL

Product code: tr001a.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Release oil - Lubricant

# 1.3. Details of the supplier of the safety data sheet

Registered company name: DURIEU S.A.: Siège Social.

Address: 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE. Telephone: + 33 (0)1.60.86.48.70. Fax: + 33 (0)1.60.86.84.84.

reglementaire@durieu.com

www.durieu.com

#### 1.4. Emergency telephone number: + 33 (0)1.45.42.59.59.

Association/Organisation: INRS / ORFILA www.centres-antipoison.net.

#### Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture



# In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).



# 2.2. Label elements

The mixture is an aerosol fitted with a sealed spray attachment.

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS02

Signal Word : DANGER

Additional labeling:

EUH208 Contains LIMONENE. May produce an allergic reaction.

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

OWATROL TRANSYL AEROSOL - TR001A

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Precautionary statements - Storage:

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 122°F.

Precautionary statements - Disposal:

P501 Dispose of contents / container in a waste collection point.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures



#### Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: T9	GHS08		25 <= x % < 50
CAS: 64742-53-6	Dgr		
EC: 265-156-6	Asp. Tox. 1, H304		
REACH: 01-2119480375			
DISTILLATES (PETROLEUM),			
HYDROTREATED LIGHT NAPHTHENIC			
INDEX: PCP186	GHS08		25 <= x % < 50
CAS: 64742-48-9	Dgr		
EC: 918-481-9	Asp. Tox. 1, H304		
REACH: 01-2119457273-39	EUH:066		
HYDROCARBONS, C10-C13,			
N-ALKANES, ISOALKANES, CYCLICS,			
<2% AROMATICS			
INDEX: 298	GHS09, GHS07, GHS08		10 <= x % < 25
CAS: 1189173-42-9	Dgr		
EC: 918-811-1	Asp. Tox. 1, H304		
REACH: 01-2119463583-34	STOT SE 3, H336		
	Aquatic Chronic 2, H411		
HYDROCARBONS, C10, AROMATICS,	EUH:066		
<1% NAPHTALENE			
INDEX: 165	GHS07, GHS04	[1]	2.5 <= x % < 10
CAS: 10024-97-2	Wng		
EC: 233-032-0	Press. Gas, H280		
	STOT SE 3, H336		
OXYDE DE DIAZOTE			
INDEX: 008		[1]	0 <= x % < 2.5
CAS: 34590-94-8		-	
EC: 252-104-2			
REACH: 01-2119450011-60			
(2-METHOXYMETHYLETHOXY)PROPANOL			
INDEX: 094	GHS07, GHS09, GHS08, GHS02		0 <= x % < 1
CAS: 8028-48-6	Dgr		
EC: 232-433-8	Flam. Liq. 3, H226		
	Asp. Tox. 1, H304		
LIMONENE	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Aquatic Chronic 2, H411		
	' ' '		

Specific concentration limits:

# OWATROL TRANSYL AEROSOL - TR001A Identification Specific concentration limits AT INDEX: 298 int

Identification	Specific concentration limits	AIE	
INDEX: 298		inhalation: ATE = 4.688 mg/l	
CAS: 1189173-42-9		4h	
EC: 918-811-1		(vapours)	
REACH: 01-2119463583-34			
HYDROCARBONS, C10, AROMATICS,			
<1% NAPHTALENE			

# Information on ingredients:

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

#### Other data:

Notes H and P (DIRECTIVE 67/548/CEE, ANNEXE I) are applicable.

# **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. description of first aid measures

#### In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

#### In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.



#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

Do not induce vomiting

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5: FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

# 5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.



# Unsuitable methods of extinction

In the event of a fire, do not use:

- water

water jet

Direct water jet.

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

#### 6.4. Reference to other sections

No data available.

# **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.



# Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Never inhale this mixture.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

# Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.



#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.



#### **Packaging**

Always keep in packaging made of an identical material to the original.

Suitable packaging materials:

- Steel

#### 7.3. Specific end use(s)

No data available.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1. Control parameters

# Occupational exposure limits:

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:		
34590-94-8	308	50	-	-	Peau		
- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):							
CAS	TWA:	STEL:	Ceiling :	Definition :	Criteria :		
10024-97-2	50 ppm			A4			

Skin

34590-94-8	100 ppm	150 ppm	
- Germany - AG	SW (BAuA - TRGS 90	0, 08/08/2019) :	

CAS	VME:	VME :	Excess	Notes
10024-97-2		100 ppm		2(II)
		180 mg/m³		
34590-94-8		50 ppm		1(I)
		310 mg/m <sup>3</sup>		

<sup>-</sup> France (INRS - ED984 / 2020-1546):

,						
CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
34590-94-8	50	308	-	-	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

,	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	·		
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria :
10024-97-2	100 ppm				
	183 mg/m³				
34590-94-8	50 ppm			Sk	
	308 mg/m <sup>3</sup>				

#### 8.2. Exposure controls

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

# - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Permeability time: >480 min for a thickness >0.45 mm

CEN recommendations : EN 420 and EN 374/3

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Category:

- FFP2

Type of mask with combined filters:

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- NOP3 (Blue + white)
- A1 (Brown)
- AX (Brown)

Particle filter according to standard EN143:

- P2 (White)

CEN recommendations: EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** 9.1. Information on basic physical and chemical properties Physical state Physical state: Fluid liquid. Colour Colour: Blue Odour Odour threshold: Not stated. **Melting point** Melting point/melting range : Not relevant. Freezing point Freezing point / Freezing range : Not stated. Boiling point or initial boiling point and boiling range Boiling point/boiling range: Not relevant. **Flammability** Flammability (solid, gas): Not stated. Lower and upper explosion limit 0.6 Explosive properties, lower explosivity limit (%): Explosive properties, upper explosivity limit (%): 7 Flash point Flash point interval: Not relevant. **Auto-ignition temperature** Self-ignition temperature : Not relevant. **Decomposition temperature** Decomposition point/decomposition range: Not relevant. pН pH (aqueous solution): Not stated. Not relevant. Kinematic viscosity Viscosity: Not stated. $v < 7 \text{ mm2/s} (40^{\circ}\text{C})$ Viscosity: Method for determining the viscosity: ISO 3104 (Petroleum products - Transparent and opaque liquids -

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)	Version 25.1 (06-07-2022) - Page 7/12
OWATROL TRANSYL AEROSOL - TR001A	
	Determination of kinematic viscosity and calculation of dynamic
	viscosity).
Solubility	
Water solubility:	Insoluble.
Fat solubility:	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C):	Not relevant.
Density and/or relative density	
Density:	0.845
	Method for determining the density :
	ISO 3507 (Laboratory glassware - Pycnometers).
Relative vapour density	
Vapour density :	>1
9.2. Other information	
VOC (g/l):	435
% VOC :	<52%
9.2.1. Information with regard to physical hazard classes	
No data available.	
Aerosols	

Not specified. Not specified.

Not specified.

Not specified. Not specified.

Not specified.

# Flame duration : 9.2.2. Other safety characteristics

No data available.

Chemical combustion heat:

Inflammation time : Deflagration density :

Flame height:

Inflammation distance:

# **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

# 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

# 10.5. Incompatible materials

Keep away from :

- water
- oxidising agents

# 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

# **SECTION 11: TOXICOLOGICAL INFORMATION**



# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as

mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

#### 11.1.1. Substances

#### Acute toxicity:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Oral route: LD50 > 5000 mg/kg

Species: Rat

OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route: LD50 > 2000 mg/kg

Species : Rabbit

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Vapours): LC50 = 4.688 mg/l

Species: Rat

OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

Duration of exposure: 4 h

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg

Species: Rat

OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route: LD50 > 5000 mg/kg

Species : Rabbit

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Vapours): LC50 > 5000 mg/l

Species: Rat

OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

# Germ cell mutagenicity:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

No mutagenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

No mutagenic effect.

# Carcinogenicity:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Carcinogenicity Test: Negative.

No carcinogenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Carcinogenicity Test : Negative.

No carcinogenic effect.

# Reproductive toxicant :

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

No toxic effect for reproduction

OCDE Ligne directrice 414 (Étude de la toxicité pour le développement

prénatal)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

No toxic effect for reproduction

OCDE Ligne directrice 414 (Étude de la toxicité pour le développement

prénatal)

# Specific target organ systemic toxicity - single exposure :

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS: 64742-53-6)

Oral route:

C > 5000 mg/kg poids corporel

Species: Rabbit

Dermal route: C > 5000 mg/kg poids corporel

Species: Rat

Inhalation route : C = 5.53 mg/l/4h

Species: Rat

#### 11.1.2. Mixture

#### Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.



#### Aspiration hazard:

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

#### 11.2. Information on other hazards

# **SECTION 12: ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

#### 12.1. Toxicity

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

#### 12.1.1. Substances

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9) Fish toxicity:

Species: Perca fluviatilis

Crustacean toxicity: EC50 <= 10 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 = 11 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure : 72 h

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Fish toxicity: LC50 = 1000 mg/l

Species : Oncorhynchus mykiss Duration of exposure : 96 h

Crustacean toxicity: EC50 = 1000 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 = 1000 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

# 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

# 12.2.1. Substances

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE (CAS: 1189173-42-9)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Biodegradability: Rapidly degradable.

# 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

Contains volatile products that will disperse in air.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Endocrine disrupting properties

No data available.

#### 12.7. Other adverse effects

No data available.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

# **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

#### 14.1. UN number or ID number

1950

#### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

# 14.3. Transport hazard class(es)

- Classification:



2.1

#### 14.4. Packing group

14.5. Environmental hazards

# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tur
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregati on	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	

# OWATROL TRANSYL AEROSOL - TR001A

	2.1	-	-	203	75 kg	203	150 kg	A145 A167	E0
								A802	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167	E0
								A802	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

# 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

#### - Container information:

No data available.

#### - Particular provisions :

Contains [x]% mass percentage of

[x] = 43.7 %

inflammable components.

#### 15.2. Chemical safety assessment

No data available

# **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3:

H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.



# Abbreviations :

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate
STEL: Short-term exposure limit
TWA: Time Weighted Averages
TMP: French Occupational Illness table
TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL TRANSYL AEROSOL - TR001A Version 25.1 (06-07-2022) - Page 12/12

SVHC : Substances of very high concern.