

DESCRIPTION

Johnstone's Trade Acrylic Durable Eggshell is a premium quality, low VOC, mid sheen coating that provides an extremely tough, stain resistant finish, ideal for all high traffic areas. Tested to meet Class 1 ISO 11998 for scrub resistance, it provides a low odour, quick drying finish that is resistant to condensation and regular cleaning, making it ideal for kitchens, bathrooms, schools, hospitals, food production areas, and public buildings.

RECOMMENDED USES

INTERIOR Suitable for interior use.



TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Mid sheen.

VOLUME SOLID

36%

COVERAGE

COVERAGE Johnstone's Trade Acrylic Durable Eggshell will cover up to 16 square metres per litre depending on the nature and porosity of the surface being painted.



FILM THICKNESS

Wet: 83µm, dry: 30µm.

DRYING TIME

RECOAT Touch dry in 1-2 hours. Recoatable after 3-4 hours under normal conditions.



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

THINNER

Thinner: Clean Water.

VOC CONTENT

EU Limit Value for this product (Cat A/a): 30g/l (2010) This product contains max 3g/l VOC



KEY PROPERTIES

- Extremely tough and stain resistant
- Ideal for use in kitchens and bathrooms
- Mid Sheen finish & non yellowing
- Mould resistant formulation*
- Class 1 scrub rating ISO 11998

PREPARATION

Apply all products in accordance with BS 6150: Code of practice for painting of buildings. All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime certain bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Trade Joncryl Water Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstones Trade datasheets call 01924 354945 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply with brush, roller and spray both conventional and airless. Seal all absorbent surfaces with a coat of Johnstone's Trade Acrylic Durable Eggshell thinned by up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix prior to use. Do not apply in temperatures below 8°C. Additional coats may be required with certain colours, or attempting a wide colour change. Conventional Spray: compatible with most equipment. Airless Spray: Un-thinned @ 2000 psi/207 bar with 517 tip.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

*Johnstone's Trade Acrylic Durable Eggshell contains a biocide to protect paint surface from mould degradation.

SIZES

2.5 Litre, 5 Litre.