

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830. - United Kingdom (UK)

## SAFETY DATA SHEET

## **INTERZONE 954 PART B**

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

**Product name** : INTERZONE 954 PART B

**Product code** : EAA964

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

### 1.3 Details of the supplier of the safety data sheet

International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

e-mail address of person : sdsfellinguk@akzonobel.com

responsible for this SDS

**National contact** 

#### 1.4 Emergency telephone number

National advisory body/Poison Centre (For use only by licensed medical professionals.)

Telephone number : +44 (0)844 892 0111

**Supplier** 

Telephone number : +46 8 33 12 31

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

**Product definition** : Mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

Version: 3 1/14

Date of issue/Date of revision 07/05/2017 AkzoNobel

# **X**International

## **SECTION 2: Hazards identification**

Hazard pictograms







Signal word : Danger

**Hazard statements**: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Avoid release to the environment. Do not eat, drink or smoke when using this

product.

**Response**: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF ON SKIN: Take off contaminated clothing and wash it before reuse. IF IN EYES: Immediately call a

POISON CENTER or physician.

**Storage**: Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazardous ingredients : benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

Amines, N-tallow alkyltrimethylenedi-, oleates

2,4,6-tris(dimethylaminomethyl)phenol

Supplemental label

elements

:

Wear appropriate respirator when ventilation is inadequate.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Туре

Date of issue/Date of revision

Version: 3

07/05/2017 2/14



#### **SECTION 3: Composition/information on ingredients** REACH #: ≥25 - ≤45 Acute Tox. 4. H302 benzyl alcohol 01-2119492630-38 Acute Tox. 4, H332 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5 [1] 3-aminomethyl-3,5, REACH #: ≥10 - ≤25 Acute Tox. 4, H302 5-trimethylcyclohexylamine 01-2119514687-32 Acute Tox. 4, H312 Skin Corr. 1B, H314 EC: 220-666-8 Skin Sens. 1, H317 CAS: 2855-13-2 Index: 612-067-00-9 Aquatic Chronic 3, H412 EC: 216-032-5 ≥10 - ≤25 Acute Tox. 4, H302 [1] m-phenylenebis (methylamine) CAS: 1477-55-0 Acute Tox. 4, H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412 [1] Amines, N-tallow REACH #: ≤10 Skin Corr. 1B, H314 alkyltrimethylenedi-, 01-2119974117-33 Aquatic Acute 1, H400 (M=100) EC: 263-186-4 oleates CAS: 61791-53-5 [1] 2,4,6-tris REACH #: ≤10 Acute Tox. 4, H312 01-2119560597-27 Skin Corr. 1C. H314 (dimethylaminomethyl) EC: 202-013-9 Skin Sens. 1, H317 phenol CAS: 90-72-2 [1] [2] 4-methylpentan-2-one REACH #: ≤5 Flam. Liq. 2, H225 01-2119473980-30 Acute Tox. 4, H332 EC: 203-550-1 Eve Irrit. 2, H319 CAS: 108-10-1 **STOT SE 3, H335** Index: 606-004-00-4 **EUH066** See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Nota (s)

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give General

anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running

3/14

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is Inhalation

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Date of issue/Date of revision

07/05/2017 Version: 3



# **XInternational**

## SECTION 4: First aid measures

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show the container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapour or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Skin contact : Causes severe burns. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. May cause burns to mouth, throat and stomach.

#### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

media

Unsuitable extinguishing : None known.

media

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

Date of issue/Date of revision

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

07/05/2017

Version: 3 4/14



## **SECTION 5: Firefighting measures**

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

nitrogen oxides

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 7.1 Precautions for safe handling

Date of issue/Date of revision 07/05/2017 Version: 3 5/14



## SECTION 7: Handling and storage

#### Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Vapours are heavier than air and may spread along floors. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

## 7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

solutions

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
1	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.  STEL: 416 mg/m³ 15 minutes.  STEL: 100 ppm 15 minutes.  TWA: 208 mg/m³ 8 hours.  TWA: 50 ppm 8 hours.

### **Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

## **PNECs**

No PNECs available

Date of issue/Date of revision

07/05/2017 Version: 3 6/14



## **SECTION 8: Exposure controls/personal protection**

#### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Skin protection

**Hand protection** 

: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

## **Appearance**

Physical state : Liquid.
Colour : Colourless.
Odour : Amine-like.
Odour threshold : Not available.

Date of issue/Date of revision

07/05/2017

Version : 3 7/14



## SECTION 9: Physical and chemical properties

: Not applicable. Melting point/freezing point : Not available.

Initial boiling point and

boiling range

: Lowest known value: 205.3°C (401.5°F) (benzyl alcohol).

Flash point : Closed cup: 86°C **Evaporation rate** : Not available. : Not available. Flammability (solid, gas)

Upper/lower flammability or

explosive limits

: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)

Vapour pressure : Not available. : Not available. Vapour density

Relative density : 1.03

Solubility(ies) : Insoluble in the following materials: cold water.

Partition coefficient: n-octanol/ : Not available.

water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available.

: Kinematic (room temperature): 190 mm<sup>2</sup>/s **Viscosity** 

**Explosive properties** : Not available. Oxidising properties : Not available.

#### 9.2 Other information

No additional information.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

: The product is stable. 10.2 Chemical stability

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	LC50 Inhalation Vapour	Rat	>4178 mg/l	4 hours
-	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1620 mg/kg	-
m-phenylenebis (methylamine)	LD50 Dermal	Rabbit	2 g/kg	-
	LD50 Oral	Rat	930 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rat	1280 mg/kg	-

Date of issue/Date of revision 07/05/2017

Version: 3 8/14





## **SECTION 11: Toxicological information**

LD50 Oral Rat 2169 mg/kg 4-methylpentan-2-one LD50 Oral Rat 2080 mg/kg

: Not available. Conclusion/Summary

**Acute toxicity estimates** 

Route	ATE value
Oral	971.5 mg/kg
Dermal	5322.4 mg/kg
Inhalation (vapours)	32.38 mg/l
Inhalation (dusts and mists)	10.73 mg/l

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16	-
				milligrams	
	Skin - Moderate irritant	Pig	-	100 Percent	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
m-phenylenebis	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
(methylamine)				Micrograms	
	Skin - Severe irritant	Rabbit	-	24 hours 750	-
				Micrograms	
2,4,6-tris	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
(dimethylaminomethyl) phenol				Micrograms	
	Skin - Mild irritant	Rat	-	0.025	-
				Mililiters	
	Skin - Severe irritant	Rat	-	0.25 Mililiters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2	-
				milligrams	
4-methylpentan-2-one	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				microliters	
	Eyes - Severe irritant	Rabbit	-	40 milligrams	
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	

Conclusion/Summary

: Not available.

**Sensitisation** 

Conclusion/Summary : Not available.

**Mutagenicity** 

: Not available. **Conclusion/Summary** 

**Carcinogenicity** 

**Conclusion/Summary** : Not available.

Reproductive toxicity

**Conclusion/Summary** : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4-methylpentan-2-one	Category 3		Respiratory tract irritation

## Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Date of issue/Date of revision

Not available.

07/05/2017

Version: 3 9/14

# **X.International.**

## **SECTION 11: Toxicological information**

Information on likely routes

of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation**: May give off gas, vapour or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion**: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Date of issue/Date of revision

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

07/05/2017

Other information : Not available.

**Version** : 3 10/14



## **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 17.4 to 21.5 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
Amines, N-tallow alkyltrimethylenedi-, oleates	Acute EC50 0.001 to 0.01 mg/l	Daphnia	48 hours
	Acute IC50 0.01 to 0.1 mg/l	Algae	72 hours
	Acute LC50 0.1 to 1 mg/l	Fish	96 hours
2,4,6-tris (dimethylaminomethyl) phenol	Acute LC50 175 mg/l	Fish - Cyprinus carpio	96 hours
4-methylpentan-2-one	Acute LC50 537000 to 557000 μg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 78 mg/l Fresh water	Daphnia - Daphnia magna	21 days

**Conclusion/Summary**: Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	-	low
3-aminomethyl-3,5,	0.99	-	low
5-trimethylcyclohexylamine			
m-phenylenebis	0.18	2.691534803	low
(methylamine)			
2,4,6-tris	0.219	-	low
(dimethylaminomethyl)			
phenol			
4-methylpentan-2-one	1.9	-	low

### 12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Date of issue/Date of revision

: 07/05/2017

AkzoNobel



## **SECTION 13: Disposal considerations**

**Hazardous waste** 

: The classification of the product may meet the criteria for a hazardous waste.

**Packaging** 

Methods of disposal

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT. Marine pollutant (Amines, N-tallow alkyltrimethylenedi-, oleates)	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	П	II	II
14.5 Environmental hazards	Yes.	Yes.	No.
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.  Tunnel code (E)	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

**IMDG Code Segregation** 

group

: Not applicable.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

Substances of very high concern

None of the components are listed.

Version: 3 12/14

Date of issue/Date of revision 07/05/2017 AkzoNobel



## **SECTION 15: Regulatory information**

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**Europe inventory** : Not determined.

**Special packaging requirements** 

Containers to be fitted with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable. Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**National regulations** 

References : Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation

(EC) No. 1272/2008 (CLP)

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Corr. 1B, H314	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

	- Caroaration motified
H302 H312 H314 H317 H319 H332 H335	Highly flammable liquid and vapour. Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.
	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
	H302 H312 H314 H317 H319 H332 H335 H400

07/05/2017 Version: 3 13/14

Date of issue/Date of revision



## **SECTION 16: Other information**

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

EUH066 Eye Irrit. 2, H319

Flam. Liq. 2, H225 Skin Corr. 1B, H314 Skin Corr. 1C, H314

Skin Sens. 1, H317 STOT SE 3, H335 ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 4
ACUTE TOXICITY (inhalation) - Category 4
ACUTE AQUATIC HAZARD - Category 1
LONG-TERM AQUATIC HAZARD - Category

Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3

Repeated exposure may cause skin dryness or cracking. SERIOUS EYE DAMAGE/ EYE IRRITATION - Category

FLAMMABLE LIQUIDS - Category 2

SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Date of printing
Date of issue/ Date of

Date of previous issue

revision

: 07/05/2017 : 07/05/2017

: 06/06/2016

Version : 3

### Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

Version: 3

Date of issue/Date of revision

07/05/2017

AkzoNobel