

Safety Data Sheet**HGA767 INTERZONE 762 RAL 9002 PART A****Version No. 4 Date Last Revised 06/01/12**

Conforms to the requirements of Regulation (EC) No.1907/2006 (REACH), Annex II and Regulation (EC) No.1272/2008

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier** INTERZONE 762 RAL 9002 PART A

Product Code HGA767

Registration Number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

For professional use only.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet**Manufacturer** International Paint Ltd.

Stoneygate Lane

Felling Gateshead

Tyne and Wear

NE10 0JY UK

Telephone No. +44 (0)191 469 6111**Fax No.** +44 (0)191 438 3711**1.4. Emergency telephone number****Manufacturer** +44 (0)191 469 6111 24hr**Official Advisory Body Telephone No.:**
Advice for Doctors and Hospitals

+44 (0)844 892 0111

Email sdsfellinguk@akzonobel.com**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Mixture NOT yet classified according to Regulation (EC) No. 1272/2008****Classification according to 67/548/EEC or 1999/45/EC.**

Xi Irritant.

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

2.2. Label elements**According to 1999/45/EC**



Irritant

Contains: Methyl methacrylate,
R36/37/38 Irritating to eyes, respiratory system and skin.
R43 May cause sensitisation by skin contact.

S23 Do not breathe vapour/spray.
S24 Avoid contact with skin.
S37 Wear suitable gloves.
S51 Use only in well-ventilated areas.

P. Phrases;

2.3. Other hazards

This product contains no PBT/vPvB chemicals.

SECTION 3: Composition/information on ingredients

If the product contains substances that present a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC, or have occupational exposure limits detailed in EH40, these substances are listed below.

Ingredient/Chemical Designations	Weight %	67/548/EEC Classification	EC No. 1272/2008 Classification	Notes
Vinyltoluene CAS Number: 0025013-15-4 EC No. 246-562-2 Index No.: REACH Reg. No.:	25 - < 50	R10 Xi; R36/37/38	Flam. Liq. 3;H226 Skin Irrit. 2;H315 Eye Irrit. 2;H319	[1]
Methyl methacrylate CAS Number: 0000080-62-6 EC No. 201-297-1 Index No.: 607-035-00-6 REACH Reg. No.: 01-2119452498-28-xxxx	2.5 - < 10	F;R11 R43 Xi;R37/38	Flam. Liq. 2;H225 STOT SE 3;H335 Skin Irrit. 2;H315 Skin Sens. 1;H317	D [1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

Eye

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO². powder, water spray.

Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

In Storage

Handle containers carefully to prevent damage and spillage.
Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.
Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.
Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.

7.3. Specific end use(s)

There are no exposure scenarios, see details in section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The following workplace exposure limits have been established by the Health and Safety Executive as published in EH40.

Material	Short term (15 min. ave)		Long term (8hr TWA)		Comments
	ppm	mg/m ³	ppm	mg/m ³	
Methyl methacrylate	100	416	50	208	
Vinyltoluene	100	-	50	-	

For Key to entries in 'Comments' column see Section 16

DNEL/PNEC values

No Data Available

8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Eye/face protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should meet the requirements of standard EN 166.

Skin protection

For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended gloves: Viton® or Nitrile
Breakthrough Time: 480 min

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Other

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. For maximum protection when spraying this product it is recommended that a multi layer combination type filter, such as ABEK1, is used. In confined spaces use compressed air or fresh air respiratory equipment.

Thermal hazards

No Data Available

SECTION 9: Physical and chemical properties
--

Appearance	Coloured Liquid
Odour	
Odour threshold	Not Measured
pH	Not Measured
Melting point / freezing point (°C)	Not Measured
Initial boiling point and boiling range (°C)	101
Flash point (°C)	56
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapour pressure (Pa)	Not Measured

Vapour density	Heavier than air.
Relative density	1.15
Solubility(ies)	Immiscible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature (°C)	Not Measured
Decomposition temperature (°C)	Not Measured
Viscosity (cSt)	Not Measured

9.2. Other information

No further information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

10.3. Possibility of hazardous reactions

May react exothermically with: oxidising agents, strong alkalis, strong acids.

10.4. Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

10.6. Hazardous decomposition products

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

SECTION 11: Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Methyl methacrylate - (80-62-6)	5,000.00, Rat	5,000.00, Rabbit	29.80, Rat	Not Available

Vinyltoluene - (25013-15-4)	2,255.00, Rat	Not Available	Not Available	Not Available
-----------------------------	---------------	---------------	---------------	---------------

SECTION 12: Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Vinyltoluene - (25013-15-4)	Not Available	Not Available	0.00 (hr),
Methyl methacrylate - (80-62-6)	79.00, Oncorhynchus mykiss	69.00, Daphnia magna	170.00 (96 hr), Selenastrum capricornutum

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

European Waste Catalogue Classification: 08 01 12 Waste paint other than those mentioned in 08 01 11

SECTION 14: Transport information

14.1. UN number

1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

ADR/RID/ADN

UN1263 Paint, 3, III

IMDG	class/div 3	Sub Class -
	Segregation Group	No segregation group appropriate

EmS	F-E,S-E
------------	---------

ICAO/IATA	Air class 3	Sub Class -
------------------	--------------------	--------------------

14.4. Packing group	III
----------------------------	-----

14.5. Environmental hazards

ADR/RID/ADN Environmentally Hazardous: No

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

SECTION 15: Regulatory information

EU Legislation

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

National Legislation

UKSI 2009 No. 716 CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS 2009.

SECTION 16: Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and

conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

The information in this Health & Safety Data Sheet is required pursuant to EC Regulation 1907(2006) and the Chemicals (Hazard Information & Packaging for Supply) Regulations 2009.

Key to 'Comments' column in Section 8.

(+) There is a risk of absorption through unbroken skin.

(C) Capable of causing cancer and/or heritable genetic damage.

(R) Suppliers recommended limit.

(S) Capable of causing occupational asthma.

The full text of the R, H & EUH phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

R10 Flammable.

R11 Highly flammable.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37/38 Irritating to respiratory system and skin.

R43 May cause sensitisation by skin contact.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 6: Accidental release measures

SECTION 8: Exposure controls/personal protection

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 13: Disposal considerations

End of document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com