

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830. - United Kingdom (UK)

### SAFETY DATA SHEET

### **Interprime 160 Pale Blue Etch Solution**

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Product name : Interprime 160 Pale Blue Etch Solution

Product code : GDA160

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Professional application of coatings and inks				
Uses advised against Reason				
All Other Uses				

#### 1.3 Details of the supplier of the safety data sheet

International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

e-mail address of person : sdsfellinguk@akzonobel.com

responsible for this SDS

**National contact** 

#### 1.4 Emergency telephone number

National advisory body/Poison Centre (For use only by licensed medical professionals.)

**Telephone number** : +44 (0)844 892 0111

**Supplier** 

**Telephone number** : +46 8 33 12 31

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Date of issue/Date of revision

Hazard pictograms



05/03/2018



### **SECTION 2: Hazards identification**

: Warning Signal word

**Hazard statements** : Flammable liquid and vapour.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : Not applicable.

**Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Avoid

release to the environment.

: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin Response

with water or shower.

: Keep cool. Storage

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label

elements

articles

Wear appropriate respirator when ventilation is inadequate.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

: Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Туре
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥10 - <20	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
ethanol	EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥10 - ≤25	Flam. Liq. 2, H225	-	[2]
Phosphoric acid, solution	EC: 231-633-2 CAS: 7664-38-2 Index: 015-011-00-6	≤8.5	Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Chronic 3, H412	В	[1] [2]
copper(II) carbonate copper(II) hydroxide (1: 1)	EC: 235-113-6 CAS: 12069-69-1 Index: 029-020-00-8	≤1	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-	[1]
methanol	EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≤1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311	-	[1] [2]

Date of issue/Date of revision 05/03/2018

Version: 4 2/14





SECTION 3: Composition/information on ingredients				
			cute Tox. 3, H331 TOT SE 1, H370	
		fu st	ee Section 16 for the Ill text of the H tatements declared bove.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Date of issue/Date of revision

**Eve contact** : No specific data.

Inhalation : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness

Skin contact : No specific data. Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

05/03/2018

Version: 4 3/14



### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Date of issue/Date of revision

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

05/03/2018

Version: 4 4/14





#### SECTION 6: Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations : Not available. Industrial sector specific : Not available. solutions

### SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

Date of issue/Date of revision

#### Occupational exposure limits

05/03/2018 5/14 Version: 4



### **ECTION 8: Exposure controls/personal protection**

Product/ingredient name	Exposure limit values
1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.  STEL: 560 mg/m³ 15 minutes.  STEL: 150 ppm 15 minutes.  TWA: 375 mg/m³ 8 hours.  TWA: 100 ppm 8 hours.
ethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 1920 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.
Phosphoric acid, solution	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 2 mg/m³ 15 minutes. TWA: 1 mg/m³ 8 hours.
methanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.  STEL: 333 mg/m³ 15 minutes.  STEL: 250 ppm 15 minutes.  TWA: 266 mg/m³ 8 hours.  TWA: 200 ppm 8 hours.

#### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

Date of issue/Date of revision

05/03/2018 Version: 4 6/14





### **SECTION 8: Exposure controls/personal protection**

#### Hand protection

: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state : Liquid.
Colour : Blue.
Odour : Solvent.
Odour threshold : Not available.
pH : Not applicable.
Melting point/freezing point : Not available.

Initial boiling point and

boiling range

: Lowest known value: 78.29°C (172.9°F) (ethanol).

Flash point : Closed cup: 33°C
Evaporation rate : Not available.
Flammability (solid, gas) : Not available.

Upper/lower flammability or

explosive limits

: Greatest known range: Lower: 3.3% Upper: 19% (ethanol)

Vapour pressure: Not available.Vapour density: Not available.

Relative density : 1.02

**Solubility(ies)** : Insoluble in the following materials: cold water.

Date of issue/Date of revision : 05/03/2018

Version : 4 7/14

**AkzoNobel** 



### SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

**Viscosity** : Kinematic (room temperature): 89 mm<sup>2</sup>/s

**Explosive properties** : Not available. Oxidising properties : Not available.

#### 9.2 Other information

No additional information.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous

decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
phosphoric acid	LD50 Oral	Rat	1.25 g/kg	-
copper(II) carbonate– copper(II) hydroxide (1:1)	LD50 Oral	Rat	159 mg/kg	-

Conclusion/Summary : Not available.

#### **Acute toxicity estimates**

Route	ATE value	
	6150 mg/kg	
Dermal	36753.5 mg/kg	
Inhalation (vapours)	275.4 mg/l	

#### Irritation/Corrosion

Date of issue/Date of revision

05/03/2018

Version: 4 8/14



### **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit		24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
methanol	Eyes - Moderate irritant	Rabbit		24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	40 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

**Conclusion/Summary** 

: Not available.

**Sensitisation** 

Conclusion/Summary

: Not available.

**Mutagenicity** 

**Conclusion/Summary** : Not available.

**Carcinogenicity** 

**Conclusion/Summary** : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-methoxy-2-propanol methanol	Category 3 Category 1		Narcotic effects Not determined

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

#### Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. Skin contact Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness

**Skin contact** : No specific data. Ingestion : No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Date of issue/Date of revision 05/03/2018

Version: 4 9/14



### **SECTION 11: Toxicological information**

**Short term exposure** 

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
phosphoric acid	Acute EC50 105 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 60 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 10000000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon	48 hours
		crangon - Adult	
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
1-methoxy-2-propanol	<1	-	low
methanol	-0.77	<10	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

Date of issue/Date of revision : 05/03/2018

Version : 4 10/14



### **SECTION 12: Ecological information**

**12.6 Other adverse effects** : No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

#### European waste catalogue (EWC)

Code number	Waste designation
EWC 08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### **Packaging**

Methods of disposal

: Dispose of containers contaminated by the product in accordance with local or national legal provisions. This material and its container must be disposed of as hazardous waste. Dispose of via a licensed waste disposal contractor.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.
Additional information	Special provisions 640 (E)  Tunnel code (D/E)	-	-

Date of issue/Date of revision

05/03/2018

AkzoNobel



### **SECTION 14: Transport information**

**IMDG Code Segregation** 

group

: Not applicable.

14.6 Special precautions for

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

#### **Annex XIV**

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**Europe inventory** : All components are listed or exempted.

#### **Special packaging requirements**

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger: Not applicable. Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **National regulations**

References : Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation

(EC) No. 1272/2008 (CLP)

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Date of issue/Date of revision 05/03/2018

Version: 4 12/14



### SECTION 16: Other information

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Procedure used to derive the classification according to Regulation (EC) No. 12/2/2008 [CLP/GHS]		
Classification		Justification
Flam. Liq. 3, H226 Aquatic Chronic 3, H412		On basis of test data Calculation method
Full text of abbreviated H statements	H225 H226 H301 H302 H311 H314 H319 H331 H332 H336 H370 H400 H410	Highly flammable liquid and vapour. Flammable liquid and vapour. Toxic if swallowed. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes serious eye irritation. Toxic if inhaled. Harmful if inhaled. May cause drowsiness or dizziness. Causes damage to organs. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of classifications : [CLP/GHS]	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 3, H412 Eye Irrit. 2, H319  Flam. Liq. 2, H225 Flam. Liq. 3, H226 Skin Corr. 1B, H314 STOT SE 1, H370  STOT SE 3, H336	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (inhalation) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Date of printing Date of issue/ Date of

Date of issue/Date of revision

revision

: 05/03/2018 : 05/03/2018

Date of previous issue : 01/06/2017

Version

#### **Notice to reader**

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety

Version: 4 13/14

05/03/2018



#### **SECTION 16: Other information**

laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

Date of issue/Date of revision : 05/03/2018

Version : 4 14/14