Safety Data Sheet ELASTOCOLOR WATERPROOF

Safety Data Sheet dated: 04/02/2020 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ELASTOCOLOR WATERPROOF

Trade code: 907K0900

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Water dispersion synthetic resin based paint

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD www.mapei.co.uk (office hour 8:30-17:30)

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)1684 299 886

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH210 Safety data sheet available on request.

Contains:

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: ELASTOCOLOR WATERPROOF

Hazardous components within the meaning of the CLP regulation and related classification:

| Quantity | Name | Ident. Numb. | Classification | Registration Number |
|----------------|----------------------------------------|--------------------------------|--------------------|-----------------------|
| ≥5 - <10 % | free crystalline silica (Ø >10 μ) | CAS:14808-60-7 EC:238-878-4 | | |
| ≥2.5 - <5 % | 2-(2-butoxyethoxy)ethanol | CAS:112-34-5 EC:203-961-6 | Eye Irrit. 2, H319 | 01-2119475104-44-XXXX |

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 1 of 10

| ≥1 - <2.5 % | 1-Phenoxypropan-2-ol | CAS:770-35-4 EC:212-222-7 | Eye Irrit. 2, H319 | 01-2119486566-23-XXXX |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| ≥1 - <2.5 % | free crystalline silica (Ø <10 μ) | CAS:14808-60-7 EC:238-878-4 | STOT RE 1, H372 | |
| ≥0.016 - <0.025 % | 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one | CAS:2634-33-5 EC:220-120-9 Index:613-088- 00-6 | Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 2, H411 | |
| ≥0.0015 - <0.005 % | 2-methyl-2H-isothiazol-3-one | CAS:2682-20-4 EC:220-239-6 | Acute Tox. 3, H311; Acute Tox. 3, H301; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 2, H330; Skin Corr. 1B, H314; Skin Sens. 1A, H317, M-Acute:10 | |
| <0.0015 % | reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) | EC:611-341-5 | Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 3, H301; Skin Corr. 1C, H314; Skin Sens. 1A, H317; Acute Tox. 2, H310; Acute Tox. 2, H330; Eye Dam. 1, H318, M-Chronic:100, M-Acute:100 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: N.A.

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand $% \left(1\right) =\left(1\right) \left(1\right)$

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 2 of 10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

| Component | OEL Type | Country | Ceiling | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Behaviour | Note |
|----------------------------------------|-------------|---------------|---------|-----------------------|---------------------|------------------------|----------------------|------------|-----------------------------------------------------------|
| free crystalline silica (Ø >10 μ) | NDS | POLAND | | 0,300 | | | | | frakcja respirabilna |
| | Nationa | I DENMARK | | 0,3 | | | | | DENMARK, inhalable aerosol inhalable aerosol |
| | Nationa | I DENMARK | | 0,100 | | | | | DENMARK, respirable aerosol respirable aerosol |
| | SUVA | GERMANY | | 0,150 | | | | | 50 μg/m³ (Partikel Durchmesser < 12 μm) - TRGS 906 |
| | Nationa | I SWITZERLAND | | 0,15 | | | | | Α |
| | ACGIH | NNN | | 0,025 | | | | | (R), A2 - Pulm fibrosis, lung cancer |
| | Nationa | I NORWAY | | 0,300 | | | | | K 7 |
| 2-(2- butoxyethoxy)ethanol | DFG | GERMANY | С | | | 100,5 | 15 | | |
| | ACGIH | | | | 10 | | | | hematologic, kidney and liver effects |
| | Nationa | I SWEDEN | | 68 | 10 | | | | |
| | EU | | | 67,5 | 10 | 101,2 | 15 | Indicative | |
| | Nationa | I FRANCE | | 68 | 10 | 101,2 | 15 | | |
| | Nationa | I SPAIN | | 67,5 | 10 | 101,2 | 15 | | |
| | Nationa | I GREECE | | 67,5 | 10 | 101,2 | 15 | | |
| | Nationa | I DENMARK | | 68 | 10 | | | | |
| | Nationa | I FINLAND | | 68 | 10 | | | | |
| | Nationa | I GERMANY | | 67 | 10 | | | | |
| | Nationa | I PORTUGAL | | 67,5 | 10 | 101,2 | 15 | | |
| | Nationa | I NORWAY | | 68 | 10 | 102 | 15 | | |
| | Nationa | I BELGIUM | | 67,5 | 10 | 101,2 | 15 | | |
| | NDS | POLAND | | 67 | | | | | |
| | NDSCh | POLAND | | | | 100 | | | |
| | CHE | SWITZERLAND | | | | 101 | 15 | | |
| | | | | | | | | | |

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 3 of 10

| | NDS | NETHERLANDS | | 50 | | 100 | | |
|----------------------------------------|----------|-------------------|---|-------|----|--------|----|--------------------------------------|
| | National | CZECH REPUBLIC | | 100 | | | | |
| | National | HUNGARY | | 67,5 | | 101,2 | | |
| | National | ESTONIA | | 67,5 | 10 | | | |
| | National | LATVIA | | 67,5 | 10 | 101,2 | 15 | |
| | National | CZECH REPUBLIC | С | | | 100 | | |
| | National | SLOVAKIA | С | | | 101,2 | | |
| | National | SLOVAKIA | | 67,5 | 10 | | | |
| | National | SLOVENIA | | 67,5 | 10 | 101,25 | 15 | |
| | National | UNITED KINGDOM | | 67,5 | 10 | 101,2 | 15 | |
| | National | BULGARIA | | 67,5 | 10 | 101,2 | 15 | |
| | National | ROMANIA | | 67,5 | 10 | 101,2 | 15 | |
| | TUR | TURKEY | | 67,5 | 10 | 101,2 | 15 | |
| | National | LITHUANIA | | 67,5 | 10 | 101,2 | 15 | |
| | National | CROATIA | | 67,5 | 10 | 101,2 | 15 | |
| free crystalline silica (Ø <10 μ) | ACGIH | NNN | | 0,025 | | | | (R), A2 - Pulm fibrosis, lung cancer |
| | National | SWEDEN | | 0,1 | | | | SWEDEN, respirable aerosol |
| | National | NORWAY | | 0,3 | | | | NORWAY, K 7 |
| | National | NORWAY | | 0,3 | | 0,6 | | DENMARK, inhalable aerosol |
| | National | NORWAY | | 0,1 | | 0,2 | | DENMARK, respirable aerosol |
| 2-methyl-2H-isothiazol-3- one | DFG | GERMANY | С | | | 0,4 | | |
| | CHE | SWITZERLAND | | | | 0,4 | | |

Predicted No Effect Concentration (PNEC) values

| Component | CAS-No. | PNEC Limit | Exposure Route | Exposure Frequency Remark |
|----------------------|----------|----------------|------------------------|---------------------------|
| 1-Phenoxypropan-2-ol | 770-35-4 | 0,1 mg/l | Fresh Water | |
| | | 0,01 mg/l | Marine water | |
| | | 0,38 mg/kg | Freshwater sediments | |
| | | 0,038 mg/kg | Marine water sediments | |

Derived No Effect Level. (DNEL)

| Component | CAS-No. | Worker Worke Industr Profes y ional | | Exposure Route | Exposure Frequency Remark |
|----------------------|----------|-------------------------------------------|---------------|------------------|----------------------------------|
| 1-Phenoxypropan-2-ol | 770-35-4 | 42 mg/kg | 21 mg/kg | Human Dermal | Long Term, systemic effects |
| | | 25,7 mg/m3 | | Human Inhalation | Long Term, systemic effects |
| | | | 3,65 mg/kg | Human Oral | Long Term, systemic effects |

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 4 of 10

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Liquid various

Odour: Characteristic Odour threshold: N.A.

pH: 8.50

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: N.A. Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A. Relative density: 1.25 g/cm3 Solubility in water: dispersible

Partition coefficient (n-octanol/water): N.A. - This product is a mixture

Auto-ignition temperature: N.A. - No explosive or spontaneous ignition in contact with air at room temperature

Decomposition temperature: N.A.

Viscosity: 3,000.00 cPs

Explosive properties: == - No components with explosive properties

Oxidizing properties: N.A. - No component with oxidizing properties

Solid/gas flammability: N.A.

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

free crystalline silica (\emptyset a) acute toxicity LD50 Oral > 2000 mg/kg

 $>10 \mu)$

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 5 of 10

LD50 Skin > 2000 mg/kg

2-(2-

butoxyethoxy)ethanol

LD50 Skin Rabbit = 2700 mg/kg

LD50 Oral Rat = 5660 mg/kg

1-Phenoxypropan-2-ol

a) acute toxicity

a) acute toxicity

a) acute toxicity

LD50 Oral Rat = 2830 mg/kg LD50 Skin Rabbit > 2000 mg/kg

LC50 Inhalation Rat > 5400 mg/m3 4h

free crystalline silica (Ø a) acute toxicity

 $<10 \mu$)

LD50 Oral Rat = 500 mg/kg

1,2-benzisothiazol-3(2H)- a) acute toxicity one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 1020 mg/kg

2-methyl-2H-isothiazol-3- a) acute toxicity

LD50 Oral Rat > 183 mg/kg

LD50 Skin Rat = 242 mg/kg LD50 Skin Rabbit = 200 mg/kg LD50 Oral Rat 232 mg/kg

LD50 Oral Rat = 120 mg/kg LC50 Inhalation Rat = 0,11 mg/l 4h

reaction mass of: 5-

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6] (3:1)

LD50 Oral Rat = 457 mg/kg

LC50 Inhalation Rat = 2,36 mg/l 4h LD50 Skin Rabbit = 660 mg/kg LD50 Oral Rat = 53 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of components with eco-toxicological properties

Date 29/09/2020 **Production Name ELASTOCOLOR WATERPROOF** Page n. 6 of

| Component | Ident. Numb. | Ecotox Infos |
|----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| 2-(2-butoxyethoxy)ethanol | CAS: 112-34-5 - EINECS: 203-961-6 | a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 1300 mg/L 96h EPA |
| | | a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna $> 100 \text{ mg/L} 48\text{h}$ IUCLID |
| | | a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus > 100 mg/L 96h IUCLID |
| 1-Phenoxypropan-2-ol | CAS: 770-35-4 - EINECS: 212-222-7 | a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96 |
| | | a) Aquatic acute toxicity: LC50 Daphnia = 370 mg/L 48 |
| | | a) Aquatic acute toxicity: EC50 Algae > 100 mg/L 72 |
| 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one | - CAS: 2634-33-5 - EINECS: 220-120-9 - INDEX: 613-088- 00-6 | a) Aquatic acute toxicity: LC50 Fish = 2,15000 mg/L |
| | | b) Aquatic chronic toxicity: NOEC Algae = 0,04030 mg/L 72h |
| | | b) Aquatic chronic toxicity: EC50 Algae = 0,11000 mg/L 72h |
| 2-methyl-2H-isothiazol-3-one | CAS: 2682-20-4 - EINECS: 220-239-6 | a) Aquatic acute toxicity: LC50 Fish = mg/L 96 |
| | | a) Aquatic acute toxicity: LC50 Daphnia = mg/L 48 |
| | | a) Aquatic acute toxicity: EC50 Algae = mg/L 72 |
| | | b) Aquatic chronic toxicity: NOEC Daphnia = mg/L |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) | | a) Aquatic acute toxicity: EC50 Daphnia = 0,12 mg/L 48 |
| | | a) Aquatic acute toxicity: LC50 Fish = 0,22 mg/L 96 |
| | | a) Aquatic acute toxicity: EC50 Algae = 0,048 mg/L 72 |
| | | b) Aquatic chronic toxicity: NOEC Algae = 0,0012 mg/L 72 |
| | | b) Aquatic chronic toxicity: NOEC Fish = 0,098 mg/L - 28 d |
| | | b) Aquatic chronic toxicity: NOEC Daphnia = 0,004 mg/L - 21 d |
| | **** | |

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

 $\label{lem:conditional} \textbf{Recover if possible. In so doing, comply with the local and national regulations currently in force.}$

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Product:

Do not dispose of waste into sewers.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to an authorized waste disposal service.

Contaminated packaging:

Empty remaining content.

Dispose of as unused product.

Do not re-use empty containers.

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 7 of 10

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N.A.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A

Road and Rail (ADR-RID):

N.A.

ADR-Hazard identification number: NA

Air (IATA):

N.A.

Sea (IMDG):

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 90 g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

German Water Hazard Class.

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 28, 55

SVHC Substances:

No data available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code Description

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 8 of 10

H319 Causes serious eye irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

| Code | Hazard class and hazard category | Description |
|-------|----------------------------------|------------------------------------------------------------------------|
| 3.3/2 | Eye Irrit. 2 | Eye irritation, Category 2 |
| 3.9/1 | STOT RE 1 | Specific target organ toxicity — repeated exposure, Category ${\bf 1}$ |

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures) BCF: Biological Concentration Factor

BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

 $\ensuremath{\mathsf{NIOSH}}\xspace$: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 9 of 10

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 5. FIRE-FIGHTING MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 13. DISPOSAL CONSIDERATIONS
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION

Date 29/09/2020 Production Name ELASTOCOLOR WATERPROOF Page n. 10 of 10