

DECLARATION OF PERFORMANCE N. CPR-GB1/0073

- 1) Unique identification code of the product-type: **MAPETHERM AR1 GG (white)**
- 2) Intended uses: **Designed general purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions**
- 3) Manufacturer: **MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD**
www.mapei.co.uk
- 4) Systems of AVCP: **System 4**
- 5) Harmonized standards: **EN 998-1:2010**

Notified bodies: **No task for the notified body**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A1
Water absorption:	W2
Water vapour permeability:	$\mu \leq 15$
Adhesion:	$\geq 1 \text{ N/mm}^2$ – FP:B
Thermal conductivity ($\lambda_{10, \text{dry}}$):	0,34 W/m*K (tab. mean value; P=50%)
Durability:	NPD
Release of dangerous substances:	see SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**

Halesowen, 10/04/2015



DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	First issue
--------------------------	--------------------

MAPETHERM AR1 GG (white)
CE MARKING
Annex to DoP N. CPR-GB1/0073



	 MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
14 CPR-GB1/0073 EN 998-1:2010 MAPETHERM AR1 GG (white) <i>Designed general purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions</i>	
Reaction to fire:	Class A1
Water absorption:	W2
Water vapour permeability:	$\mu \leq 15$
Adhesion:	≥ 1 N/mm ² – FP:B
Thermal conductivity ($\lambda_{10, dry}$):	0,34 W/m*K (tab. mean value; P=50%)
Durability:	NPD
Release of dangerous substances:	see SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.