

DECLARATION OF PERFORMANCE N. CPR-GB1/0074

- 1) Unique identification code of the product-type: **MAPEWALL GPR**
- 2) Intended uses: **General purpose rendering/plastering mortar for internal and external use**
- 3) Manufacturer: **MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD**

www.mapei.co.uk

- 4) Systems of AVCP: **System 4**
- 5) Harmonized standards: **EN998-1: 2010**

Notified bodies: **No task for the notified body**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A1
Water absorption:	W2
Water vapour permeability:	$\mu \leq 18$
Adhesion:	$\geq 0,4 \text{ N/mm}^2 \text{ FP:B}$
Thermal Conductivity ($\lambda_{10, \text{dry}}$):	$0.67 \text{ W/m}\cdot\text{K}$ (tab. mean value; P=50%)
Durability:	NPD
Dangerous substances:	See SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**



Halesowen, 24/11/2015

DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	First issue
-------------------	-------------

	 MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
15 CPR- GB1/0074 EN998-1: 2010 MAPEWALL GPR <i>General purpose rendering/plastering mortar for internal and external use</i>	
Reaction to fire:	Class A1
Water absorption:	W2
Water vapour permeability:	$\mu \leq 18$
Adhesion:	$\geq 0,4 \text{ N/mm}^2 \text{ FP:B}$
Thermal Conductivity ($\lambda_{10, \text{dry}}$):	0.67 W/m·K (tab. mean value; P=50%)
Durability:	NPD
Dangerous substances:	See SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.