

DECLARATION OF PERFORMANCE N. CPR-IT1/0292

- 1) Unique identification code of the product-type: **PLANITOP 210**
- 2) Intended uses: **General purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 998-1:2016**

Notified bodies: **The notified laboratory CSI SpA, N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class E
Water absorption:	W_c 2
Water vapour permeability:	μ ≤ 35
Adhesion:	≥ 1,0 N/mm² – FP:B
Thermal conductivity (λ_{10, dry}):	0,61 W/m·K (tab. mean value; P=50%)
Durability:	NPD
Dangerous substances:	NPD

- 7) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance.

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Lorenzo Martino – Corporate Quality Management**

Milan, 11/02/2020





DoP in Pdf format are available in the Mapei website.

Revision 2 notes:	Updated performances
--------------------------	-----------------------------

PLANITOP 210
CE MARKING
Annex to DoP N. CPR-IT1/0292



 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
12 CPR-IT1/0292 EN 998-1 PLANITOP 210 <i>General purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions</i>	
Reaction to fire:	Class E
Water absorption:	$W_C 2$
Water vapour permeability:	$\mu \leq 35$
Adhesion:	$\geq 1,0 \text{ N/mm}^2$ – FP:B
Thermal conductivity ($\lambda_{10, \text{dry}}$):	0,61 W/m·K (tab. mean value; P=50%)
Durability:	NPD
Dangerous substances:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.