

**DECLARATION OF PERFORMANCE N. CPR-GB1/0030**

- 1) Unique identification code of the product-type: **PLANITOP FAST 330**
- 2) Intended uses: **General purpose rendering/plastering mortar for internal and external use**

Manufacturer: **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD**

**www.mapei.co.uk**

- 3) Systems of AVCP: **System 2+**  
**System 3 (for reaction to fire)**

- 4) Harmonized standards: **EN 998-1**

Notified bodies: **the notified body BSI UK No. 0086, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

- 5) Performances declared:

Essential characteristics	Performances
Consistence	165mm
Dry density	1618kg/m <sup>3</sup>
Compressive strength 28dd	22.8 MPa (class CS IV)
Water vapour permeability	≤ 76μ
Water absorption coefficient	0.1 kg/(m <sup>2</sup> ·h <sup>0.5</sup> )
Reaction to fire	Class E
Dangerous substances:	See SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**

**Halesowen, 25/06/2016**



.....



*DoP in Pdf format are available in the Mapei website.*

Revision 1 notes:



**PLANITOP FAST 330**  
**CE MARKING**  
*Annex to DoP N. CPR-GB1/0030*



 0086	 MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD <a href="http://www.mapei.co.uk">www.mapei.co.uk</a>
<b>11</b> <b>CPR-GB1/0030</b> <b>EN 998-1</b> <b>PLANITOP FAST 330</b> <i>General purpose rendering/plastering mortar for internal and external use</i>	
Consistence	165mm
Dry density	1618kg/m <sup>3</sup>
Compressive strength 28dd	22.8 MPa (class CS IV)
Water vapour permeability	< 76μ
Water absorption coefficient	0.1 kg/(m <sup>2</sup> ·h0.5)
Reaction to fire	Class E
Dangerous substances:	See SDS

**Note:**

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.