# Safety Data Sheet SILANCOLOR "T" PLUS 1.5MM

Safety Data Sheet dated: 14/06/2022 - version 3



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: SILANCOLOR "T" PLUS 1.5MM

Trade code: 906XF9990

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Wall coating paste Uses advised against: Data not available

#### 1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# Regulation (EC) n. 1272/2008 (CLP)

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

#### **Hazard statements:**

H412 Harmful to aquatic life with long lasting effects.

# **Precautionary statements:**

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with applicable regulations.

**Special Provisions:** 

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH208 Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

# Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

# 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances

present in concentration >= 0.1%.

Other Hazards: No other hazards

Further hazards:

Methanol is released by hydrolysis during application.

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not Relevant

#### 3.2. Mixtures

Mixture identification: SILANCOLOR "T" PLUS 1.5MM

# Hazardous components within the meaning of the CLP regulation and related classification:

Concentra Name Ident. Numb. Classification Registration Number

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 1 of 13

tion (% w/w)			
≥0.1 - <0.25 %	Alcohols, C16-18 and C18-unsatd., ethoxylated	CAS:68920-66-1 EC:500-236-9	Skin Irrit. 2, H315; Aquatic Acute 1, H400; Aquatic Chronic 3, H412, M-Acute:1
≥0.025 - <0.05 %	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS:2634-33-5 EC:220-120-9 Index:613-088- 00-6	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411
			Specific Concentration Limits: C ≥ 0,05%: Skin Sens. 1 H317
≥0.016 - <0.025 %	free crystalline silica (Ø <10 $\mu$ )	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372
≥0.005 - <0.01 %	terbutryn	CAS:886-50-0 EC:212-950-5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, H302 Skin Sens. 1B, H317, M- Chronic:100, M-Acute:100
			Specific Concentration Limits: C ≥ 3%: Skin Sens. 1B H317
<0.0015 %	4,5-dichloro-2-octyl-2H-isothiazol- 3-one	CAS:64359-81-5 EC:264-843-8 Index:613-335- 00-8	Acute Tox. 2, H330 Acute Tox. 4, H302 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Corrosive to the respiratory tract., M-Chronic:100, M-Acute:100
			Specific Concentration Limits: $0.025\% \le C < 5\%$ : Skin Irrit. 2 H315 $0.025\% \le C < 3\%$ : Eye Irrit. 2 H319 $C \ge 0.0015\%$ : Skin Sens. 1A H317
			Acute Toxicity Estimate: ATE - Oral: 567mg/kg bw
<0.0015 %	2-octyl-2H-isothiazol-3-one	CAS:26530-20-1 EC:247-761-7 Index:613-112- 00-5	Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410, M-Chronic:100, M-Acute:100, EUH071
			Specific Concentration Limits: C ≥ 0,0015%: Skin Sens. 1A H317
			Acute Toxicity Estimate: ATE - Oral: 125mg/kg bw ATE - Dermal: 311mg/kg bw
<0.0015 %	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1)	EC:611-341-5 Index:613-167-	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic:100, M-Acute:100
			Specific Concentration Limits: $C \ge 0,6\%$ : Skin Corr. 1C H314 0,06% ≤ C < 0,6%: Skin Irrit. 2 H315 $C \ge 0,6\%$ : Eye Dam. 1 H318 0,06% ≤ C < 0,6%: Eye Irrit. 2 H319 $C \ge 0,0015\%$ : Skin Sens. 1A H317

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 2 of 13

CAS:50-00-0 EC:200-001-8 Index:605-001-

00-5

Acute Tox. 3, H311 Acute Tox. 3, 01-2119488953-20-XXXX H331 Acute Tox. 3, H301 Skin

Corr. 1B, H314 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350

Specific Concentration Limits:  $0.2\% \le C < 100\%$ : Skin Sens. 1 H317

 $5\% \le C < 25\%$ : Skin Irrit. 2 H315  $5\% \le C < 25\%$ : Eye Irrit. 2 H319  $5\% \le C < 100\%$ : STOT SE 3 H335  $25\% \le C < 100\%$ : Skin Corr. 1B

H314

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# 4.2. Most important symptoms and effects, both acute and delayed

Not available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

Not available

(see paragraph 4.1)

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

# 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

# 5.3. Advice for firefighters

Use suitable breathing apparatus.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

# 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 3 of 13

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

# 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

List of components wit	h OEL va	alue							
	OEL Type	Country Ceilin	ng Lon Ter ma		Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
free crystalline silica (Ø $<10~\mu$ ) CAS: 14808-60-7	Nationa	I SWEDEN	0,10		<b>PP</b>		pp		SWEDEN, respirable aerosol
	Nationa	I NORWAY	0,10	00					K: Chemicals to be treated as carcinogenic.
	NDS	POLAND	2,00	00					frakcja wdychalna
	NDS	POLAND	0,30	00					frakcja respirabilna
	Nationa	I DENMARK	0,3			0,600			DENMARK, inhalable aerosol inhalable aerosol
	Nationa	I DENMARK	0,10	00		0,200			DENMARK, respirable aerosol
	ACGIH		0,02	25					(R), A2 - Pulm fibrosis, lung cancer
	EU		0,02	25					A2 (R) - Pulm fibrosis, lung cancer
	Nationa	I AUSTRIA	0,1	50					A*
	ACGIH		0,02	25					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	Nationa	I SWEDEN	0,1						
	Nationa	I FRANCE	0,1						
	Nationa	I SPAIN	0,0	5					
	Nationa	I DENMARK	0,3						
	Nationa	I FINLAND	0,0	5					
	Nationa	I PORTUGAL	0,02	25					
	Nationa	I NORWAY	0,3			0,9			
	Nationa	I BELGIUM	0,1						
	NDS	POLAND	0,1						
	NDS	NETHERLANDS	0,0	75					
	Nationa	l CZECH REPUBLIC	0,1						
	Nationa	I HUNGARY	0,1	5					
	Malaysi a OEL	MALAYSIA	0,1						0.1 mg/m3 TWA (respirable dust)
	Nationa	I ESTONIA	0,1						
	Nationa	I SLOVAKIA	0,1			0,5			

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 4 of 13

	National SLOVENIA		0,1				
	National BULGARIA		0,07				
	National ROMANIA						
			0,1				
	National LITHUANIA		0,1				
	National CROATIA		0,1				
	National ITALY		0,100				
2-octyl-2H-isothiazol-3-	DFG GERMANY	С			54	10	
one CAS: 26530-20-1							
	National CERMANN		0.05				
	National GERMANY	_	0,05				
	CHE SWITZERLAN	D			0,1		
	National SLOVENIA		0,05		0,05		
formaldehyde CAS: 50-00-0	ACGIH	С				0,3	DSEN, RSEN, A2 - URT and eye irr
	DFG GERMANY	С			0,74	0,6	
	ACGIH			0,1		0,3	A1 - Confirmed Human Carcinogen; eye and upper respiratory tract irritation; upper respiratory tract cancer; dermal sensitizer; respiratory sensitizer
	National SWEDEN		0,37	0,3			
	National FRANCE		-,-	0,5		1	
	National SPAIN		0,37	0,3	0,74	0,6	
	National GREECE		2,5	2	2,5	2	
	National DENMARK	С	2,3	2	0,4	0,3	
		C	0.27	0.2	0,4	0,3	
	National FINLAND	6	0,37	0,3	1.0	4	
	National FINLAND	С	0.27	0.2	1,2	1	
	National GERMANY		0,37	0,3			
	National NORWAY		0,6	0,5			
	National NORWAY	С			1,2	1	
	NDS POLAND		0,37				
	NDSCh POLAND				0,74		
	CHE SWITZERLAN	D			0,74	0,6	
	NDS NETHERLAND	S	0,15		0,5		
	National CZECH REPUBLIC		0,5				
	National HUNGARY		0,6		0,6		
	Malaysi MALAYSIA a OEL	С			0,37	0,3	
	National PORTUGAL	С				0,3	
	National ESTONIA	-	0,6	0,5	1,2	1	
	National LATVIA		0,5	-,-	-,-	-	
	National CZECH REPUBLIC	С	3/3		1		
	National SLOVAKIA	С			0,74		
	National SLOVAKIA	C	0.37	UЗ	0,74		
			0,37	0,3	0.62	0.5	
	National SLOVENIA		0,62	0,5 2	0,62	0,5	
	National UNITED KINGDOM		2,5	2	2,5	2	
	National BULGARIA		1,0		2,0		
	National ROMANIA		1,2	1	3	2	
	National LITHUANIA		0,6	0,5			
	National LITHUANIA	С			1,2	1	
	National CROATIA		2,5	2	2,5	2	

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 5 of 13

ΕU 0,37 Bindina 0,3

#### Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency Remark
formaldehyde CAS: 50-00-0	0,47 mg/l	Fresh Water	
	0,47 mg/l	Marine water	
	4,7 mg/l	Intermittent release	
	0,19 mg/l	Microorganisms in sewage treatments	
	2,44 mg/kg	Freshwater sediments	
	2,44 mg/kg	Marine water sediments	
	0,21 mg/kg	Soil	

#### **Derived No Effect Level. (DNEL)**

	Worker Worker Industr Profess y ional		Exposure Route	Exposure Frequency Remark			
formaldehyde CAS: 50-00-0	1 mg/m3		Human Inhalation	Short Term, local effects			
	240 mg/kg	102 mg/kg	Human Dermal	Long Term, systemic effects			
	9 mg/m3	3,2 mg/m3	Human Inhalation	Long Term, systemic effects			
	0,037 mg/cm2	0,012 mg/cm2	Human Dermal	Long Term, local effects			
	0,5 mg/m3	0,1 mg/m3	Human Inhalation	Long Term, local effects			
		4,1 mg/kg	Human Oral	Long Term, systemic effects			

# 8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

In case of insufficient ventilation use mask with AX filters (EN 14387).

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance: paste Color: various

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: Not available

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not available Viscosity: Not available

Kinematic viscosity: Not available Solubility in water: partly soluble Solubility in oil: Not available

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: Not available Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available No other relevant information

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

# 10.3. Possibility of hazardous reactions

None

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

None in particular.

# 10.6. Hazardous decomposition products

None.

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicological information of the mixture:

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

 Print date
 05/08/2022
 Production Name
 SILANCOLOR "T" PLUS 1.5MM
 Page n.
 7 of 13

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

#### Toxicological information on main components of the mixture:

1,2-benzisothiazol-3(2H)- a) acute toxicity

one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 670, mg/kg

free crystalline silica (Ø a) acute toxicity

<10 µ)

LD50 Oral Rat = 500 mg/kg

terbutryn a) acute toxicity LD50 Skin Rabbit > 10200 mg/kg

LC50 Inhalation Rat > 8 g/m3 4h LD50 Oral Rat = 2045 mg/kg LD50 Skin Rabbit > 10200 mg/kg

4,5-dichloro-2-octyl-2H- a) acute toxicity

isothiazol-3-one

oxicity ATE - Oral : 567 mg/kg bw

LC50 Inhalation Dust Rat = 0,16 mg/l

LD50 Oral Rat = 567, mg/kg

ATE - Oral: 125 mg/kg bw

2-octyl-2H-isothiazol-3- a) acute toxicity

one

ATE - Dermal : 311 mg/kg bw LD50 Oral Rat = 318 mg/kg

LD50 Skin Rabbit = 311 mg/kg

LC50 Inhalation Dust Rat = 0,58 mg/l 4h

reaction mass of: 5- a) acute toxicity

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6] (3:1) LC50 Inhalation Rat = 2,36 mg/l 4h

LD50 Skin Rabbit = 660, mg/kg LD50 Oral Rat = 53, mg/kg

formaldehyde a) acute toxicity LD50 Oral Rat = 700 mg/kg

LC50 Inhalation Rat = 0,578 mg/l LD50 Skin Rabbit = 270 mg/kg LD50 Skin Rabbit = 270 mg/kg LC50 Inhalation Rat = 0,578 mg/l 4h

LD50 Oral Rat = 100 mg/kg

# 11.2 Information on other hazards

# **Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 8 of 13

# List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

# List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
1,2-benzisothiazol-3(2H)-one; 1,2 benzisothiazolin-3-one	- CAS: 2634-33-5 - EINECS: 220- 120-9 - INDEX: 613-088-00-6	a) Aquatic acute toxicity: LC50 Fish = 2,15 mg/L
		b) Aquatic chronic toxicity: NOEC Algae = 0,0403 mg/L 72h
		b) Aquatic chronic toxicity: EC50 Algae = 0,11 mg/L 72h
		b) Aquatic chronic toxicity: EC10 Algae = 0,04 mg/L 72h
		b) Aquatic chronic toxicity: EC50 Daphnia = 3,27 mg/L 48h
		NOEC Daphnia = 1,2 mg/L 21d
terbutryn	CAS: 886-50-0 - EINECS: 212- 950-5	a) Aquatic acute toxicity: EC50 Daphnia = 6,4 mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = 0,0067 mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = 1,9 mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = 0,05 mg/L - 21d
		b) Aquatic chronic toxicity: NOEC Fish = 0,073 mg/L - 28d
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	CAS: 64359-81- 5 - EINECS: 264-843-8 - INDEX: 613- 335-00-8	a) Aquatic acute toxicity: EC50 Daphnia = mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = mg/L
		b) Aquatic chronic toxicity: NOEC Fish = mg/L
2-octyl-2H-isothiazol-3-one	CAS: 26530-20- 1 - EINECS: 247-761-7 - INDEX: 613- 112-00-5	a) Aquatic acute toxicity: EC50 Daphnia = 0,42 mg/L 48
		a) Aquatic acute toxicity: EC50 Algae = 0,084 mg/L 72
		a) Aquatic acute toxicity: LC50 Fish = 0,036 mg/L 96
		a) Aquatic acute toxicity: LC50 Fish = 0,18 mg/L 96
		b) Aquatic chronic toxicity: NOEC Daphnia = 0,002 mg/L - 21 d
		b) Aquatic chronic toxicity: NOEC Fish = 0,022 mg/L - 28 d
		b) Aquatic chronic toxicity: NOEC Algae = 0,004 mg/L 72
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)		a) Aquatic acute toxicity: EC50 Daphnia = 0,12 mg/L 48
		a) Aquatic acute toxicity: LC50 Fish = 0,22 mg/L 96
		a) Aquatic acute toxicity: EC50 Algae = 0,048 mg/L 72
		b) Aquatic chronic toxicity: NOEC Algae = 0,0012 mg/L 72
		b) Aquatic chronic toxicity: NOEC Fish = 0,098 mg/L - 28 d
		b) Aquatic chronic toxicity: NOEC Daphnia = 0,004 mg/L - 21 d
formaldehyde	CAS: 50-00-0 - EINECS: 200- 001-8 - INDEX: 605-001-00-5	a) Aquatic acute toxicity: LC50 Fish = 41 mg/L 96
		a) Aquatic acute toxicity: EC50 Daphnia = 42 mg/L 24
		a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 22,6 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 1510 $\mu$ g/L 96h EPA

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 9 of 13

a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio = 41 mg/L 96h IUCLID

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss 0,032 mL/L 96h

EPA

a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 100 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 23,2 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Daphnia Daphnia magna = 2 mg/L 48h

UCLID

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna 11,3 mg/L 48h EPA

# 12.2. Persistence and degradability

N.A.

#### 12.3. Bioaccumulative potential

N.A.

#### 12.4. Mobility in soil

N.A.

#### 12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

# 12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7 Other adverse effects

Not available

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

#### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

# **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number or ID number

Not Applicable

# 14.2. UN proper shipping name

Not Applicable

# 14.3. Transport hazard class(es)

Not Applicable

# 14.4. Packing group

Not Applicable

# 14.5. Environmental hazards

Not Applicable

## 14.6. Special precautions for user

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 10of 13

Sea ( IMDG ):

Not Applicable

# 14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 30 g/l

Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

# Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 28, 40, 72, 75  $\,$ 

#### **SVHC Substances:**

SVHC substances not present in a concentration ≥ 0.1% (w/w)

# German Water Hazard Class (WGK)

Class 1: slightly hazardous for water.

# 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

# **SECTION 16: Other information**

Code	Description					
H301	Toxic if swallowed.					
H311	Toxic in contact with skin.					
H314	Causes severe skin burns and eye damage.					
H315	Causes skin irritation.					
H317	May cause an allergic skin reaction.					
H319	Causes serious eye irritation.					
H331	Toxic if inhaled.					
H335	May cause respiratory irritation.					
H341	Suspected of causing genetic defects.					
H350	May cause cancer.					
Drint data	05/09/2022 Production Name					

H412	Harmful to aquatic life with long lasting effects.				
Code	Hazard class and hazard category	Description			
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3			
3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3			
3.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3			
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B			
3.2/2	Skin Irrit. 2	Skin irritation, Category 2			
3.3/2	Eye Irrit. 2	Eye irritation, Category 2			
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1			
3.5/2	Muta. 2	Germ cell mutagenicity, Category 2			
3.6/1B	Carc. 1B	Carcinogenicity, Category 1B			
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3			
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category ${\bf 1}$			
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1			
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3			

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

# Classification according to Regulation (EC) Nr. 1272/2008 4.1/C3 Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

H372

H400

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

 ${\tt ADR: European \ Agreement \ concerning \ the \ International \ Carriage \ of \ Dangerous \ Goods \ by \ Road.}$ 

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 12of 13

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

\* Sheet model entirely changed in compliance to regulatory update.

Print date 05/08/2022 Production Name SILANCOLOR "T" PLUS 1.5MM Page n. 13of 13