

DECLARATION OF PERFORMANCE N. CPR-IT1/0341

- 1) Unique identification code of the product-type: **SILEXCOLOR TONACHINO**
- 2) Intended uses: **Water based, organic render/plaster, for external and internal use on walls, ceilings, columns and partitions**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 15824:2017**

Notified bodies: **the notified laboratory SWISSI Process Safety GmbH, N. 2139, carried out the assessment of the performance (for reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Water vapour permeability:	V1
Water absorption:	W2
Adhesion:	≥ 0,3 MPa
Durability:	≥ 0,3 MPa
Thermal conductivity:	1,21 W/m*K (tab value, P = 90%)
Reaction to fire:	Class A2-s1, d0
Dangerous substances:	see SDS


- 7) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 09/01/2019





DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Updated in compliance with standard revision
--------------------------	---

SILEXCOLOR TONACHINO
CE MARKING
Annex to DoP N. CPR-IT1/0341



 2139	 MAPEI Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
11 CPR-IT1/0341 EN 15824 SILEXCOLOR TONACHINO <i>Water based, organic render/plaster, for external and internal use on walls, ceilings, columns and partitions</i>	
Water vapour permeability:	V1
Water absorption:	W2
Adhesion:	≥ 0,3 MPa
Durability:	≥ 0,3 MPa
Thermal conductivity:	1,21 W/m*K (tab value, P = 90%)
Reaction to fire:	Class A2-s1, d0
Dangerous substances:	see SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.