Safety Data Sheet ULTRACARE EPOXY OFF GEL

Safety Data Sheet dated: 14/06/2022 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ULTRACARE EPOXY OFF GEL

Trade code: 9011499 UFI: 1RA1-W0YF-H009-407K

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Cleaner Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Eye Irrit. 2 Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.

Special Provisions:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration \geq 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 1 of 13

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: ULTRACARE EPOXY OFF GEL

Hazardous components within the meaning of the CLP regulation and related classification:

Concentra tion (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥20 - <25 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057- 00-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Irrit. 2, H319	01-2119492630-38-XXXX
≥2.5 - <5 %	monoethanolamine oleate	CAS:2272-11-9 EC:218-878-0	Eye Irrit. 2, H319	
≥1 - <2.5 %	1-methoxy-2-propanol	CAS:107-98-2 EC:203-539-1 Index:603-064- 00-3	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119457435-35-XXXX
≥0.49 - <1 %	2-aminoethanol; ethanolamine	CAS:141-43-5 EC:205-483-3 Index:603-030- 00-8	Skin Corr. 1B, H314 STOT SE 3, H335 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332	01-2119486455-28-XXXX
		00 0	Specific Concentration Limits: 5% ≤ C < 100%: STOT SE 3 H335	
≥0.016 - <0.025 %	1,2-benzisothiazol-3(2H)-one; 1,2 benzisothiazolin-3-one	EC:220-120-9	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411	
			Specific Concentration Limits: C ≥ 0,05%: Skin Sens. 1 H317	
<0.0015 %	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	EC:611-341-5 Index:613-167-	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic:100, M-Acute:100	
			Specific Concentration Limits: $C \ge 0.6\%$: Skin Corr. 1C H314 $0.06\% \le C < 0.6\%$: Skin Irrit. 2 H315 $C \ge 0.6\%$: Eye Dam. 1 H318 $0.06\% \le C < 0.6\%$: Eye Irrit. 2 H319 $C \ge 0.0015\%$: Skin Sens. 1A H317	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 2 of 13

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

OEL	Country	Ceiling	Long	Long	Short	Short	Behaviour	Note
Type			Term	Term	Term	Term		
			ma/m3	nnm	ma/m3	nnm		

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 3 of 13

benzyl alcohol CAS: 100-51-6	National	FINLAND		45	10			
		POLAND GERMANY	С	240		44	10	
		GERMANY	C	22	5			
	NDS	POLAND		240	J			
	National			40				
		REPUBLIC						
	National			5				
	National	CZECH REPUBLIC	С			80		
	National	BULGARIA		5,0				
	National	LITHUANIA		5				
	National	SLOVENIA		22	5	44	10	
1-methoxy-2-propanol CAS: 107-98-2	SUVA			375	100	568	150	
	National	SWEDEN		190	50	300	75	SWEDEN, Short-term value, 15 minutes average value
	National	FINLAND		370	100	560	150	FINLAND, hud
	National	NORWAY		180	50			NORWAY, H
	NDS			180				
	NDSCh			360				
	National	NORWAY		185	50	370	100	
	EU			375	100	563	150	Skin
	ACGIH				50		100	A4 - Eye and URT irr
	DFG	GERMANY	С			740	200	
	ACGIH				50		100	A4 - Not Classifiable as a Human Carcinogen; eye and upper respiratory tract irritation
	National	SWEDEN		190	50			
	National	FRANCE		188	50	375	100	
	National			375	100	568	150	
		GREECE		360	100	1080	300	
		DENMARK		185	50			
		FINLAND		370	100	560	150	
		GERMANY		370	100			
		PORTUGAL		375	100	568	150	
	National	BELGIUM		375	100	568	150	
	NDS	POLAND		180				
	NDSCh	POLAND				360		
		SWITZERLAND				720	200	
	NDS	NETHERLANDS		375		563		
	National	CZECH REPUBLIC		270				
	National	HUNGARY		375		568		
		MALAYSIA		369	100			
	a OEL					560	150	
		ESTONIA		375	100	568	150	
	National		6	375	100	568	150	
	National	REPUBLIC	С			550		
	National	SLOVAKIA	С			568		
	National	SLOVAKIA		375	100			

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 4 of 13

National	SLOVENIA		375	100	562,5	150		
National	UNITED		375	100	560	150		
	KINGDOM							
National	BULGARIA		375,0	100	568,0	150		
National	ROMANIA		375	100	568	150		
TUR	TURKEY		375	100	568	150		
National	LITHUANIA		190	50	300	75		
National	CROATIA		375	100	568	150		
EU			375	100	568	150	Indicative	Possibility of significant
								uptake through the skin
National	NORWAY		2,500	1,000				H E
			•	,				
NDS			2,5					
NDSCh			7,500					
National	SWEDEN		8,000	3,000	15,000	6,000		SWEDEN, Short-term value, 15 minutes average value
National	FINLAND		2,500	1,000	7,600	3,000		FINLAND, hud
EU			2,5	1	7,600	3,000		Skin
ACGIH			•	3,000	,	6,000		Eye and skin irr
DFG	GERMANY	С		,	0,510	0,200		,
ACGIH		_		3,000	-,	6,000		eye and skin irritation
EU			2,500	1,000	7,600	3,000	Indicative	Possibility of significant
					7,000	3,000	Trialcative	uptake through the skin
	DENMARK		2,5	1				
National	GERMANY		0,500	0,200				
National	PORTUGAL		2,5	1	7,6	3		
NDS	POLAND		2,5					
NDSCh	POLAND				7,500			
NDS	NETHERLANDS	;	2,500		7,600			
National	CZECH REPUBLIC		2,500					
National	HUNGARY		2,500		7,600			
National		С	,		7,500			
	REPUBLIC				,			
National	SLOVAKIA	С			7,600			
	ROMANIA		2,5	1	7,6	3		
	LITHUANIA		2,5	1	7,6	3		
	SWEDEN		2,5	1	, -			
	FRANCE		2,5	1	7,6	3		
National			2,5	1	7,5	3		
	GREECE		2,5	1	7,6	3		
	FINLAND		2,5	1	7,6	3		
	NORWAY		2,5	1	5	2		
	BELGIUM		2,5	1	7,6	3		
CHE	SWITZERLAND		2,3	•	10	4		
	MALAYSIA		7,5	3	10	7		
a OEL	MALATSIA		7,5	3				
National	ESTONIA		2,5	1	7,6	3		
National	LATVIA		0,5	0,2	7,6	3		
National	SLOVAKIA		2,5	1				
National	SLOVENIA		2,5	1	7,6	3		
National	UNITED KINGDOM		2,5	1	7,6	3		

2-aminoethanol; ethanolamine CAS: 141-43-5

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 5 of 13

Nationa	I BULGARIA	2,5	1	7,6	3
TUR	TURKEY	2,5	1	7,6	3
Nationa	l CROATIA	2,5	1	7,6	3

Predicted No Effect Concentration (PNEC) values

Predicted No Effect Con	centration	(PNEC) values	
	PNEC Limit	Exposure Route	Exposure Frequency Remark
benzyl alcohol CAS: 100-51-6	1 mg/l	Fresh Water	
	0,1 mg/l	Marine water	
	5,27 mg/kg	Freshwater sediments	
	0,527 mg/kg	Marine water sediments	
	39 mg/l	Microorganisms in sewage treatments	
	0,45 mg/kg	Soil	
	2,3 mg/l	Intermittent release	
1-methoxy-2-propanol CAS: 107-98-2	10 mg/l	Fresh Water	
	100 mg/l	Intermittent release	
	1 mg/l	Marine water	
	100 mg/l	Microorganisms in sewage treatments	
	52,3 mg/kg	Freshwater sediments	
	5,2 mg/kg	Marine water sediments	
	4,59 mg/kg	Soil	
2-aminoethanol; ethanolamine CAS: 141-43-5	0,085 mg/l	Fresh Water	
	0,0085 mg/l	Marine water	
	0,025 mg/l	Intermittent release	
	0,425 mg/kg	Freshwater sediments	
	0,0425 mg/kg	Marine water sediments	
	0,035 mg/kg	Soil	
	100 mg/l	Microorganisms in sewage treatments	

Derived No Effect Level. (DNEL)

	Worker Worker Industr Profess y ional		Exposure Route	Exposure Frequency Remark
benzyl alcohol CAS: 100-51-6		20 mg/kg	Human Oral	Short Term, systemic effects
		4 mg/kg	Human Oral	Long Term, systemic effects
	110 mg/m3	27 mg/m3	Human Inhalation	Short Term, systemic effects
	22 mg/m3	5,4 mg/m3	Human Inhalation	Long Term, systemic effects

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 6 of 13

	40 mg/kg		20 mg/kg	Human Dermal	Short Term, systemic effects
	8 mg/kg		4 mg/kg	Human Dermal	Long Term, systemic effects
1-methoxy-2-propanol CAS: 107-98-2		369 mg/m3		Human Inhalation	Long Term, systemic effects
		553,5 mg/m3		Human Inhalation	Short Term, systemic effects
		553,5 mg/m3		Human Inhalation	Short Term, local effects
		183 mg/kg		Human Dermal	Long Term, systemic effects
			43,9 mg/m3	Human Inhalation	Long Term, systemic effects
			78 mg/kg	Human Dermal	Long Term, systemic effects
			33 mg/m3	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid Color: opalescent Odour: Characteristic

Melting point / freezing point: Not available

Initial boiling point and boiling range: 100 °C (212 °F)

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: 100 °C (212 °F)

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: 9.00

Viscosity: Not available

Kinematic viscosity: Not available

Solubility in water: yes Solubility in oil: soluble

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 7 of 13

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: 1.10 g/cm3 Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the mixture:

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation The product is classified: Eye Irrit. 2(H319)

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

benzyl alcohol a) acute toxicity LC50 Inhalation Rat = 11, mg/l 4h

LD50 Oral Rat = 1230, mg/kg

g) reproductive toxicity NOAEL Rat = 1072, mg/m3

1-methoxy-2-propanol a) acute toxicity LD50 Oral Rat = 5300 mg/kg

LD50 Skin Rabbit = 13000 mg/kgLC50 Inhalation Rat = 28.8 mg/l 4h

LD50 Skin Rabbit = 13 g/kg

LC50 Inhalation Rat > 7559 ppm 6h

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 8 of 13

LD50 Oral Rat = 5000 mg/kg

h) STOT-single exposure NOAEL Oral Rat = 919 mg/kg

NOAEL Inhalation Rat = 3,7 mg/kg NOAEL Skin Rabbit > 1000 mg/kg

2-aminoethanol; ethanolamine

a) acute toxicity

a) acute toxicity

LD50 Oral Rat 2100 mg/kg

LD50 Skin Rabbit 1000 mg/kg

1,2-benzisothiazol-3(2H)- a) acute toxicity

one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 670, mg/kg

reaction mass of: 5-

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6] LC50 Inhalation Rat = 2,36 mg/l 4h

(3:1)

LD50 Skin Rabbit = 660, mg/kg LD50 Oral Rat = 53, mg/kg

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards

Based on available data, the classification criteria are not met

List of components with eco-toxicological properties

benzyl alcohol CAS: 100-51-6 - a) Aquatic acute toxicity: EC50 Daphnia = 230 mg/L 48

EINECS: 202-859-9 - INDEX: 603-057-00-5

a) Aquatic acute toxicity: LC50 Fish = 770 mg/L 1
 a) Aquatic acute toxicity: EC50 Algae = 770 mg/L 72

a) Aquatic acute toxicity: LC50 Fish = 460 mg/L 96

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h

EPA

1-methoxy-2-propanol CAS: 107-98-2 - a) Aquatic acute toxicity: LC50 Fish = 5000 mg/L 96

EINECS: 203-539-1 - INDEX: 603-064-00-3

a) Aquatic acute toxicity: EC50 Daphnia = 23300 mg/L 48

a) Aquatic acute toxicity: EC50 Algae > 1000 mg/L 96

a) Aquatic acute toxicity: LC50 Bacteria > 1000 mg/L 3a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 20,8 g/l 96h

IUCLID

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 23300 mg/L 48h

IUCLID

2-aminoethanol; ethanolamine CAS: 141-43-5 - a) Aquatic acute toxicity: EC50 Daphnia = 65 mg/L 48

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 9 of 13

EINECS: 205-483-3 - INDEX: 603-030-00-8

a) Aquatic acute toxicity: EC50 Algae = 22 mg/L 72

a) Aquatic acute toxicity: LC50 Fish = 349 mg/L 96

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 227 mg/L 96h

a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio = 3684 mg/L 96h

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus 300 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss 114 mg/L 96h EPA

a) Aquatic acute toxicity: EC50 Algae Desmodesmus subspicatus = 15 mg/L

72h IUCLID

1,2-benzisothiazol-3(2H)-one; 1,2- CAS: 2634-33-5 a) Aquatic acute toxicity: LC50 Fish = 2,15 mg/L

benzisothiazolin-3-one

- EINECS: 220-120-9 - INDEX:

613-088-00-6

b) Aquatic chronic toxicity: NOEC Algae = 0,0403 mg/L 72h

b) Aquatic chronic toxicity: EC50 Algae = 0,11 mg/L 72h

b) Aquatic chronic toxicity: EC10 Algae = 0,04 mg/L 72h

b) Aquatic chronic toxicity: EC50 Daphnia = 3,27 mg/L 48h

NOEC Daphnia = 1.2 mg/L 21d

reaction mass of: 5-chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - 611-341-5 isothiazol-3-one [EC no. 220-239- INDEX: 613-

9 - EINECS: 167-00-5

CAS: 55965-84- a) Aquatic acute toxicity: EC50 Daphnia = 0,12 mg/L 48

a) Aquatic acute toxicity: LC50 Fish = 0,22 mg/L 96

a) Aquatic acute toxicity: EC50 Algae = 0,048 mg/L 72

b) Aquatic chronic toxicity: NOEC Algae = 0,0012 mg/L 72

b) Aquatic chronic toxicity: NOEC Fish = 0,098 mg/L - 28 d

b) Aquatic chronic toxicity: NOEC Daphnia = 0,004 mg/L - 21 d

12.2. Persistence and degradability

N.A.

6] (3:1)

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 10of Hazardous waste: Yes
Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH)

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 11of 13

and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 30, 40, 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

German Water Hazard Class (WGK)

Class 1: slightly hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
11330	ria, cause aromonicos or aizzinessi	
Code	Hazard class and hazard category	Description
	,	Description Flammable liquid, Category 3
Code	Hazard class and hazard category	•
Code 2.6/3	Hazard class and hazard category Flam. Liq. 3	Flammable liquid, Category 3
Code 2.6/3 3.1/4/Dermal	Hazard class and hazard category Flam. Liq. 3 Acute Tox. 4	Flammable liquid, Category 3 Acute toxicity (dermal), Category 4
Code 2.6/3 3.1/4/Dermal 3.1/4/Inhal	Hazard class and hazard category Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4	Flammable liquid, Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4
Code 2.6/3 3.1/4/Dermal 3.1/4/Inhal 3.1/4/Oral	Hazard class and hazard category Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4	Flammable liquid, Category 3 Acute toxicity (dermal), Category 4 Acute toxicity (inhalation), Category 4 Acute toxicity (oral), Category 4

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation	Classification procedure
(EC) Nr. 1272/2008	
3.3/2	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center CE: European Community

CLP: Classification, Labeling, Packaging. CMR: Carcinogenic, Mutagenic and Reprotoxic

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 12of 13

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

* Sheet model entirely changed in compliance to regulatory update.

Print date 05/08/2022 Production Name ULTRACARE EPOXY OFF GEL Page n. 13of 13