Safety Data Sheet ULTRACOAT HT 2K /A

Safety Data Sheet dated: 06/02/2020 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ULTRACOAT HT 2K /A

Trade code: 9074401

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy paint

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel: +39-02-376731 Fax: +39-02-37673.214

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

0 The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: ULTRACOAT HT 2K /A

Hazardous components within the meaning of the CLP regulation and related classification:

Quantity	Name	Ident. Numb.	Classification	Registration Number
≥1 - <2.5 %	2-butoxyethanol; ethylene glycol monobutyl ether	CAS:111-76-2 EC:203-905-0	Eye Irrit. 2, H319; Skin Irrit. 2, H315; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	01-2119475108-36

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

 Date
 18/06/2020
 Production Name
 ULTRACOAT HT 2K /A
 Page n. 1 of 8

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: N.A.

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Term	Short Term mg/m3	Term	Behaviour	Note
2-butoxyethanol; ethylene glycol monobutyl ether	SUVA	NNN		49,000	10,000	98,000	20,000		

 Date
 18/06/2020
 Production Name
 ULTRACOAT HT 2K /A
 Page n. 2 of 8

NDS	NNN		98,000					
National	SWEDEN		50,000	10,000	100,000	20,000		SWEDEN, Short-term value, 15 minutes average value
National	FINLAND		98,000	20,000	250,000	50,000		FINLAND, hud
National	NORWAY		50,000	10,000				H E
NDSCh	NNN		200,000)				
EU	NNN		-		246,000	50,000		Skin
ACGIH	NNN		,	20,000	·	•		A3, BEI - Eye and URT irr
DFG	GERMANY	С		,	98,000	20,000		
ACGIH	NNN			20,000				A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans;eye and upper respiratory tract irritation
National	SWEDEN		50,000	10,000				
National	FRANCE		49,000	10,000	246,000	50,000		
National	SPAIN		98,000	20,000	245,000	50,000		
National	GREECE		120,000	25,000				
National	DENMARK		98,000	20,000				
National	FINLAND		98,000	20,000	250,000	50,000		
National	GERMANY		49,000	10,000				
National	PORTUGAL		98,000	20,000	246,000	50,000		
National	BELGIUM		98,000	20,000	246,000	50,000		
NDS	POLAND		98					
NDSCh	POLAND				200,000			
CHE	SWITZERLAND				98,000	20,000		
NDS	NETHERLANDS		100,000)	246,000			
National	CZECH REPUBLIC		100,000)				
National	HUNGARY		98,000		246,000			
Malaysia OEL	MALAYSIA		96,700	20,000				Skin notation
National	ESTONIA		98,000	20,000	246,000	50,000		
National	LATVIA		98,000	20	246,000	50,000		
National	CZECH REPUBLIC	С			200,000			
National	SLOVAKIA	С			246,000			
National	SLOVAKIA		98,000	20,000				
National	SLOVENIA		98,000	20,000	245,000	50,000		
National	UNITED KINGDOM		123,000	25,000	246,000	50,000		
National	BULGARIA		98,000	20,000	246,000	50,000		
National	ROMANIA		98,000	20,000	246,000			
TUR	TURKEY		98,000	20,000	246	50		
National	LITHUANIA		50,000	10,000	100,000	20,000		
National	CROATIA		98	20	246	50		
EU	NNN		98	20	246	50	Indicative	Possibility of significant uptake through the skin

Biological Exposure Index

CAS-No.	Component	Value	UoM	Medium	Biological Indicator	Sampling Period
111-76-2	2-butoxyethanol ethylene glycol monobutyl ether	•	MGGCREAT	Urine	Butoxyacetic acid (BAA)	End of turn

Derived No Effect Level. (DNEL)

Date 18/06/2020 Production Name ULTRACOAT HT 2K /A Page n. 3 of 8

Component	CAS-No.	Worker Worker Industr Profess y ional		Exposure Route	Exposure Frequency Remark
2-butoxyethanol; ethylene glycol monobutyl ether	111-76-2	135 ppm	426 mg/m3	Human Inhalation	Short Term, systemic effects
		89 mg/kg	44,5 mg/kg	Human Dermal	Short Term, systemic effects
			13,4 mg/kg	Human Oral	Short Term, systemic effects
		50 ppm	123 mg/m3	Human Inhalation	Short Term, local effects
		75 mg/kg	38 mg/kg	Human Dermal	Long Term, systemic effects
		20 ppm	49 mg/m3	Human Inhalation	Long Term, systemic effects
			3,2 mg/kg	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance and colour: Liquid white

Odour: Characteristic Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: N.A. Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A. Relative density: N.A.

Solubility in water: partly soluble

Partition coefficient (n-octanol/water): N.A. - This product is a mixture

Auto-ignition temperature: N.A. - No explosive or spontaneous ignition in contact with air at room temperature

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A. - No components with explosive properties

Oxidizing properties: N.A. - No component with oxidizing properties

 Date
 18/06/2020
 Production Name
 ULTRACOAT HT 2K /A
 Page n. 4 of 8

Solid/gas flammability: N.A.

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

a) acute toxicity 2-butoxyethanol; ethylene glycol monobutyl

LC50 Inhalation Rat = 2,2 mg/l 4h

ether

LD50 Oral Rat = 615 mg/kg LD50 Skin Rabbit = 405 mg/kg LD50 Skin Rabbit = 99 mg/kg LC50 Inhalation Rat = 450 ppm 4h LC50 Inhalation Rat = 486 ppm 4h LD50 Oral Rat = 470 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. **Eco-Toxicological Information:**

List of components with eco-toxicological properties

Ident. Numb. Component **Ecotox Infos**

Date 18/06/2020 **Production Name** ULTRACOAT HT 2K /A Page n. 5 of 8 monobutyl ether

a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 1490 mg/L 96h

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 2950 mg/L 96h

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna > 1000 mg/L 48h

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

NΔ

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Product:

Do not dispose of waste into sewers.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to an authorized waste disposal service.

Contaminated packaging:

Empty remaining content.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N.A.

14.2. UN proper shipping name

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

Date 18/06/2020 **Production Name** ULTRACOAT HT 2K /A Page n. 6 of 8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 90 (A+B) g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

German Water Hazard Class.

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 40

Restrictions related to the substances contained: 28

SVHC Substances:

No data available

MAL-kode: 00-1

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Code	Hazard class and hazard category	Description
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

Date 18/06/2020 Production Name ULTRACOAT HT 2K /A Page n. 7 of 8

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 5. FIRE-FIGHTING MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 13. DISPOSAL CONSIDERATIONS
- 15. REGULATORY INFORMATION

 Date
 18/06/2020
 Production Name
 ULTRACOAT HT 2K /A
 Page n. 8 of 8