

Declaration of performance: No. CPR-GB1/0027

1. Unique identification code of the product-type: **ULTRATOP INDUSTRIAL**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR: **CEMENTITIOUS SCREED MATERIAL FOR INTERNAL USE (CT-C40-F10-A9)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Cementitious screed material for internal use in floor construction**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI U.K. Ltd – Mapei House – Steel Park Road, Halesowen, West Midlands B62 8HD**
www.mapei.co.uk
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4** **System 3 for reaction to fire**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified testing laboratory MPA Dresden GmbH, N. 0767, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. 2012-B-4189/01.
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:

| Essential characteristics | Performance | Harmonised technical specification |
|---|--|------------------------------------|
| Reaction to fire: Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance: | Class A2fl-s1 CT NPD NPD C40 F10 A9 NPD NPD NPD NPD | EN 13813:2002 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**

(name and function)





Halesowen, 01/07/2013

(place and date of issue)

.....
(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|-------------------|---------------|----------------------------------|----|---------------------|-----|----------------------------|-----|-----------------------|-----|--------------------|-----|------------------|----|-------------------|-----|-------------------|-----|---------------------|-----|----------------------|-----|---------------------------------|---------|
|  0767 |  MAPEI MAPEI UK Ltd - Mapei House - Steel Park Road Halesowen – West Midlands B62 8HD www.mapei.co.uk | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>10 CPR-GB1/0027 EN 13813:2002 CT-C40-F10-A9 ULTRATOP INDUSTRIAL <i>Cementitious screed material for internal use in floor construction</i></p> <table><tr><td>Reaction to fire:</td><td>Class A2fl-s1</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C40</td></tr><tr><td>Flexural strength:</td><td>F10</td></tr><tr><td>Wear resistance:</td><td>A9</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr><tr><td>Release of dangerous substances</td><td>see SDS</td></tr></table> | | Reaction to fire: | Class A2fl-s1 | Release of corrosive substances: | CT | Water permeability: | NPD | Water vapour permeability: | NPD | Compressive strength: | C40 | Flexural strength: | F10 | Wear resistance: | A9 | Sound insulation: | NPD | Sound absorption: | NPD | Thermal resistance: | NPD | Chemical resistance: | NPD | Release of dangerous substances | see SDS |
| Reaction to fire: | Class A2fl-s1 | | | | | | | | | | | | | | | | | | | | | | | | |
| Release of corrosive substances: | CT | | | | | | | | | | | | | | | | | | | | | | | | |
| Water permeability: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Water vapour permeability: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Compressive strength: | C40 | | | | | | | | | | | | | | | | | | | | | | | | |
| Flexural strength: | F10 | | | | | | | | | | | | | | | | | | | | | | | | |
| Wear resistance: | A9 | | | | | | | | | | | | | | | | | | | | | | | | |
| Sound insulation: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Sound absorption: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Thermal resistance: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Chemical resistance: | NPD | | | | | | | | | | | | | | | | | | | | | | | | |
| Release of dangerous substances | see SDS | | | | | | | | | | | | | | | | | | | | | | | | |