



EMULSION STABILISER FIXATIVE W/B SF1

● Product Information

DESCRIPTION

An emulsion based, water dilutable scrim fixative and sealer for absorbent masonry surfaces.

USAGE/PURPOSE

Undiluted: As a fixative for Glixtone PWS9 scrim along joints in board substrates (eg: plasterboard, cement particle board etc), prior to application of high build coatings such as Glixtone RW2 and PL16.

Diluted (1 part SF1 to 3 parts water):

To seal masonry substrates prior to the application of water based finishes.

CHARACTERISTICS

Environmentally friendly, water-borne formulation
No fire or solvent vapour hazards during application or use

PERFORMANCE

Easy to use

Reliable, effective results

Fast drying

COLOUR

Clear

ENVIRONMENTAL CONSIDERATIONS

Water-borne. Contains no added lead

PACKAGING

Can size: 5 litres

● Technical Specification

COMPOSITION

Water based resin dispersion

PROPERTIES

VOC content: 0g/l

Cat. H: 50g/l (2007)/30g/l (2010)

● Surface Preparation

Ensure surfaces are clean, firm and dry.

● Application

METHOD

Apply by brush or roller.

THINNING

For fixing scrim: Do not thin.

For sealing masonry substrates:

Dilute with water, 1 part SF1 to 3 parts water.

COVERAGE

Undiluted: Will fix approx. 50 linear metres of PWS9 per litre

Diluted: 1 litre (*diluted mixture*) will cover approx. 20m²

DRYING TIME

Approx. 3 hours, depending upon atmospheric conditions.

CLEANING

Clean all brushes, rollers and associated equipment with water immediately after use.

LIMITATIONS

- DO NOT apply
- outside the temperature range 5-28°C
- when the temperature is likely to fall below 5°C within 2 hours
- if rain is likely within 4 hours

● Health & Safety Notes

Detailed information and guidance is provided in **Material Safety Data Sheet:**

SF1. The following represents important selected information only

Ensure good ventilation during application and drying

Avoid contact with eyes and skin

In case of contact with eyes:

Rinse immediately with plenty of water and seek medical advice

In case of contact with skin:

Wash immediately with plenty of soap water or a proprietary skin cleanser

Keep out of reach of children

STORAGE

Store in secure, dry conditions at temperature between 5° and 28°C. Protect from frost. Containers should be kept closed during storage. Avoid spillage and contamination. Do not empty into drains and water courses.

SHELF LIFE

1 year in original, unopened container, if stored in accordance with recommendations above.

● Specification

Fully written model propriety specifications for Glixtone products are available from the Glixtone Technical Services Department.

● Additional Information

TECHNICAL ASSISTANCE

For further information, advice or guidance regarding any aspect of Glixtone products, please contact the Technical Services Department at the address below.

WARRANTY

As Glixtone has no direct control over the methods employed by the user in applying its products, any warranty either written or implied, is given in good faith and can only cover the material itself.

Glixtone Limited 2E Eagle Road North Moons Moat Redditch B98 9HF

Tel: +44 (0)1527 599 470 Fax: +44 (0)1527 599 471 Email: sales@glixtone.com Web: www.glixtone.com

Co Reg No: 07464794 | Registered in England & Wales