

PRODUCT DATA SHEET

Sika® BentoShield® Termination Strip

GALVANISED STEEL FIXING STRIP OF MEMBRANE TERMINATION

PRODUCT DESCRIPTION

Sika® BentoShield® Termination Strip is a galvanised steel bonding strip with 5mm holes at 15mm centres in a solid plastic holder.

USES

Sika® BentoShield® Termination Strip is used for fixing and sealing the top edge of Sika BentoShield® MAX LM on vertical sections.

CHARACTERISTICS / ADVANTAGES

- Corrosion resistant
- Secure fixing
- Easy and fast to install

PRODUCT INFORMATION

Chemical Base	Hot dipped, galvanised steel
Packaging	10 rolls, packed in one cardboard box
Appearance / Colour	Galvanised steel roll in a red plastic holder
Shelf Life	Store in a dry place, safe from weathering and mechanical damage.
Storage Conditions	Store at temperatures between +5°C and +35°C.
Dimensions	Width: 12 mm Length: 10 m Thickness: 1.0 mm

SYSTEM INFORMATION

System Structure	Sika® BentoShield® Termination Strip is an ancillary product for the Sika BentoShield® MAX LM membrane waterproofing system.
------------------	--

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Sika® BentoShield® Termination Strip is used to seal the top edge of Sika BentoShield® MAX LM against ingress of water. It is fixed in place with the Sika BentoShield® Fixing System.

For further more detailed information about the installation method, please refer to the Sika BentoShield® MAX LM membrane Product Data Sheet and the Method Statement.

NOTES ON APPLICATION / LIMITATIONS

The Sika BentoShield® MAX LM system must only be installed by trained contractors.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet
Sika® BentoShield® Termination Strip
April 2019, Version 01.01
020704310020000011

SikaBentoShieldTerminationStrip-en-GB-(04-2019)-1-1.pdf