

PRODUCT DATA SHEET

SikaRoof® Primer-600 UK

Primer for Sarnavap®-5000 E SA / Sikaplan® RV-s / Sarnafil® TG 76 FSA / Sarnafil® G 410 FSA roof membranes

PRODUCT DESCRIPTION

SikaRoof® Primer-600 UK is a synthetic rubber and resin based 1-part ready to use primer for improving the adhesion properties of specific Sika® roof membranes.

USES

SikaRoof® Primer-600 UK may only be used by experienced professionals.

A substrate primer for applying self-adhesive roof membranes including:

- S-Vap®-5000 E SA
- SikaBit VB SA 724
- Sarnafil® TG 76 FSA
- Sarnafil® G 410 FSA

A primer for SikaRoof® 250 adhesive to critical substrates.

CHARACTERISTICS / ADVANTAGES

- Proven performance over decades
- Easily applied
- Flame free application
- High adhesion to different structural deck types and substrates
- 1-part ready to use
- Increased adhesion for the specific membrane types
- Applied by brush or roller

PRODUCT INFORMATION

Chemical Base	Synthetic rubber and resins. Contains solvents.
Packaging	12,5 kg Containers Packing unit: Euro pallet or single container. Refer to current price list for packaging variations.
Appearance / Colour	black
Shelf Life	12 months from date of production.
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.
Density	~0,84 kg/l (+20 °C)
Consistency	liquid

APPLICATION INFORMATION

Consumption	~150–500 g/m ² Consumption depends on the roughness and absorbency of the substrate. These figures are theoretical and do not allow for any additional material due to surface porosity, surface profile, variations in level or wastage etc.
Ambient Air Temperature	+5 °C min
Substrate Temperature	+5 °C min
Setting time	Final properties are achieved after ~1 week, depending on temperature and humidity.
Tack Free Time	~30 minutes Depending on environmental conditions, characteristics of the substrate and amount of primer applied.
Waiting Time / Overcoating	~30 minutes Depending on environmental conditions, characteristics of the substrate and amount of primer applied.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LIMITATIONS

- Do not apply to wet, damp or unclean surfaces.
- Do not use on the following substrates: Synthetic membranes e.g. PVC, FPO.
- Do not use on EPS/XPS thermal insulation boards.
- Do not use on existing coated surfaces.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

- The substrate surface/supporting layer must be of sufficient structural adequacy to apply the new roof membrane and all layers of the roof build-up including wind uplift.
- The substrate can be one of the following materials: Concrete, lightweight concrete, screed, brick, plaster, Oriented Strand Boards (OSB), plywood panels, timber boards, metal decking.

SUBSTRATE PREPARATION

The substrate must be uniform, firm, solvent resistant, smooth and free of any sharp protrusion or burrs, clean, dry, free of grease, bitumen, oil, paint coatings and dust. If heavily contaminated or oiled, sheet metal decking must be cleaned with Sarna Cleaner before applying the primer.

MIXING

Important: Do not thin product or mix with other products.

- 1-part ready to use
- Before use, stir product thoroughly.

APPLICATION

Important: Application must be during dry weather at temperatures above +5 °C.

Important: Apply roofing membrane on the same day. Note: Absorbent substrates may require 2 coats.

1. Apply a uniform, thin coat to the substrate by brush or roller.
2. Allow primer to dry tack free.
3. If required, apply a 2nd coat

CLEANING OF TOOLS

Clean all tools and application equipment with Sarna Cleaner immediately after use. Hardened material can only be mechanically removed.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaRoof® Primer-600 UK
November 2020, Version 01.02
020945072100000019

SikaRoofPrimer-600UK-en-GB-(11-2020)-1-2.pdf