Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikafloor-91, Part A

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444 : 01707 329129 Fax no. e-mail address of person

responsible for this SDS

: EHS@uk.sika.com

Emergency telephone number : +44 (0)1707 363899 (available during office hours).

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38

R43 N; R51/53

Human health hazards : Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Modified epoxy resin

Characteristics

Ingredient name	CAS number	%	EC number	Classification	
reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	50-75	500-033-5	Xi; R36/38 [R43 N; R51/53	1]
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	5-10	500-006-8	Xi; R36/38 [R43 N; R51/53	1]
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	5-10	271-846-8	Xi; R36/38 [* R43 N; R51/53	1]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

Date of issue : 08.04.2010. **MSDS no.** : 23917 1/6 Sikafloor-91, Part A 08.04.2010 2/6

3. COMPOSITION/INFORMATION ON INGREDIENTS

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

Inhalation

: Get medical attention if adverse health effects persist or are severe.

Ingestion

: Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

Hazardous combustion

products

In a fire or if heated, a pressure increase will occur and the container may burst.Decomposition products may include the following materials:

carbon dioxide

carbon monoxide halogenated compounds

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

Date of issue : 08.04.2010. MSDS no. : 23917 2/6

Sikafloor-91. Part A 08.04.2010 3/6

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection Hand protection : No special measures required.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue : 08.04.2010. MSDS no. : 23917 3/6

Sikafloor-91. Part A 08.04.2010 4/6

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.

Colour : Yellowish.

Odour : Faint odour.

Important health, safety and environmental information

Flash point : Closed cup: >101°C (>213.8°F)

Density : ~1.1 g/cm³ [20°C (68°F)]

Solubility: Insoluble in the following materials: water

Viscosity : Dynamic: 1600 mPa·s (1600 cP)

10. STABILITY AND REACTIVITY

Stability: The product is stable.

Conditions to avoid : Avoid release to the environment. Refer to special instructions/safety data sheet.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : May cause irritation.

Ingestion: Irritating to mouth, throat and stomach.

Skin contact: Irritating to skin. May cause sensitisation by skin contact.

Eye contact: Irritating to eyes.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

12. ECOLOGICAL INFORMATION

Environmental effects: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Empty

containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

European waste catalogue

(EWC)

: 08 01 11* waste paint and varnish containing organic solvents or other dangerous

substances

Packaging :

Date of issue : 08.04.2010. MSDS no. : 23917 4/6

Sikafloor-91, Part A 08.04.2010 5/6

13. DISPOSAL CONSIDERATIONS

Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

<u>ADR</u>

UN number : UN3082

ADR Class : 9
Classification code : M6
Packing group : III

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

Contains : Epoxide resin

Label No. : 9

IMDG

UN number : UN3082

IMDG Class : 9
Packing group : III

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Contains : Epoxide resin

Emergency schedules

(EmS)

: F-A, S-F

Marine pollutant : P Label no. : 9

IATA

UN number : UN3082

IATA Class : 9
Packing group : III

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

Contains : Epoxide resin

Label no. : 9

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi, N

Irritant, Dangerous for the environment

Contains : reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average

molecular weight <= 700)

reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average

molecular weight <= 700)

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Date of issue : 08.04.2010. MSDS no. : 23917 5/6

Sikafloor-91, Part A 08.04.2010 6/6

REGULATORY INFORMATION 15.

Risk phrases : R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S37- Wear suitable gloves.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.

VOC content (EU) : VOC (w/w): 0.01%

National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

OTHER INFORMATION 16.

Full text of classifications referred to in sections 2 and : R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: Xi - Irritant

N - Dangerous for the environment

3

History

Date of printing : 08.04.2010. : 08.04.2010. Date of issue

Date of previous issue : No previous validation.

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

: 08.04.2010. Date of issue **MSDS no.** : 23917 6/6

Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikafloor-91, Part B

Use of the substance/preparation: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444

Fax no. : 01707 329129

e-mail address of person : EHS@uk.sika.com

responsible for this SDS

Emergency telephone number

: +44 (0)1707 363899 (available during office hours).

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xn; R20/21/22

C; R35 R43 R52/53

Human health hazards: Harmful by inhalation, in contact with skin and if swallowed. Causes severe burns.

May cause sensitisation by skin contact.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Modified polyamine

Characteristics

Ingredient name	CAS number	%	EC number	Classification	
benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine	100-51-6 2855-13-2	35-50 10-25	202-859-9 220-666-8	Xn; R20/22 Xn; R21/22 C; R34 R43 R52/53	[1] [1]
m-phenylenebis(methylamine)	1477-55-0	10-20	216-032-5	Xn; R20/22 C; R35 R43 R52/53	[1] [2]
3,6,9-triazaundecamethylenediamine	112-57-2	5-10	203-986-2	Xn; R21/22 C; R34 R43 N; R51/53	[1]
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	5-7	202-013-9	Xn; R22 Xi; R36/38	[1]
2-Propenenitrile, reaction products with 2,2,4(or	90530-20-4	3-5	292-059-6	Xn; R22	[1]

Date of issue : 08.04.2010. MSDS no. : 23916 1/7

Sikafloor-91. Part B 08.04.2010 2/7

3. COMPOSITION/INFORMATION ON INGREDIENTS 2,4,4)-trimethyl-1,6-hexanediamine C: R34 R43 N: R51/53 1-2.5 Xn; R22 Trimethylhexane-1,6-diamine 25620-58-0 247-134-8 [1] C; R34 R43 R52/53 See section 16 for the full text of the R-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

phrases declared above

- [3] PBT-substance
- [4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention immediately. If it is suspected that fumes are still present, the

rescuer should wear an appropriate mask or self-contained breathing apparatus.

Ingestion : Get medical attention immediately. Do not induce vomiting unless directed to do so

by medical personnel. Chemical burns must be treated promptly by a physician.

Maintain an open airway.

Skin contact: Get medical attention immediately. Flush contaminated skin with plenty of water.

Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10

minutes. Chemical burns must be treated promptly by a physician.

Eye contact: Get medical attention immediately. Immediately flush eyes with plenty of water.

occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated

promptly by a physician.

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

Hazardous combustion

products

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Date of issue : 08.04.2010. MSDS no. : 23916 2/7

Sikafloor-91. Part B 08.04.2010 3/7

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

: No special measures required.

Date of issue : 08.04.2010. MSDS no. : 23916 3/7

Sikafloor-91. Part B 08.04.2010 4/7

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a risk assessment indicates

this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists,

gases or dusts.

Skin protection: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before

handling this product. Recommended: Use barrier skin cream.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.
Colour : Yellowish.
Odour : Amine-like.

Important health, safety and environmental information

pH : 12

Flash point : Closed cup: >101°C (>213.8°F) Density : ~1.018 g/cm³ [23°C (73.4°F)]

Solubility: Insoluble in the following materials: water

Viscosity : Dynamic: 12 mPa·s (12 cP)

10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : Reactive or incompatible with the following materials:

acids

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : Harmful by inhalation. May give off gas, vapor or dust that is very irritating or corrosive

to the respiratory system. May cause irritation.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Skin contact: Severely corrosive to the skin. Causes severe burns. Harmful in contact with skin.

May cause sensitisation by skin contact.

Eye contact: Severely corrosive to the eyes. Causes severe burns.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Date of issue : 08.04.2010. MSDS no. : 23916 4/7

Sikafloor-91. Part B 08.04.2010 5/7

12. ECOLOGICAL INFORMATION

Environmental effects

: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC)

: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Packaging

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

<u>ADR</u>

UN number : UN1760

ADR Class : 8
Classification code : C9
Packing group : II

Proper shipping name : Corrosive liquid, n.o.s.

Contains: Isophoronediamine, Xylylenediamine

Label No. : 8

IMDG

UN number : UN1760

IMDG Class : 8
Packing group : ||

Proper shipping name : Corrosive liquid, n.o.s.

Contains: Isophoronediamine, Xylylenediamine

Emergency schedules

(EmS)

: F-A, S-B

Marine pollutant : No Label no. : 8

<u>IATA</u>

UN number : UN1760

IATA Class : 8
Packing group : II

Proper shipping name : Corrosive liquid, n.o.s.

Date of issue : 08.04.2010. MSDS no. : 23916 5/7

Sikafloor-91, Part B 08.04.2010 6/7

14. TRANSPORT INFORMATION

Contains : Isophoronediamine, Xylylenediamine

Label no. : 8

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : C

Corrosive

Contains : benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine) 3,6,9-triazaundecamethylenediamine

2-Propenenitrile, reaction products with 2,2,4(or 2,4,4)-trimethyl-1,6-

hexanediamine

Trimethylhexane-1,6-diamine

Risk phrases : R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.

R35- Causes severe burns.

R43- May cause sensitisation by skin contact.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S26- In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.

S45- In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

VOC content (EU) : VOC (w/w): 48%

National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

3)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R22- Harmful if swallowed.

R20/22- Harmful by inhalation and if swallowed.

R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.

R21/22- Harmful in contact with skin and if swallowed.

R34- Causes burns.

R35- Causes severe burns. R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

Date of issue : 08.04.2010. MSDS no. : 23916 6/7

Sikafloor-91, Part B 08.04.2010 7/7

16. OTHER INFORMATION

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: C - Corrosive Xn - Harmful Xi - Irritant

N - Dangerous for the environment

History

Date of printing : 08.04.2010.

Date of issue : 08.04.2010.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 08.04.2010. MSDS no. : 23916 7/7

Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

Sikafloor-91, Part C

Use of the substance/preparation: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444 Fax no. : 01707 329129 e-mail address of person

responsible for this SDS

: EHS@uk.sika.com

: +44 (0)1707 363899 (available during office hours). **Emergency telephone number**

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

: Handling and/or processing of this material may generate a dust which can cause Additional hazards

mechanical irritation of the eyes, skin, nose and throat.

Additional warning phrases : Safety data sheet available for professional user on request.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Composition of fillers

Characteristics

Ingredient name	CAS number	%	EC number	Classification
Quartz (SiO2)	14808-60-7	>=90	238-878-4	Not classified. [2]
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

: 08.04.2010. Date of issue **MSDS no.** : 38030 1/5 Sikafloor-91. Part C 08.04.2010 2/5

FIRST AID MEASURES 4.

First-aid measures

Inhalation : Get medical attention if symptoms occur.

Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

: Flush contaminated skin with plenty of water. Remove contaminated clothing and Skin contact

shoes. Get medical attention if symptoms occur.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

: No specific treatment. Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : No specific fire or explosion hazard.

Hazardous combustion

products

: Decomposition products may include the following materials:

metal oxide/oxides

Special protective

equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

ACCIDENTAL RELEASE MEASURES 6.

: Keep unnecessary and unprotected personnel from entering. Do not touch or walk Personal precautions

> through spilt material. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment (see section 8).

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains **Environmental precautions**

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Large spill Move containers from spill area. Prevent entry into sewers, water courses.

> basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent

wind dispersal.

Move containers from spill area. Vacuum or sweep up material and place in a Small spill

designated, labelled waste container.

HANDLING AND STORAGE 7.

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended : Use original container.

: 08.04.2010. Date of issue **MSDS no.** : 38030 2/5 Sikafloor-91, Part C 08.04.2010 3/5

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name Occupational exposure limits

EH40/2005 WELs (United Kingdom (UK), 8/2007). Quartz (SiO2)

TWA: 0.1 mg/m3 8 hour(s). Form: respirable dust

Recommended monitoring

procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure

controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

particulate filter P

P1: Inert material: P2: Xn: P3: T. T+ No special measures required.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PHYSICAL AND CHEMICAL PROPERTIES 9.

General information

Appearance

Form : Powder. Colour : Tan. : Odourless. Odour

Important health, safety and environmental information

Flash point : Closed cup: Not applicable.

Loose bulk density : ~1600 kg/m³

Solubility : Insoluble in the following materials: water

: 08.04.2010. Date of issue **MSDS no.** : 38030 3/5 Sikafloor-91. Part C 08.04.2010 4/5

10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Ingestion: Can cause gastrointestinal disturbances.

Skin contact: May cause skin irritation.

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Chronic effects: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

12. ECOLOGICAL INFORMATION

Environmental effects

: Avoid contact of spilt material and runoff with soil and surface waterways. Do not empty into drains; dispose of this material and its container in a safe way.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC)

: 16 03 03* inorganic wastes containing dangerous substances

Packaging

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

ADR

Not regulated.

<u>IMDG</u>

Not regulated.

Marine pollutant : No

Date of issue : 08.04.2010. MSDS no. : 38030 4/5

Sikafloor-91, Part C 08.04.2010 5/5

14. TRANSPORT INFORMATION

IATA

Not regulated.

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Classification : This product is not classified according to EU legislation.Additional warning phrases : Safety data sheet available for professional user on request.

VOC content (EU) : VOC (w/w): 0%

National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP

3)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Workplace Exposure Limits, HSE (as updated).

HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

16. OTHER INFORMATION

History

Date of printing : 08.04.2010.

Date of issue : 08.04.2010.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 08.04.2010. MSDS no. : 38030 5/5