



Technical Data Sheet

Blackfriar Anti-Slip Deck Coating

Blackfriar Anti-Slip Deck Coating provides all types of exterior timber decking and walkways with a protective, slip-resistant surface. Containing micro-aggregates, this coating gives increased grip in wet conditions while allowing the beauty of wood to show through.

Performance characteristics –

- Clear, protective, anti-slip surface.
- Contains micro-aggregates for slip resistance.
- For all wood decking and walkways.
- Exterior use.

Preparation - Ensure surface to be treated is clean, thoroughly dry, sound and free from wax, oil or any other contamination. It is important that the substrate is thoroughly dry before application and during the drying period otherwise blanching (whitening) may occur. Existing coatings should be lightly sanded to aid adhesion. Weathered timber should be made good. On bare wood the use of a decking stain is recommended prior to application of this product as this will give the wood better UV resistance and prolong the lifetime of the coating. Ensure new or bare timber is adequately preserved prior to applying wood finishes, apply Blackfriar Goldstar Clear Wood Preservative to untreated timbers where required.

Application - Stir thoroughly prior to use. For best results apply two coats by short pile roller. Allow the first coat to fully dry before applying a second coat. A brush may be used for small or awkward areas.

Thinning - Not recommended.

Limitations - Do not apply in wet or frosty conditions. The anti-slip properties make this product difficult to clean. This product is not suitable for heavy duty use or steel wheeled vehicles. Do not allow the build up of moss / mould growth or wet leaves etc. as this will impair or even cancel the anti-slip properties.

Coverage - Up to 9m² per litre per coat.

Drying Time - Touch dry in 4 - 6 hours. Recoat after 12 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Warning

Contains: Naphtha (petroleum), hydrotreated heavy.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour. Avoid release to the environment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, neodecanoic acid, cobalt salt and 2-butanone oxime. May

produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 600g/l (2007) 500g/l (2010.) This product contains a maximum of 500g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.