



Technical Data Sheet

Blackfriar Professional Acrylic Floor Paint

Protects and transforms floors inside and out, with an attractive, tough, durable, easy-to-clean thermoplastic coating which prevents the dusting of concrete surfaces. Suitable for asphalt and Tarmac®.

Performance characteristics –

- Indoor and outdoor use.
- Water Based - low odour.
- Suitable for asphalt, Tarmac®, brickwork, concrete, cement, wood, metal and stone.
- Resistant to grease, oil and weak solutions of acid and alkali.
- Can be applied to previously painted surfaces.
- Brush or roller application.
- Ideal for domestic, commercial and light industrial use.

Preparation

Ensure the surface to be painted is sound, clean, dry and free from grease or any substance liable to give adhesion problems. Scrape off any old or flaking paint until you have a firm surface. Special attention should be given to areas under cars to ensure all oil, grease, dirt and road salt is removed. New concrete must be left for at least 6 months before applying Blackfriar Professional Acrylic Floor Paint.

Application

Stir thoroughly before use. Apply with a brush or roller working the paint in any surface imperfections. On bare or new surfaces first apply Blackfriar Professional Water Based Floor Sealer followed by 1-2 coats of Blackfriar Professional Acrylic Floor Paint. On previously painted surfaces apply 1-2 coats as required. Blackfriar Professional Acrylic Floor Paint is not suitable for use over PVC, thermoplastic tiles, quarry tiles or granolithic concrete. Do not apply it on concrete surfaces treated with alkali containing liquids, areas subjected to rising damp or areas treated with PVA bonding solutions. Do not apply in cold (below 10°C), damp or humid conditions. If concrete floors have no profile then pre-treat with Blackfriar

Professional Acid etch to provide a mechanical key, followed after thorough rinsing by Blackfriar Professional Water Based Floor Sealer prior to applying 1-2 coats of Blackfriar Professional Acrylic Floor Paint.

Coverage Rate

10-12m²/litre per coat. Two coats recommended.

Drying Time

4-6hrs @20°C. Allow to dry for a minimum of 6hrs @20°C between coats. Full cure is achieved in 3-5 days @20°C.

Clean Up

Remove as much product from application equipment as possible before washing with water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol and formaldehyde.

May produce an allergic reaction.

Safety data sheet available on request.

EU limit value for this product (cat IIA/i): 140g/l (2007) 140g/l (2010) This product contains max 140g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.