according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-327 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

: +44 (0)1707 394444 Telephone

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled. Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eve irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer. Specific target organ toxicity - single ex-H335: May cause respiratory irritation.

posure, Category 3, Respiratory system Specific target organ toxicity - repeated

exposure, Category 2 longed or repeated exposure.

Classification (67/548/EEC, 1999/45/EC)


Harmful R20: Harmful by inhalation.

R48/20: Harmful: danger of serious damage to

H373: May cause damage to organs through pro-

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B



health by prolonged exposure through inhalation.

Carcinogenic Category 3 R40: Limited evidence of a carcinogenic effect.

Sensitising R42/43: May cause sensitisation by inhalation and

skin contact.

Irritant R36/37/38: Irritating to eyes, respiratory system

and skin.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

May cause respiratory irritation.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through pro-

longed or repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P260 Do not breathe dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Hazardous components which must be listed on the label:

• 618-498-9 Diphenylmethanediisocyanate, isomeres and homologues

202-966-0
4,4'-methylenediphenyl diisocyanate
227-534-9
219-799-4
2,2'-methylenediphenyl diisocyanate

Additional Labelling:

Contains isocyanates. May produce an allergic reaction.

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1



2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Diphenylmethanediisocyanate, isomeres and homologues 9016-87-9 618-498-9	Carc.Cat.3; R40 Xn; R20-R48/20 Xi; R36/37/38 R42/43	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	>= 50 - <= 100
4,4'-methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47-XXXX	Carc.Cat.3; R40 Xn; R20-R48/20 Xi; R36/37/38 R42/43	Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT RE2; H373	>= 10 - < 20
diphenylmethane-2,4'-diisocyanate 5873-54-1 227-534-9 01-2119480143-45-XXXX	Carc.Cat.3; R40 Xn; R20-R48/20 Xi; R36/37/38 R42/43	Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT RE2; H373	>= 5 - < 10
2,2'-methylenediphenyl diisocyanate 2536-05-2 219-799-4 01-2119927323-43-XXXX	Carc.Cat.3; R40 Xn; R20-R48/20 Xi; R36/37/38 R42/43	Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Resp. Sens.1; H334	>= 3 - < 5

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B



Revision Date 22.01.2015 Version 1.1 Print Date 22.01.2015

Skin Sens.1; H317 Carc.2; H351 STOT RE2; H373

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B





SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod: : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Avoid exceeding of the given oc-

> cupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Country GB 000000214438

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B





Revision Date 22.01.2015

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures

when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40
diphenylmethane-2,4'-diisocyanate	5873-54-1	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40
2,2'-methylenediphenyl diisocyanate	2536-05-2	TMW	0,005 ppm 0,05 mg/m3	AT OEL
		KZW	0,01 ppm 0,1 mg/m3	AT OEL
		TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1



8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015

Version 1.1



respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : brown

Odour : characteristic

Odour Threshold : No data available

Flash point : ca. 220 °C

Ignition temperature : not applicable

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : No data available

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,24 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1 Pr



9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral rat: > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal rabbit: > 9.400 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate : 1,5 mg/l

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Product

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1



Causes skin irritation.

Serious eye damage/eye irritation

Product

Causes serious eye irritation.

Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : Suspected of causing cancer.

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1 Print



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

wav.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 05 01* waste isocyanates

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

Not dangerous goods

IATA

Not dangerous goods

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1 Print I



IMDG

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

Hazard pictograms



Harmful

R-phrase(s) : R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and

skin.

R40 Limited evidence of a carcinogenic effect. R42/43 May cause sensitisation by inhalation and

skin contact.

R48/20 Harmful: danger of serious damage to

health by prolonged exposure through in-

halation.

S-phrase(s) : S23 Do not breathe vapour.

S36/37 Wear suitable protective clothing and

gloves.

S45 In case of accident or if you feel unwell,

seek medical advice immediately (show

the label where possible).

Hazardous components which must be listed on the label:

618-498-9 Diphenylmethanediisocyanate, isomeres and homologues

202-966-0
4,4'-methylenediphenyl diisocyanate
227-534-9
219-799-4
2,2'-methylenediphenyl diisocyanate

Special labelling of certain

: Contains isocyanates. See information supplied by the manu-

mixtures facturer.

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on : Banned and/or restricted

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015 Version 1.1 Pr

Print Date 22.01.2015

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

(Diphenylmethanediisocyanate) (4,4'-methylenediphenyl diisocya-

nate)

(o-(p-isocyanatobenzyl)phenyl isocyanate (Vapour and aerosols)) (2,2'-methylenediphenyl diisocya-

nate)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: not applicable

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin. R40 Limited evidence of a carcinogenic effect.

R42/43 May cause sensitisation by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure

through inhalation.

Full text of H-Statements

according to Regulation (EC) No. 1907/2006

Sikafloor®-327 Part B

Revision Date 22.01.2015



H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Version 1.1

Full text of other abbreviations

Acute Tox. Acute toxicity
Carc. Carcinogenicity
Eye Irrit. Eye irritation

Resp. Sens. Respiratory sensitisation

Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!