according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard®-Wallcoat N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Epoxy coating.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Classification (67/548/EEC, 1999/45/EC)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Country GB 000000118661

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0



Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P272 Contaminated work clothing should not be

allowed out of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

Hazardous components which must be listed on the label:

• 203-986-2 3,6,9-triazaundecamethylenediamine

• 220-666-8 3-aminomethyl-3,5,5-trimethylcyclohexylamine

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
2-(2-butoxyethoxy)ethanol 112-34-5 203-961-6 01-2119475104-44-XXXX	Xi; R36	Eye Irrit.2; H319	>= 1 - < 2,5
3,6,9-triazaundecamethylenediamine 112-57-2 203-986-2 / 01-2119487290-37-0002	C; R34 Xn; R21/22 R43 N; R51/53	Acute Tox.4; H311 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 0,25 - < 1
3-aminomethyl-3,5,5- trimethylcyclohexylamine 2855-13-2 220-666-8 01-2119514687-32-XXXX	C; R34 Xn; R21/22 R43 R52-R53	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1C; H314 Skin Sens.1A; H317 Aquatic Chronic3; H412	>= 0,25 - < 1

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A



Remarks : WEL substance

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

: No hazardous combustion products are known

ucts

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29



5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

: Do not breathe vapours or spray mist. Avoid exceeding of the Advice on safe handling

> given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against fire and explosion

: Normal measures for preventive fire protection.

: Handle in accordance with good industrial hygiene and safety Hygiene measures

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.2014

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm	2006/15/EC
			67,5 mg/m3	
		STEL	15 ppm	2006/15/EC
			101,2 mg/m3	
		TWA	10 ppm	GB EH40
			67,5 mg/m3	
		STEL	15 ppm	GB EH40
			101,2 mg/m3	

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.


Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A



long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

Flash point : Note: not applicable

Ignition temperature : not applicable

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : Note: not applicable

Melting point/range / Freez-

ing point

: No data available

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.2014

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,55 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.20

2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: ca. 2.700 mg/kg

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral rat: 1.716,2 mg/kg

Acute dermal toxicity : LD50 Dermal rat: 1.260 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral rat: 1.030 mg/kg

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg

Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Product

No data available

Serious eye damage/eye irritation

Product

No data available

Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.2014

Paris Day 20 20 20 44

Teratogenicity

: No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.2014

European Waste Catalogue : 08 01 12 waste paint and varnish other than those mentioned

in 08 01 11

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Special labelling of certain

mixtures

: Safety data sheet available for professional user on request.

Sensitising components : 3,6,9-triazaundecamethylenediamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

May produce an allergic reaction.

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

properties and articles (Appen VVIII)

preparations and articles (Annex XVII)

: not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: not applicable

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or

- excluded from the regulation, and/or

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A

Revision Date 29.09.2014 Version 1.0 Print Date 29.09.207

- exempted from the registration.

VOC-CH (VOCV) : 2,05 %

no VOC duties

VOC-EU (solvent) : 2,06 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Sup-

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R21/22 Harmful in contact with skin and if swallowed.

R34 Causes burns.
R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52 Harmful to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Chronic aquatic toxicity

Eye Irrit. Eye irritation
Skin Corr. Skin corrosion
Skin Sens. Skin sensitisation

Revision Date 29.09.2014

according to Regulation (EC) No. 1907/2006

Sikagard®-Wallcoat N Part A





The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall

apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!