

# SAFETY DATA SHEET Flameguard Ultra Vinyl Matt WHITE

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Flameguard Ultra Vinyl Matt WHITE

PRODUCT NO. BM0630002

SUPPLIER Bollom Fire Protection

Portobello Industrial Estate

Birtley

County Durham DH3 2RE +44 191 4106611 +44 191 4920125

enquiries@tor-coatings.com

CONTACT PERSON ian.mccormack@tor-coatings.com

EMERGENCY TELEPHONE +44(0)1865 407333 (NCEC)

# 2 HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45) Not classified.

CLASSIFICATION (EC 1272/2008)

Physical and Chemical Hazards Not classified.

Human health Not classified.

Environment Not classified.

LABEL IN ACCORDANCE WITH (EC) NO. 1272/2008

Not classified.

## **ENVIRONMENT**

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

# 3 COMPOSITION/INFORMATION ON INGREDIENTS

MonoPropylene Glycol 1.0-2.5%

CAS-No.: 57-55-6 EC No.: 200-338-0 Registration Number: 01-2119456809-23-xxxx

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. Not classified

Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic

CAS-No.: 64742-65-0 EC No.: 265-169-7

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. Not classified

AMMONIA ...% < 1%

CAS-No.: 1336-21-6 EC No.: 215-647-6

Classification (EC 1272/2008) Classification (67/548/EEC)

 Skin Corr. 1B - H314
 C;R34

 STOT Single 3 - H335
 N;R50

 Aquatic Acute 1 - H400
 N;R50

# Flameguard Ultra Vinyl Matt WHITE

PROPAN-2-OL			< 1%
CAS-No.: 67-63-0	EC No.: 200-661-7		
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT Single 3 - H336		Classification (67/548/EEC) F;R11 Xi;R36 R67	
ETHANEDIOL			< 1%
CAS-No.: 107-21-1	EC No.: 203-473-3		
Classification (EC 1272/2008) Acute Tox. 4 - H302		Classification (67/548/EEC) Xn;R22	
2-AMINOETHANOL			< 1%
CAS-No.: 141-43-5	EC No.: 205-483-3		
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332		Classification (67/548/EEC) C;R34 Xn;R20/21/22	

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

## **4 FIRST-AID MEASURES**

#### **GENERAL INFORMATION**

Skin Corr. 1B - H314 STOT Single 3 - H335

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

## INHALATION

Place unconscious person on the side in the recovery position and ensure breathing can take place. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

## INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

# SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

## EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

# **5 FIRE-FIGHTING MEASURES**

# EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

# SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

# UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

# PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

# **6 ACCIDENTAL RELEASE MEASURES**

# PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

# **ENVIRONMENTAL PRECAUTIONS**

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

# SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

Report Date : 29/05/2012 REVISION DATE 02/12/2004

# Flameguard Ultra Vinyl Matt WHITE

## 7 HANDLING AND STORAGE

**USAGE PRECAUTIONS** 

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
2-AMINOETHANOL		1 ppm(Sk)	2.5 mg/m3(Sk)	3 ppm(Sk)	7.6 mg/m3(Sk)	
AMMONIA%	WEL	25 ppm	18 mg/m3	35 ppm	25 mg/m3	
Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic	OEL		5 mg/m3			
ETHANEDIOL	WEL		52 mg/m3(Sk)		104 mg/m3(Sk)	
MonoPropylene Glycol	WEL	150 ppm	474 mg/m3			
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

mg/m3(Sk)

OEL = Occupational Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





# PROCESS CONDITIONS

Provide eyewash station.

**ENGINEERING MEASURES** 

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

**EYE PROTECTION** 

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid
COLOUR White.
ODOUR Mild.

SOLUBILITY Miscible with water

RELATIVE DENSITY 1.46 Approx. @20°C.

VAPOUR DENSITY (air=1) Heavier than air

VOLATILE ORGANIC COMPOUND (VOC) Cat A/i : < 140 g/l (EU Limit 140

g/l)

## 10 STABILITY AND REACTIVITY

Report Date : 29/05/2012 REVISION DATE 02/12/2004

# Flameguard Ultra Vinyl Matt WHITE

## STABILITY

No particular stability concerns.

# HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

# 11 TOXICOLOGICAL INFORMATION

## **GENERAL INFORMATION**

Not regarded as a health hazard under current legislation.

 Name
 AMMONIA ...%

 Toxic Dose 1 - LD 50
 350 mg/kg (oral rat)

 Toxic Conc. - LC 50
 2 mg/l/4h (inh-rat)

 Name
 PROPAN-2-OL

Toxic Dose 1 - LD 50 4700 - 5500 mg/kg (oral rat)
Toxic Conc. - LC 50 47 - 73 mg/l/4h (inh-rat)

Name ETHANEDIOL

 Toxic Dose 1 - LD 50
 4700 mg/kg (oral rat)

 Name
 2-AMINOETHANOL

 Toxic Dose 1 - LD 50
 1720 mg/kg (oral rat)

 Name
 MonoPropylene Glycol

 Toxic Dose 1 - LD 50
 >2000 mg/kg (oral rat)

Name Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic

# 12 ECOLOGICAL INFORMATION

## **ECOTOXICITY**

The product is not expected to be hazardous to the environment.

Name AMMONIA ...%

Ecotoxicity

Very toxic to aquatic organisms.

LC 50, 96 Hrs, Fish mg/l 15 EC 50, 48 Hrs, Daphnia, mg/l 89

Mobility

The product is water soluble and may spread in water systems.

Bioaccumulative potential

This material is not expected to significantly bioaccumulate.

Degradability

The product is biodegradable.

Name PROPAN-2-OL

LC 50, 96 Hrs, Fish mg/l 9600 EC 50, 48 Hrs, Daphnia, mg/l 4600

Name ETHANEDIOL

LC 50, 96 Hrs, Fish mg/l >100

Name 2-AMINOETHANOL

**Ecotoxicity** 

The product contains a substance which is harmful to aquatic organisms.

LC 50, 96 Hrs, Fish mg/l 170 - 227
EC 50, 48 Hrs, Daphnia, mg/l 65
IC 50, 72 Hrs, Algae, mg/l 15

Bioaccumulative potential

This material is not expected to significantly bioaccumulate.

Degradability

The product is easily biodegradable. The product is degraded completely by photochemical oxidation.

Name MonoPropylene Glycol
Partition Coefficient 0.92 (water/Octanol)

LC 50, 96 Hrs, Fish mg/l 40613 EC 50, 48 Hrs, Daphnia, mg/l >100

Name Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic

Report Date: 29/05/2012 REVISION DATE 02/12/2004

# Flameguard Ultra Vinyl Matt WHITE

## 13 DISPOSAL CONSIDERATIONS

**GENERAL INFORMATION** 

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

**DISPOSAL METHODS** 

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

# 14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

Nο

**ENVIRONMENTALLY HAZARDOUS** 

SUBSTANCE/MARINE POLLUTANT

# 15 REGULATORY INFORMATION

**EU DIRECTIVES** 

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

## **16 OTHER INFORMATION**

INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

**REVISION COMMENTS** 

This is first issue.

ISSUED BY

D Charles

**REVISION DATE** 02/12/2004

REV. NO./REPL. SDS GENERATED 1

SDS NO. 18094

SAFETY DATA SHEET STATUS

Approved.

DATE 29/05/2012

RISK PHRASES IN FULL

R34 Causes burns.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R22 Harmful if swallowed. R11 Highly flammable R36 Irritating to eyes.

R37 Irritating to respiratory system.

NC Not classified

R67 Vapours may cause drowsiness and dizziness.

R50 Very toxic to aquatic organisms.

HAZARD STATEMENTS IN FULL

H319 Causes serious eye irritation.

H314 Causes severe skin burns and eye damage.

Harmful if inhaled. H332 H302 Harmful if swallowed. H312 Harmful in contact with skin. H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness. H335 May cause respiratory irritation. H400

Very toxic to aquatic life.

Report Date : 29/05/2012

REVISION DATE 02/12/2004

# Flameguard Ultra Vinyl Matt WHITE

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.