

Page 1/9

## Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.08.2022 Version number 6 (replaces version 5) Revision: 31.08.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Trade name VERDÜNNUNG V 101

Article number: 0978

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance** / **the mixture** Thinner, Diluent **Uses advised against** No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13 Unit 4 , Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley – West Sussex RH10 9QU

Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

## **Hazard pictograms**









GHS02 GHS07 GHS08 GHS09

Signal word Danger

## Hazard-determining components of labelling:

hydrocarbons, C9, aromatics cumene

2-methoxy-1-methylethyl acetate

# Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article

Printing date 31.08.2022 Version number 6 (replaces version 5) Revision: 31.08.2022

## Trade name VERDÜNNUNG V 101

(Contd. of page 1)

## **Hazard statements**

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Solvent mixture.

Dangerous components [% w/w]:			
EC number: 918-668-5 Reg.nr.: 01-2119455851-35- XXXX	hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥80-100%	
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29- XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥5-<10%	
CAS: 98-82-8 EINECS: 202-704-5 Index number: 601-024-00-X	cumene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H335	≥1-<2.5%	

Additional information For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

### **General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

Immediately remove any clothing soiled by the product.

After inhalation Take affected persons into the open air and position comfortably

After skin contact Wash off immediately with water.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

## 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

nausea

Unconsciousness

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 31.08.2022

Version number 6 (replaces version 5)

## Trade name VERDÜNNUNG V 101

(Contd. of page 2)

Revision: 31.08.2022

# 4.3 Indication of any immediate medical attention and special treatment needed symptomatic treatment

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing agents

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

## 5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

## 5.3 Advice for firefighters

## Protective equipment:

Wear full protective suit.

Wear self-contained breathing apparatus.

#### **Additional information**

Cool endangered containers with water spray jet.

Use large quantities of foam as it is partially destroyed by the product.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

## 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

## 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

## 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

## Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: none

#### Further information about storage conditions:

Store container in a well ventilated position.

Keep container tightly closed.

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2022

Version number 6 (replaces version 5) Revision: 31.08.2022

## Trade name VERDÜNNUNG V 101

(Contd. of page 3)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Com	Components with limit values that require monitoring at the workplace:		
CAS: 108-65-6 2-methoxy-1-methylethyl acetate			
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk		
CAS: 98-82-8 cumene			
WEL	WEL Short-term value: 250 mg/m³, 50 ppm Long-term value: 125 mg/m³, 25 ppm Sk		

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see item 7.

Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures

Do not eat, drink or smoke while working.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euigment is not required or the amount of the PPE can be adpated accordingly.

## Respiratory equipment:

In case vapours/aerosols develop:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

Break through time: max. 240 min (DIN EN 374).

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

#### CTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid Colour: clear

according to 1907/2006/EC, Article 31

Printing date 31.08.2022 Version number 6 (replaces version 5) Revision: 31.08.2022

## Trade name VERDÜNNUNG V 101

(Contd. of page 4)

Odour:
Odour threshold:
Melting point/freezing point:

Aromatic
Not determined.
Not determined

Boiling point or initial boiling point and boiling

range 167 °C

Flammability Not applicable.

Lower and upper explosion limit

Lower: 1.5 Vol % 0.8 % (V)
Upper: 10.8 Vol % 6 % (V)

Flash point: 48 °C | Ignition temperature: 315 °C

**Decomposition temperature: pH**Not determined.
Not determined.

Viscosity:

**Kinematic viscosity at 20 °C** 9 s (DIN 53211/4) **dynamic:** Not determined.

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 1.3 hPa 1.3 hPa

Density and/or relative density

Density at 20 °C:

Relative density

Vapour density

0.87 g/cm<sup>3</sup>

Not determined.

Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

**Explosive properties:** Product is not explosive. However, formation of

dangerous explosive vapour/air mixtures is

possible.

Solvent separation test < 3 % Organic solvents: 100.0 % VOC EU 870.0 g/l

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard

classes
Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids

Self-reactive substances and mixtures

Pyrophoric liquids

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit

flammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoid

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Version number 6 (replaces version 5) Printing date 31.08.2022 Revision: 31.08.2022

## Trade name VERDÜNNUNG V 101

(Contd. of page 5)

Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

## Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:			
CAS: 108-	CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,500 mg/kg (rat)	
Inhalative	LC50/4 h	35.7 mg/l (rat)	

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

## **Endocrine disrupting properties**

None of the ingredients is listed.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

## 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. vPvB: Not applicable.

## 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

## 12.7 Other adverse effects

Remark: Toxic for fish

## Additional ecological information:

#### **General notes:**

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

(Contd. on page 7)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2022 Version number 6 (replaces version 5)

## Trade name VERDÜNNUNG V 101

(Contd. of page 6)

Revision: 31.08.2022

## **SECTION 13: Disposal considerations**

#### Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions. Must be specially treated in compliance with official regulations.

## European waste catalogue

07 06 04\* other organic solvents, washing liquids and mother liquors

#### Uncleaned packaging:

#### Recommendation:

Packaging can be reused or recycled after cleaning.

Disposal must be made according to official regulations.

SECTION 14: Transport information		
14.1 UN number or ID number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG IATA	1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL, MARINE POLLUTANT PAINT RELATED MATERIAL	
14.3 Transport hazard class(es)		
ADR		
Class Label	3 (F1) Flammable liquids. 3	
IMDG		
<b>*</b>		
Class Label	3 Flammable liquids. 3	
IATA		
Class Label	<ul><li>3 Flammable liquids.</li><li>3</li></ul>	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Product contains environmentally hazardous	
Marine pollutant:	substances: hydrocarbons, C9, aromatics Yes	
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)	
14.6 Special precautions for user hazard identification number: EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>	

according to 1907/2006/EC, Article 31

Printing date 31.08.2022

Version number 6 (replaces version 5)

## Trade name VERDÜNNUNG V 101

(Contd. of page 7)

Revision: 31.08.2022

Stowage Category	A	
14.7 Maritime transport in bulk according to		
IMO instruments	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III,	
	ENVIRONMENTALLY HAZARDOUS	

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

## **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

## Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

## Relevant phrases

Flammable liquid and vapour. H226

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 Calculation method

(Contd. on page 9)

Page 9/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.08.2022 Version number 6 (replaces version 5)

Trade name VERDÜNNUNG V 101

(Contd. of page 8)

Revision: 31.08.2022

Department issuing data specification sheet: Product Safety department / EHS Version number of previous version: 5

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2