

Page 1/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 (replaces version 4) Revision: 29.04.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

# Trade name EPOXY COLOR TOP KOMP A

Article number: 6190-6196

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

**Process category** 

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

# Application of the substance / the mixture

Coating Sealing

# 1.3 Details of the supplier of the safety data sheet

# Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13 Unit 4 Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley - West Sussex RH10 9QU Tel.: +49(0)5432/83-0

fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

Information department:

Fax: +49(0)5432/3985

Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

# 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 11.10.2021 Version number 5 (replaces version 4) Revision: 29.04.2020

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 1)

# **Hazard pictograms**





GHS07 GHS09

# Signal word Warning

#### Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,6-Bis(2,3-epoxypropoxy)hexan

# **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

# **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

# Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

# 2.3 Other hazards

# Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205  Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	≥25-<40%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥5-<10%

(Contd. on page 3)

Printing date 11.10.2021

Version number 5 (replaces version 4) Revision: 29.04.2020

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 2)

	(1)	contd. of page 2)
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	≥2.5-<5%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22- XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17- XXXX	titanium dioxide Carc. 2, H351	≥2.5-<5%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41- XXXX	1,6-Bis(2,3-epoxypropoxy)hexan Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-≤0.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### **General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

#### After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

#### After skin contact

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

#### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

# After swallowing

Rinse out mouth immediately with plenty of water and administer plenty of water in small swallows (diluting effect).

# 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing agents

Water spray jet

Foam

Carbon dioxide

Fire-extinguishing powder

# 5.2 Special hazards arising from the substance or mixture

May be released in case of fire

carbon monoxides

further harmful conflagration gases and fumes

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCI)

# 5.3 Advice for firefighters

# **Protective equipment:**

Wear full protective suit.

Wear self-contained breathing apparatus.

(Contd. on page 4)

Printing date 11.10.2021

Version number 5 (replaces version 4)

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 3)

Additional information Collect contaminated fire fighting water separately. It must not enter drains.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

# 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

# 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires: No special requirements.

# 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

# Requirements to be met by storerooms and containers:

Suitable material for containers and pipes: Light metals and their alloys.

Prevent any penetration into the ground.

Information on storage in a common storage facility: none

# Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

# 8.1 Control parameters

# Components with limit values that require monitoring at the workplace:

# CAS: 13463-67-7 titanium dioxide

WEL Long-term value: 10\* 4\*\* mg/m³

\*total inhalable \*\*respirable

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see item 7.

# Individual protection measures, such as personal protective equipment

# General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euigment is not required or the amount of the PPE can be adpated accordingly.

(Contd. on page 5)

Revision: 29.04.2020

Printing date 11.10.2021 Version number 5 (replaces version 4) Revision: 29.04.2020

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 4)

# Respiratory equipment:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

## Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

# Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

# SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

**General Information** 

**Colour:** According to product specification

Odour:Weak, characteristicOdour threshold:Not determined.Melting point/freezing point:Not determined

Boiling point or initial boiling point and boiling

range Not determined Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableDecomposition temperature:Not determined.pHNot determined.

Viscosity:

**Kinematic viscosity dynamic at 20 °C:**Not determined.
4500 mPas

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not determined.

Density and/or relative density

Density at 20 °C:1.65 g/cm³Relative densityNot determined.Vapour densityNot determined.

# 9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

**Ignition temperature:** not applicable

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 (replaces version 4) Revision: 29.04.2020

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 5)

	( 10 /
Explosive properties: Solvent separation test	Product is not explosive. < 3 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void
<u>-</u>	

# **SECTION 10: Stability and reactivity**

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly. None if stored properly.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:		
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)		
Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

### Skin corrosion/irritation:

Causes skin irritation.

# Serious eye damage/irritation:

Causes serious eye irritation.

Sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 11.10.2021

Version number 5 (replaces version 4)

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 6)

Revision: 29.04.2020

#### 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

# 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

# 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects Remark: Toxic for fish

Additional ecological information:

**General notes:** 

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

# SECTION 13: Disposal considerations

# Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

## European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

# Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)))

(Contd. on page 8)

Printing date 11.10.2021 Version r

Version number 5 (replaces version 4)

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 7)

Revision: 29.04.2020

	(Contd. of page 7)
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9
IMDG, IATA	
Class Label	<ul><li>9 Miscellaneous hazardous substances and articles.</li><li>9</li></ul>
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight $\leq 700$ ))
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and articles.
hazard identification number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according IMO instruments	g to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1  Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700))), 9, III

(Contd. on page 9)

Printing date 11.10.2021

Version number 5 (replaces version 4)

# Trade name EPOXY COLOR TOP KOMP A

(Contd. of page 8)

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### **National regulations**

# Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

#### Relevant phrases

H302	Harmful if swallowed

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

# Version number of previous version: 4

# Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

(Cantal of mana

Revision: 29.04.2020