

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **EPOXY COLOR TOP KOMP. B**

Article number: 6188-6196

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Sector of Use

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

**Product category** PC9a Coatings and paints, thinners, paint removers

**Process category** PROC10 Roller application or brushing

**Environmental release category** ERC11a Widespread use of articles with low release (indoor)

**Article category** AC0 Other

**Technical function** Plating agent

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH

Postfach 1255

D-49624 Lönningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

##### Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

Remmers (UK) Limited  
Unit B1 The Fleming Centre  
West Sussex RH10 9NN  
fon +44 (0) 1293 594 010  
fax +44 (0) 1293 594 037

#### 1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 1)

**Hazard pictograms**

GHS05 GHS07

**Signal word** Danger**Hazard-determining components of labelling:**

benzyl alcohol  
 m-phenylenebis(methylamine)  
 3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 salicylic acid  
 phenol, styrenated

**Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264 Wash thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of the substances listed below with harmless additions.

<b>Dangerous components:</b>		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	≥40-<60%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥20-<25%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥20-<25%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≥2.5-<5%
CAS: 61788-44-1 Reg.nr.: 01-2119486984-17-XXXX	phenol, styrenated Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<5%

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 2)

CAS: 69-72-7 EINECS: 200-712-3 Index number: 607-732-00-5	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<2.5%
---	---	----------

**Additional information** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

#### After skin contact

Do not use solvents or thinners!

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

**After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

#### After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

### 5.2 Special hazards arising from the substance or mixture

Thick black smoke forms in fires. Inhalation of dangerous decomposition products may cause serious damage to your health.

May be released in case of fire

Nitrogen oxides (NO<sub>x</sub>)

carbon monoxides

### 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

#### Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid skin contact. Avoid eye contact.

Do not breathe fumes/aerosol

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 3)

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

**Information about protection against explosions and fires:** Keep breathing equipment ready.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.**Information on storage in a common storage facility:** Store away from food.**Further information about storage conditions:**

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical systems:** No further data; see item 7.**8.1 Control parameters****Components with limit values that require monitoring at the workplace:****CAS: 64-17-5 ethanol**WEL | Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**Additional information:** The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

**Respiratory equipment:**

Short term filter device:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

**Protection of hands:**

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tightly sealed safety glasses.**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

<b>9.1 Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Colour:</b>	Clear
<b>Odour:</b>	Amine-like
<b>Odour threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Not determined
<b>Initial boiling point and boiling range:</b>	Not determined
<b>Flash point:</b>	64 °C
<b>Inflammability (solid, gaseous)</b>	Not applicable.
<b>Ignition temperature:</b>	not applicable
<b>Decomposition temperature:</b>	Not determined.
<b>Self-inflammability:</b>	Product is not self-igniting.
<b>Explosive properties:</b>	Product is not explosive.
<b>Explosive Limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	0.1 hPa
<b>Density at 20 °C:</b>	1.05 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Distribution coefficient (n-octanol/water):</b> Not determined.	
<b>Viscosity:</b>	
<b>dynamic at 20 °C:</b>	90 mPas
<b>kinematic:</b>	Not determined.
<b>Solvent separation test</b>	< 3 %
<b>9.2 Other information</b>	No further relevant information available.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 5)

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if handled and stored according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:**

None if used properly.

None if stored properly.

## SECTION 11: Toxicological information

**11.1 Information on toxicological effects****Acute toxicity:**

Harmful if swallowed or if inhaled.

**LD/LC50 values that are relevant for classification:****CAS: 100-51-6 benzyl alcohol**

Oral LD50 1,230 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

**CAS: 1477-55-0 m-phenylenebis(methylamine)**

Oral LD50 1,040 mg/kg (rat)

Inhalative LC50/4 h 2.4 mg/l (rat)

**CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral LD50 1,030 mg/kg (rat)

Dermal LD50 1,840 mg/kg (rabbit)

**Skin corrosion/irritation:**

Causes severe skin burns and eye damage.

**Serious eye damage/irritation:**

Causes serious eye damage.

**Sensitisation:**

May cause an allergic skin reaction.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.**Aspiration hazard:** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

**12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Harmful to fish**Additional ecological information:****General notes:**

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 6)

**12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

**Recommendation**



Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

<b>14.1 UN-Number</b>	UN2735
<b>ADR, IMDG, IATA</b>	
<b>14.2 UN proper shipping name</b>	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.
<b>ADR</b>	(3-aminomethyl-3,5,5-trimethylcyclohexylamine)
<b>IMDG, IATA</b>	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)
<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
	
<b>Class</b>	8 (C7) Corrosive substances.
<b>Label</b>	8
<b>IMDG, IATA</b>	
	
<b>Class</b>	8 Corrosive substances.
<b>Label</b>	8
<b>14.4 Packing group</b>	III
<b>ADR, IMDG, IATA</b>	
<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Warning: Corrosive substances.
<b>hazard identification number:</b>	80
<b>EMS Number:</b>	F-A,S-B
<b>Segregation groups</b>	Alkalis
<b>Stowage Category</b>	A
<b>Segregation Code</b>	SG35 Stow "separated from" SGG1-acids
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

Trade name **EPOXY COLOR TOP KOMP. B**

(Contd. of page 7)

Transport/Additional information:	
<b>ADR</b>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
<b>IMDG</b>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-AMINOMETHYL-3,5,5- TRIMETHYLCYCLOHEXYLAMINE), 8, III

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

#### National regulations

#### Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H361d Suspected of damaging the unborn child.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008** Calculation method

**Department issuing data specification sheet:** Product Safety department / EHS

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 10.03.2020

Version number 4

Revision: 06.08.2019

**Trade name EPOXY COLOR TOP KOMP. B**

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3