# **SAFETY DATA SHEET**





#### SILOKSAN FACADE - All variants

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SILOKSAN FACADE - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product description : Paint.

1.3 Details of the supplier of the safety data sheet

knos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Frod-safe@teknos.com

**National contact** 

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

Telephone number : Teknos UK Limited; TEL: +44 1608 683 494; Opening hours: MON-FRI, 7am – 6pm.

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word : Warning

Hazard statements : №317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**General** : P102 - Keep out of reach of children.

Prevention : P280 - Wear protective gloves.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapour.

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

STLOKSAN FACADE - All variantsLabel No : 3/4878Date of issue/Date of revision: 20/12/2021 Date of previous issue: 29/10/2020 Version : 2 1/13

## **SECTION 2: Hazards identification**

**Hazardous ingredients** 

: 4,5-dichloro-2-octyl-2H-isothiazol-3-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Supplemental label elements

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for dry film and in-can preservation: IPBC and DCOIT and EGForm and C(M)IT/MIT (3:1) and OIT. Risk of skin sensitisation.

**Annex XVII - Restrictions** on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

#### 2.3 Other hazards

3.2 Mixtures

Other hazards which do not result in classification : None known.

# **SECTION 3: Composition/information on ingredients**

# : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	[1] [*]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	≤0.023	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
			See Section 16 for the full text of the H statements declared above.	

SILOKSAN FACADE - All variants **Label No** : 34878 Date of issue/Date of revision Version : 2 : 29/10/2020 2/13 : 20/12/2021 Date of previous issue

# **SECTION 3: Composition/information on ingredients**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy
- [\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with diameter ≤ 10 μm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Femove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: ₩ash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**Label No** : 34878

#### 4.2 Most important symptoms and effects, both acute and delayed

## Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Freat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

SILOKSAN FACADE - All variants

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 3/13

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

## 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: In a fire, decomposition may produce toxic gases/fumes.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

Fspecialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# **6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

# 6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Label No : 34878

SILOKSAN FACADE - All variants

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 4/13

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## 7.2 Conditions for safe storage, including any incompatibilities

To not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds (in tonnes)

#### 7.3 Specific end use(s)

Recommendations : Mot available.

Industrial sector specific : Mot available.

solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

## 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

# Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
Manium dioxide	DNEL	Long term Inhalation	10 mg/m³	Workers	Local
	DNEL	Long term Oral	700 mg/kg bw/day	General population	Systemic

#### **PNECs**

SILOKSAN FACADE - All variants

Label No : 34878

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 5/13

# **SECTION 8: Exposure controls/personal protection**

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Mitrile gloves. thickness > 0.3 mm

Not recommended village of the suitable gloves tested to EN374.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Refer to European Standard EN 14605 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): P

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Label No** : 34878

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : ☑quid.
Colour : ☑quid.
Odour : ☑fight

Odour threshold: Mot available.

PH: Mot available.

Mot available.

Mot available.

Initial boiling point and: Mot available.

boiling range

SILOKSAN FACADE - All variants

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 6/13

# SECTION 9: Physical and chemical properties

Flash point : Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or : Lower: 0.8% explosive limits Upper: 73% Not available. Vapour pressure

Not available. Vapour density 1.4 kg/l **Density** Not available. Solubility(ies) Partition coefficient: n-octanol/ : Not applicable.

water

Not available. **Auto-ignition temperature** : Not available. **Decomposition temperature** Not available. **Viscosity** : Not available. **Explosive properties** : Not available. **Oxidising properties** 

9.2 Other information

VOC g/l Solubility in water Not available.

No additional information.

# SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Label No : 34878

# SECTION 11: Toxicological information

## 11.1 Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
	LC50 Inhalation Dusts and mists	Rat	0.67 g/m³	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat - Male, Female	0.26 mg/l	4 hours
	LD50 Dermal	Rabbit	>652 mg/kg	-
	LD50 Oral	Rat	1585 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7]	LD50 Oral	Rat	53 mg/kg	-

SILOKSAN FACADE - All variants

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 7/13

# **SECTION 11: Toxicological information**

and 2-methyl-2H-isothiazol-		
3-one [EC no. 220-239-6] (3:		
1)		

Conclusion/Summary

: Based on available data, the classification criteria are not met.

**Acute toxicity estimates** 

Not available.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug I	-
3-iodo-2-propynyl-butyl carbamate	Eyes - Severe irritant	Rabbit	-	-	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

## **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
	skin	Guinea pig	Not sensitizing

**Conclusion/Summary** 

: May cause an allergic skin reaction.

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
<b>3</b> -iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

**Carcinogenicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
<b>3</b> -iodo-2-propynyl-butyl carbamate	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week
	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

## **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
<b>3</b> -iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

SILOKSAN FACADE - All variantsLabel No : 34878Date of issue/Date of revision: 20/12/2021 Date of previous issue: 29/10/2020Version : 2 8/13

# **SECTION 11: Toxicological information**

Product/ingredient name	Category	Route of exposure	Target organs
<b>3</b> -iodo-2-propynyl-butyl carbamate	Category 1	-	larynx

#### **Aspiration hazard**

Not available.

Information on likely routes :

of exposure

: Not available.

Potential acute health effects

Eye contactInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInhalationInha

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : Ønce sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Other information : Not available.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

ØLOKSAN FACADE - All variantsLabel No : 3/4878Date of issue/Date of revision: 20/12/2021 Date of previous issue: 29/10/2020Version : 2 9/13

# **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
Manium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
3-iodo-2-propynyl-butyl carbamate	Acute EC50 0.022 mg/l Fresh water	Algae - Scenedemus subspicatus	72 hours
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute EC50 18 ppb Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 0.003 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0.001 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 22 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 2.7 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 19.789 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.56 ppb	Fish - Oncorhynchus mykiss	97 days

**Conclusion/Summary**: Farmful to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

**Conclusion/Summary**: This product has not been tested for biodegradation.

Aquatic half-life	Photolysis	Biodegradability
-	-	Not readily
	Aquatic half-life -	· · · · · · · · · · · · · · · · · · ·

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
<b>3</b> -iodo-2-propynyl-butyl carbamate	>1	-	low

12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

Mobility : Not available.

## 12.5 Results of PBT and vPvB assessment

PBT : Mot applicable.

vPvB : Mot applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

**Product** 

SILOKSAN FACADE - All variantsLabel No : 34878Date of issue/Date of revision: 20/12/2021Date of previous issue: 29/10/2020Version : 210/13

# SECTION 13: Disposal considerations

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue: 080111\*, 200127\*

(EWC)

**Packaging Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	<b>N</b> ot regulated.	<b>⋈</b> ot regulated.	<b>N</b> ot regulated.	₩ot regulated.
14.2 UN proper shipping name				
14.3 Transport hazard class(es)				
14.4 Packing group				
14.5 Environmental hazards	Mo.	No.	No.	No.
Additional information	<b>-</b>	<b>F</b>		

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

SILOKSAN FACADE - All variants **Label No** : 34878 Date of issue/Date of revision Version : 2 : 20/12/2021 Date of previous issue : 29/10/2020 11/13

# **SECTION 15: Regulatory information**

Annex XVII - Restrictions : on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Europe inventory : Not determined.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Seveso Directive** 

Other EU regulations

This product is not controlled under the Seveso Directive.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method	

Full text of abbreviated H statements

SILOKSAN FACADE - All variants

Label No : 34878

Date of issue/Date of revision : 20/12/2021 Date of previous issue : 29/10/2020 Version : 2 12/13

## **SECTION 16: Other information**

<b>⊮</b> 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

## Full text of classifications [CLP/GHS]

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Carc. 2 Eye Dam. 1	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1 Skin Corr. 1C Skin Sens. 1	SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1C SKIN SENSITISATION - Category 1
Skin Sens. 1A STOT RE 1	SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of

revision

Date of previous issue : 29/10/2020

Version : 2

SLOKSAN FACADE

: 20/12/2021

## M variants

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

SILOKSAN FACADE - All variantsLabel No : 34878Date of issue/Date of revision: 20/12/2021 Date of previous issue: 29/10/2020Version : 2 13/13