Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 - United Kingdom (UK)

## SAFETY DATA SHEET



UVILUX SEALER 1453-02 - HY 0020 CLEAR

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

: UVILUX SEALER 1453-02 - HY 0020 CLEAR

**1.2 Relevant identified uses of the substance or mixture and uses advised against Product description** : Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : prod-safe@teknos.com responsible for this SDS

## **National contact**

Teknos (UK) Limited, Unit E1, Heath Farm, Banbury Road, Swerford, Oxfordshire OX7 4BN, United Kingdom. Tel. +44 (0) 1608 683 494.

#### 1.4 Emergency telephone number

Telephone number : Teknos UK Limited; TEL: +44 1608 683 494; Opening hours: MON-FRI, 7am – 6pm.

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** 



Signal word	Irning	
Hazard statements	<ul> <li>H319 - Causes serious eye irritation.</li> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H335 - May cause respiratory irritation.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>	
Precautionary statements		
General	applicable.	
Prevention	80 - Wear protective gloves. Wear e 73 - Avoid release to the environmer	

## **SECTION 2: Hazards identification**

Response	: P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	<ul> <li>4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2, 3-epoxypropane, esters with acrylic acid (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate</li> <li>2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)]] ester, reaction products with diethylamine</li> <li>Propylidynetrimethanol, ethoxylated, esters with acrylic acid</li> </ul>
Supplemental label elements	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
.3 Other hazards	

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : M	ixture			
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥25 - ≤50	Skin Sens. 1, H317	[1]
(1-methyl-1,2-ethanediyl)bis[oxy (methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≥10 - <25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
2-Propenoic acid, 1,1'-[(1-methyl-1, 2-ethanediyl)bis[oxy(methyl-2, 1-ethanediyl)]] ester, reaction products with diethylamine	REACH #: 01-2119961351-42 CAS: 111497-86-0	≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	[1]
Propylidynetrimethanol,	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≤5	Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
2-hydroxy-2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119976378-19 CAS: 85711-46-2	≤0.3	Skin Irrit. 2, H315 Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

UVILUX SEALER 1453-02 - HY 00	20 CLEAR			Label No	:21056	3
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	2/12

## **SECTION 3: Composition/information on ingredients**

## Туре

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

•	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Over-exposure signs/sympt	<u>oms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

## 4.3 Indication of any immediate medical attention and special treatment needed

UVILUX SEALER 1453-02 - H	Y 0020 CLEAR			Label No	:2105	6
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	3/12

# SECTION 4: First aid measures Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Specific treatments : No specific treatment. SECTION 5: Firefighting measures 5.1 Extinguishing media

Suitable extinguishing media	Jse an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising f	the substance or mixture	
Hazards from the substance or mixture	n a fire or if heated, a pressure increase will occur and the container m This material is harmful to aquatic life with long lasting effects. Fire wat contaminated with this material must be contained and prevented from lischarged to any waterway, sewer or drain.	ter
Hazardous combustion products	n a fire, decomposition may produce toxic gases/fumes.	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of t here is a fire. No action shall be taken involving any personal risk or w suitable training.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-cor- preathing apparatus (SCBA) with a full face-piece operated in positive p node. Clothing for fire-fighters (including helmets, protective boots and conforming to European standard EN 469 will provide a basic level of p chemical incidents.	oressure d gloves)

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for o	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

UVILUX SEALER 1453-02 - HY 0	020 CLEAR			Label No	2105	6
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	4/12

## **SECTION 6: Accidental release measures**

6.4 Reference to other	
sections	

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific solutions

## : Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

## **Occupational exposure limits**

No exposure limit value known.

#### **Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### PNECs

UVILUX SEALER 1453-02 - HY 00	20 CLEAR			Label No	:21056	6
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	5/12

## **SECTION 8: Exposure controls/personal protection**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374. < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm > 8 hours (breakthrough time): 4H / Silver Shield® gloves.
	Wash hands before breaks and immediately after handling the product.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Refer to European Standard EN 14605 for further information on material and design requirements and test methods.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	spray application Filter type: A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

Date of issue/Date of revision

9.1 Information on basic physic	al and chemical properties	
Appearance		
Physical state	: Liquid.	
Colour	: Clear.	
Odour	: Slight	
Odour threshold	: Not available.	
рН	: Not available.	
Melting point/freezing point	: Not available.	
UVILUX SEALER 1453-02 - HY 0	020 CLEAR	Label No :21056

: 25/10/2018 Date of previous issue

: 20/07/2016 Version : 1.03 6/12

## **SECTION 9: Physical and chemical properties**

	10	ononnoar prop
Initial boiling point and boiling range	:	Not available.
Flash point	:	Closed cup: >100°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Lower: 0.8% Upper: 7.6%
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Density	:	1.3 kg/l
Solubility(ies)	:	Not available.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Not available.
Explosive properties	:	Not available.
Oxidising properties	:	Not available.
9.2 Other information		
VOC	1	8 g/l
Solubility in water	:	Not available.
No additional information.		

## **SECTION 10: Stability and reactivity**

		-
10.1 Reactivity	No spec	cific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	The pro	duct is stable.
10.3 Possibility of hazardous reactions	Under r	ormal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	No spe	cific data.
10.5 Incompatible materials	No spec	cific data.
10.6 Hazardous decomposition products		normal conditions of storage and use, hazardous decomposition products not be produced.

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	LD50 Oral	Rat	6200 mg/kg	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
2-hydroxy- 2-methylpropiophenone	LD50 Dermal	Rat	6929 mg/kg	-
	LD50 Oral	Rat	1694 mg/kg	-

UVILUX SEALER 1453-02 - HY 0020 CLEAR				Label No	:2105	6
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	7/12

## **SECTION 11: Toxicological information**

## Acute toxicity estimates

Route	ATE value
Oral	85702.7 mg/kg

## Irritation/Corrosion

Intation/Corrosion	1	1	-		
Product/ingredient name	Result	Species	Score	Exposure	Observation
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	Eyes - Severe irritant	Rabbit	-	24 hours 100 microliters	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
<b>Conclusion/Summary</b>	: Causes skin irritation.				
<u>Sensitisation</u>					
<b>Conclusion/Summary</b>	: May cause an allergic skin re	eaction.			
<u>Mutagenicity</u>					
Conclusion/Summary	: Based on available data, the	classification c	riteria are	not met.	
Carcinogenicity					
Conclusion/Summary	: Based on available data, the	classification c	riteria are	e not met.	
Reproductive toxicity					
Conclusion/Summary	: Based on available data, the	classification c	riteria are	e not met.	
Teratogenicity					
Conclusion/Summary	: Based on available data, the	classification c	riteria are	not met.	
Specific target organ toxicit	<u>y (single exposure)</u>				

Product/ingredient name	Category	Route of exposure	Target organs
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

## Information on likely routes : Not available.

of exposure

#### Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : May cause respiratory irritation. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards.

Symptoms related to the phy	ysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing

UVILUX SEALER 1453-02 - HY 00	20 CLEAR			Label No	:21056	
Date of issue/Date of revision	: 25/10/2018	Date of previous issue	: 20/07/2016	Version	:1.03	8/1

SECTION 11: Toxicological information				
Skin contact	:	Adverse symptoms may include the following: irritation redness		
Ingestion	:	No specific data.		
Delayed and immediate effect	<u>ts</u>	as well as chronic effects from short and long-term exposure		
<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	1	Not available.		
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Potential chronic health eff Not available.	<u>ect</u>	<u>s</u>		
Conclusion/Summary		Not available.		
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.		
Carcinogenicity	1	No known significant effects or critical hazards.		
Mutagenicity	1	No known significant effects or critical hazards.		
Teratogenicity	:	No known significant effects or critical hazards.		
<b>Developmental effects</b>	:	No known significant effects or critical hazards.		
Fertility effects	:	No known significant effects or critical hazards.		

## **Other information**

: Not available.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Conclusion/Summary

: Harmful to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily

## 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2, 3-epoxypropane, esters with	1.6 to 3	-	low
acrylic acid (1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	low
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	low
2-hydroxy- 2-methylpropiophenone	1.62	-	low

## **SECTION 12: Ecological information**

12.4 Mobility in soil	
Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment		
PBT	: Not applicable.	
vPvB	: Not applicable.	

12.6 Other adverse effects : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

-		
13.1 Waste treatment method	S	
Product		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	Yes.
European waste catalogue (EWC)	1	080111*
Packaging		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	:	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Additional information	-	The product is only regulated as a dangerous good when transported in tank vessels.	-	-

## **SECTION 14: Transport information**

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not relevant/applicable due to nature of the product.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

#### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Other EU regulations

**Europe inventory** : Not determined.

•

**Black List Chemicals** 

(76/464/EEC)

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

$\checkmark$	Indicates information that has changed from previously issued version.	
--------------	--	--

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

I dir text of classifications		
Acute Tox. 4, H302 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Skin Sens. 1B, H317 STOT SE 3, H335		ACUTE TOXICITY (oral) - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
Date of issue/ Date of revision	: 25/10/2018	
Date of previous issue	: 20/07/2016	
Version	: 1.03	

LIVILLIX SEALER 1453-02 HV 0020

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.