

TEKNOFILL 5001

Acrylate Filler

TEKNOFILL 5001-00, an aqueous product for spot filling of primed wood designated for interior and exterior use such as windows and doors.

To be used together with ANTISTAIN AQUA 5200 to minimise resin penetration from knots in pine.



TECHNICAL DATA

Fields of application	Exterior doors, Windows
Recommended substrate	Hardwood, Softwood
Volatile organic compound (VOC)	See safety data sheet.
Colours	White.
Storage	Storage temperature is +5°C - +30°C. Shelf life in unopened containers: See "Best before date" on the label. Keep containers tightly closed after use.
Packaging	235 ml tube

DIRECTION FOR USE

Surface preparation	<p>The primed wood must be clean and free from wood dust and contamination. The moisture content of the wood should be approx. 13% and should not exceed 15%.</p> <p>Pretreatment is required for wood substrates not meeting Durability Class 3, EN 350:2016.</p> <p>Teknos has a range of preservative products meeting the requirements of EN 599-1, please contact Teknos for further guidance.</p>
Application method	Filling knife
Application conditions	<p>Optimum temperature for products and surroundings: +18°C - +22°C.</p> <p>Optimum relative air humidity: Approx. 50%.</p> <p>Do not use at the following temperatures: Below +5°C and above +25°C.</p>
Thinning	The product is delivered ready for use.
Drying time	+23°C / 50% RH
Fit for sanding and overcoating	1-3 h
	The drying times are approximate and may vary according to wood quality, temperatures, humidity, ventilation, and film thickness.
Coating system	Primed parts must always be protected with a topcoat treatment before they are exposed to the influence of the weather.
Cleaning	Water.

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.