

Wood Preservative & Primer

AQUAPRIMER 2907

**Protect your wood against biological factors**

AQUAPRIMER 2907-02: a translucent, water based, combi primer for softwood and hardwood in hazard risk class 3 combining base stain and wood preservative capabilities in a single product.

Applied by flow or dip coater, protects exterior joinery against wood destroying fungi and blue stain when used in combination with Teknos' fully factory finished top coat systems.

AQUAPRIMER 2907-42: an opaque sprayable primer for protection against bluestain.

Proven protection

AQUAPRIMER 2907-02 (translucent) meets EN 599 standard (includes EN 113 and EN 152). AQUAPRIMER 2907-42 (opaque) meets the EN 152 standard.


EU regulations

AQUAPRIMER 2907 is being supported in accordance with the BPR Directive and complies with the VOC Directive. We work continuously to ensure our products comply with REACH regulations.

Give us a call


A call to Teknos is a quick and easy way to get sound advice if you are considering using AQUAPRIMER 2907 or any other Teknos coating product.


Our technical support organisation are always ready to support you in designing your optimal coatings solution and application system.



▲ Translucent
AQUAPRIMER 2907-02
for flowcoating and
dipping

Opaque AQUAPRIMER
2907-42 for spraying ▼





Features and benefits

Features	Benefits
Includes optimised combination of fungicides	AQUAPRIMER 2907-02: Effective protection against bluestain and wood-degrading fungi
	AQUAPRIMER 2907-42: Effective protection against bluestain
Low viscosity	Deeper penetration of fungicides into the wood
Combines the conventional wood preservative features with the features of a conventional primer	Ease and speed of application as 2 conventional layers can be applied in a single coat

AQUAPRIMER 2907-02* / 2907-42*

Product	AQUAPRIMER 2907-02	AQUAPRIMER 2907-42
Content	Synthetic binder, fungicides, water	Synthetic binder, fungicides, water
Colour	Colourless and translucent shades	White
Packing	20, 120, 1000 l	20, 120, 1000 l

Recommended coating systems

	Softwood 2-layers Translucent / Opaque	All wood species 3-layers Translucent / Opaque
Wood preservative * / Primer *	AQUAPRIMER 2907-02	AQUAPRIMER 2907-02
Intermediate		AQUAFILLER 6500
Top-coat	AQUATOP 2600	AQUATOP 2600

* Use biocides safely. Always read the label and product information before use.

www.teknos.com

Teknos A/S
 Industrivej 19
 DK-6580 VAMDRUP
 Danmark
 Tel. +45 76 93 94 00
salg@teknos.dk

Teknos Oy
 Takkatie 3, P.O.Box 107
 FI-00371 HELSINKI
 Finland
 Tel. +358 9 506 091
sales@teknos.fi