

## Primer

AQUAPRIMER 2900-02  
ANTISTAIN AQUA 2901-52



### Primers for tomorrows needs

Teknos' standard flow coat primers have been developed to meet the growing demand for high quality wooden windows and doors. Its robust formulation can be applied on a wide variety of application equipment.

### Practical formulations

Teknos flow coat primers offer good equalisation, hiding power, sandability, and run-off.

The primers are formulated to offer a certain reduction in discoloration from water soluble tannins and extractives from hardwood and around knots in softwood (1)

AQUAPRIMER 2900-02 is available in translucent colours and ANTISTAIN AQUA 2901-52 is available in white.

### The value of higher speed

We all know how important it is that your manu-

facturing process runs smoothly and fast, but it is equally important that the surface coating process applied is of high quality. Applied with flow-coat AQUAPRIMER 2900-02 / ANTISTAIN AQUA 2901-52 are good foundations for continuous fast production processes with no compromise on quality and durability.

### EU regulations

Teknos products comply with the VOC Directive and we work continuously to ensure that our products comply with REACH regulations.

### Give us a call


A call to Teknos is a quick and easy way to get sound advice if you are considering using AQUAPRIMER 2900-02 / ANTISTAIN AQUA 2901-52 or any other Teknos coating product.

Our technical support organisation are always ready to support you in designing your optimal coatings solution and application system.



▲ The primer offers a high colour equalisation effect ▼

To secure coverage of end grains and V-joints the primer should be flowcoated ▼





## Features and benefits

| Features                                                                                      | Benefits                                                                                                                                                      |
|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Excellent run off and wetting properties                                                      | This ensures a trouble free priming process with excellent surface appearance – fine crafted for the subsequent layers                                        |
| Increased colour pigmentation levels can be obtained thanks to a high dry content formulation | High colour equalisation effects can be incorporated in the colour formulation from translucent to opaque colour, returning a more even colour primed surface |
| Implementation of a high end de foaming system ensures a highly persistent formulation        | Ensures a smooth and fast manufacturing process without having to build in corrective actions during operation                                                |
| Formulated to reduce the colour migration from tannin extractives (1)                         | A high quality primed surface reducing problems with migration discolouration coming through the topcoat                                                      |

(1) To obtain a higher reduction in discolouration from water soluble and extractives around knots in softwood we recommend to use ANTISTAIN AQUA 5200.

## AQUAPRIMER 2900-02 / ANTISTAIN AQUA 2901-52

| Product | AQUAPRIMER 2900-02      | ANTISTAIN AQUA 2901-52  |
|---------|-------------------------|-------------------------|
| Content | Synthetic binder, water | Synthetic binder, water |
| Colour  | Translucent             | White and opaque        |
| Packing | 3, 10, 20, 120, 1000 l. | 3, 10, 20, 120, 1000 l. |

## Recommended coating systems

|                     | Softwood 3-layers<br>Translucent / Opaque                                 | All wood species 4-layers<br>Translucent / Opaque                         |
|---------------------|---------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Wood preservative * | TEKNOL AQUA 1410 / TEKNOL AQUA 1412-01 / TEKNOL S 6005-00                 | TEKNOL AQUA 1410 / TEKNOL AQUA 1412-01 / TEKNOL S 6005-00 **              |
| Primer              | AQUAPRIMER 2900-02 (translucent) / ANTISTAIN AQUA 2901-52 (white, opaque) | AQUAPRIMER 2900-02 (translucent) / ANTISTAIN AQUA 2901-52 (white, opaque) |
| Intermediate        |                                                                           | AQUAFILLER 6500                                                           |
| Top-coat            | AQUATOP 2600                                                              | AQUATOP 2600                                                              |

\* Use biocides safely. Always read the label and product information before use.  
\*\* Only softwood.

**www.teknos.com**

**Teknos A/S**  
Industrivej 19  
DK-6580 VAMDRUP  
Denmark  
Tel. +45 76 93 94 00  
salg@teknos.dk

**Teknos Oy**  
Takkatie 3, P.O.Box 107  
FI-00371 HELSINKI  
Finland  
Tel. +358 9 506 091  
sales@teknos.fi