

Machine Specification | EXTERNAL USE

Motor Wattage:	2800 Watt (2x 1400 Motors)
Water Lift:	110"
Air Flow Movement:	7,166 LPM
Cyclonic Entry Port:	50mm
Container:	45 Litre
Weight:	17.2kg
Decibel Level:	74 dB
Mains Connection:	240V
Dimensions (cm):	50(l) x 50(w) x 78(h)



Clamped Pole



POLE TYPE:	CLAMPED
Material:	Carbon Fibre/ Fibre Glass Hybrid
Weight per 1.5m:	350g
Diameter:	50mm
Length:	1.5m
Reach:	4 Storeys / 12m / 40ft

Packages include

• 1.5M Suction Poles (50mm) • 1 x Vac Release Cuff • 1 x Anti-Block Hairpin Neck tool holder • 5M Wire Reinforced 50mm Suction Hose
• 5 x Gutter End tools • 2 x Cuffs • skyVac® Pole & tools Carry Case

Floor Tool kit: 3 x Brush Heads 1) Carpet 2) Hard floor 3) Water pick up. Handle (3 sections)

Available with 4, 6, or 8 poles



Vac Release Cuff

Hairpin Neck
Tool Holder

Patent Pending
No: GB1713830.6

EU Registered Design
No: 008458913

Key Features



Steel Filter
Protection Plate



Blow Function



Removable
Washable Filter



Carbon Fibre / Fibre
Glass Hybrid



4 x Multi Directional
Castor Wheels