

skyVac INDUSTRIAL 85

Wet & Dry Industrial Gutter Vacuum

Machine Specification | EXTERNAL USE

Motor Wattage:	3300 Watt (3x 1100 Motors)
Water Lift*:	150"
Air Flow Movement*:	10,000 LPM
Cyclonic Entry Port:	50mm
Container:	78 Litre
Weight:	36kg
Decibel Level:	72 dB
Mains Connection:	240V @ 13amp/ 110V @ 32amp
Dimensions (cm):	60(l) x 64(w) x 114(h)

*Unique patented "Power Mix" adapts the Air Flow and Inch Water Lift to suit cleaning conditions.
†Fast Cleaning: 10,000 LPM / 95" Water Lift. / Stubborn Blockages: 8,600LPM / 150" Water Lift


**150"
WATER LIFT**
10,000 LITRES
PER MINUTE



skyVac ELITE Clamped Pole



POLE TYPE:	CLAMPED
Material:	Carbon Fibre
Weight per 1.5m:	280g
Diameter:	50mm
Length:	1.5m
Reach:	12m/40ft



Elite Suction Pole

Vac Release Cuff

Hairpin Neck Tool Holder

Patent Pending
No: GB1713830.6

EU Registered Design
No: 008458913

Package include

- 1.5M skyVac® Elite Suction Poles (50mm) · 1 x Vac Release Cuff · 1 x Anti-Block Hairpin Neck tool holder
- 7.5M Wire Reinforced 50mm Suction Hose · 5 x Gutter End tools. 2 x Cuffs · skyVac® Pole & tools Carry Case

Available with 4, 6, or 8 poles

Key Features



Power Mix:
Dual Power
Settings



3 Powerful
Motors



Drain Hose



Sieve Basket



Tilting Chassis



Carbon
Fibre Poles