

Page 1/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Trade name QP 100 KOMP A

Article number: 6890

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating

Uses advised against No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited
Postfach 1255 Unit B1 The Fleming Centre
D-49624 Löningen / Germany West Sussex RH10 9NN
Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010
Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

#### 1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## **Hazard pictograms**





GHS07 GHS09

## Signal word Warning

## Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
(Contd. on page 2)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 1)

bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)

1,6 hexandiglycidylether

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Pine oil

#### Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:			
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-80%	
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	10-20%	
	1,6 hexandiglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-20%	
CAS: 3101-60-8 EINECS: 221-453-2	p-tert-butylphenyl 1-(2,3-epoxy)propyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥5-<10%	
CAS: 94266-48-5 EC number: 304-455-9	Pine oil Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.1-<0.25%	

Additional information For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

#### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing In case of prolonged discomfort, see a doctor.

(Contd. on page 3)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 2)

## 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

## Suitable extinguishing agents

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Use fire fighting measures that suit the environment.

## 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

### 5.3 Advice for firefighters

#### **Protective equipment:**

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

Wear full protective suit.

#### Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter drains.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures Not required.

#### 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

## 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

## 7.2 Conditions for safe storage, including any incompatibilities

### Storage

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

## Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Store dry.

Store cool.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

Additional information about design of technical systems: No further data; see item 7.

#### 8.1 Control parameters

## Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

(Contd. on page 4)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 3)

#### 8.2 Exposure controls

## Personal protective equipment

## General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

#### Respiratory equipment:

Only during spraying without adequate removal by suction.

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tightly sealed safety glasses. **Body protection:** Protective work clothing.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and ch General Information Appearance:	emical properties
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Not determined >200 °C
Flash point:	101 °C
Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	>300 °C
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not self-igniting.
Explosive properties:	Product is not explosive.
Explosive Limits:	
Lower:	Not determined.
Upper:	Not determined.

(Contd. on page 5)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 4)

	, , ,	
Vapour pressure at 20 °C:	<1.0 hPa	
Density at 20 °C:	1.154 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
Distribution coefficient (n-octanol/water): Not determined.		
Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
Solvent separation test	< 3 %	
Organic solvents:	0.0 %	
9.2 Other information	No further relevant information available.	

## **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:			
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)			
Oral	LD50	>10,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
CAS: 3101-60-8 p-tert-butylphenyl 1-(2,3-epoxy)propyl ether			
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	6,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	3,466 mg/l (rat)	

#### Skin corrosion/irritation:

Causes skin irritation.

#### Serious eye damage/irritation:

Causes serious eye irritation.

Sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met. **STOT-single exposure:** Based on available data, the classification criteria are not met. **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 5)

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects: Remark: Toxic for fish

Additional ecological information:

**General notes:** 

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

#### Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

#### Uncleaned packaging:

### Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

## SECTION 14: Transport information

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)))

(Contd. on page 7)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 6)

	(Contd. of page 6)
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9
IMDG, IATA	
Class Label	<ul><li>9 Miscellaneous hazardous substances and articles.</li><li>9</li></ul>
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and articles.
hazard identification number:	90
EMS Number: Stowage Category	F-A,S-F A
14.7 Transport in bulk according to Annex	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700))), 9, III

(Contd. on page 8)

Printing date 28.03.2019 Version number 2 Revision: 28.03.2019

## Trade name QP 100 KOMP A

(Contd. of page 7)

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

## **Department issuing data specification sheet:** Product Safety department / EHS **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3